



### PROJECT LOCATION AERIAL VIEW - 2D




PROJECT LOCATION MAP





PROJECT LOCATION - CITY OF PHILADELPHIA MAP



# CITY OF PHILADELPHIA DEPARTMENT OF PARKS and RECREATION

MAYOR – JAMES F. KENNEY

**ARCHITECT:** 

MANAGING DIRECTOR — TUMAR ALEXANDER REBUILD EXECUTIVE DIRECTOR — KIRA STRONG

DISSTON RECREATION CENTER - UPGRADES 4423 LONGSHORE AVE, PHILADELPHIA, PA 19135 PROJECT NO. 16228E-03-01 CWA-1909.01

**BUILDING ENVELOPE:** 

	CONVERSE WINKLER ARCHITECTURE, LLC. 331 MONTGOMERY AVE BALA CYNWYD, PA 19004 610-664-0806		DELWARE AVE, SUITE 507 622 COOPER STREET, SUITE 200 PHIA, PA 19125 CAMDEN, NJ 08102	ARCHITECTURAL LIGHTING DESIGN 340 TENNIS AVE AMBLER, PA 19002 610-449-4049
	PROJECT SCOPE	DRAWING LIST		PROJECT APPROVED
	DISSTON RECREATION CENTER UPGRADES PROJECT INCLUDES:	G-000 COVER SHEET G-001 GENERAL INFORMATION G-002 CODE ANALYSIS	A-411 INTERIOR MULTIPURPOSE ROOM . ELEVS & DTLS	COMMISSIONER/DEPARTMENT OF RECREATION
	ENVELOPE	G-003 SITE/STAGING PLAN	A-601 FIRST & SECOND FLOOR RCP A-602 LIGHTING FIXTURE SCHEDULE	DEPUTY COMMISSIONER/DEPARTMENT OF RECREATION
	<ol> <li>MASONRY RESTORATION OF BUILDING AND SITE RETAINING WALLS.</li> <li>FULL REPLACEMENT OF EXISTING EIFS</li> </ol>	D-101 PARTIAL BASEMENT, FIRST & SEC FLOORS DEMO PLANS	OND A-701 WINDOW SCHEDULE & DETAILS	PROJECT DIRECTOR
	ROOF CORNICE WITH NEW GFRC CORNICE.	D-102 FIRST & SECOND FLOOR RCP DEMO PLANS D-103 ROOF DEMO PLAN	A-702 WINDOW & LOUVER DETAILS A-703 DOOR SCHEDULE & DETAILS A-704 DOOR DETAILS	
	<ol> <li>REPLACEMENT OF EXISTING ROOFS.</li> <li>WINDOW REPLACEMENT.</li> </ol>	D-201 DEMO ELEVATIONS D-202 DEMO ELEVATIONS	A-705 FINISH SCHEDULES  A-706 ENTRANCE FLOOR GRILLES DETAILS	
	<ul><li>5. ACCESSIBLE REAR ENTRY.</li><li>6. EXTERIOR AND INTERIOR DOOR</li></ul>	A-101 PARTIAL BASEMENT, FIRST & SEC		
	REPLACEMENT.  7. REPLACEMENT OF FIRE ESCAPE WITH EXTERIOR STAIRWAY.	FLOOR PLANS A-102 ROOF PLAN	A-902 FIRE ESCAPE DETAILS  MECHANICAL	· · · · · · · CONVERSE · WINKLER
	8. RENOVATION OF EXISTING PUBLIC RESTROOMS ON THE FIRST FLOOR.  9. ADDITION OF A UNISEX WHEEL CHAIR	A-201 BUILDING ELEVATIONS A-202 BUILDING ELEVATIONS	M-0.0 MECHANICAL SYMBOLS, ABBREVIATIONS & GENERAL NOTES	ARCHITECTURE
	ACCESSIBLE RESTROOM ON THE FIRST FLOOR.  10.INTERIOR WALL AND CEILING	A-203 BUILDING ELEVATIONS A-204 SITE WALL ELEVATIONS (ADD/ALT A-205 SITE WALL ELEVATIONS (ADD/ALT	1) M-1.1 MECHANCIAL PARTIAL BASEMENT &	331 MONTGOMERY AVENUE, BALA CYNWYD, PA 19004 T: 610-664-0806 F:610-664-1075
	UPGRADES. 11.RESTORATION OF FLOOR FINISHES IN	A-301 PEDIMENT/CORNICE ELEVATIONS A-302 CORNICE TYPES	M-2.1 MECHANICAL SCHEDULES & DETAILS M-2.2 MECHANICAL SCHEDULES	
	THE PUBLIC SPACES ON FIRST AND SECOND FLOORS.  12.REPLACEMENT OF MAIN STAIR	A-302 CORNICE TIFES  A-303 CORNICE & GUTTER DETAILS  A-304 ROOF DETAILS - MAIN & GYM	PLUMBING	SEALS
9	RAILING. 13.REPAIRS TO EXISTING BOILER &	A-305 ROOF DETAILS - LINK A-306 ROOF DETAILS	P-0.0 PLUMBING COVER SHEET P-1.0 PLUMBING PARTIAL FLOOR PLAN P-1.1 PLUMBING DIAGRAMS AND SCHEDULES	
	STEAM RADIATOR HEATING; UPGRADES TO GYM AIR HANDLING SYSTEM.	A-307 ROOF DETAILS A-308 ROOF DETAILS A-309 ROOF DETAILS	P-2.0 PLUMBING DETAILS	
3	14.INSTALLATION OF SPLIT—UNIT AC OFFICES AND ACTIVITY SPACES 15.UPGRADES TO INTERIOR AND	A-310 MASONRY REPAIR DETAILS	ELECTRICAL E-0.0 ELECTRICAL LEGEND & GENERAL NOTES	
2	ELECTRIC LIGHTING AND LIGHTING CONTROLS (NOT INCLUDING GYM	A-401 FIRST FLOOR ACCESSIBLE TOILET UTILITY ROOM PLANS	E-I.I FIRST FLOOR PLAN LIGHTING NFW WORK PLAN	CITY OF PHILADELPHIA
	INTERIOR AND BASEMENT).	A-402 FIRST FLOOR MEN'S/WOMEN'S TO ROOM PLANS	E-1.2 FIRST FLOOR PLAN POWER - NEW WORK F-2.0 SECOND FLR PLAN LIGHTING -	DEPARTMENT OF PUBLIC PROPERTY
		A-403 FIRST FLOOR TOILET ROOM ELEVA A-404 FIRST FLOOR TOILET ROOM DETAI A-405 INTERIOR LOBBY AREA ELEVS	DEMOLITION AND NEW WORK  LS E-2.1 SECOND FLOOR PLAN POWER — NEW WORK	1515 ARCH STREET  11TH FLOOR, ONE PARKWAY BUILDING  PHILADELPHIA  PENNSYLVANIA
		A-406 INTERIOR LOBBY AREA ELEVS A-407 INTERIOR STAIR DETAILS	E-3.0 ROOF PLAN POWER - NEW WORK	PROJECT NO. DRAWING NO. CW-1909.01
		A-408 INTERIOR STAIR DETAILS A-409 INTERIOR STAIR DETAILS A-410 DOOR DETAILS		DATE 09/09/2022 SCALE
		A-410 DOOR DETAILS		G-000

**STRUCTURAL ENGINEER:** 

MECHANICAL/PLUMBING ENGINEERS:

**LIGHTING CONSULTANT:** 

G-000

ALL DIMENSIONS AND CONDITIONS SHALL BE VERIFIED BY THE CONTRACTOR AT THE SITE BEFORE PROCEEDING WITH THE WORK.

CHECKED BY PD, MCW

BID SET - 09-09-2022

CONSTRUCTION JOINT

BLDG BLKG BO BOD CBU CH BOTTOM OF BASIS OF DESIGN CEMENTITIOUS BACKER UNIT CEILING HEIGHT CAST IRON

CL CLNG CLOSET CEILING CONCRETE MASONRY UNIT CONCRETE

CJ

FEC

CMU CONC CONT CT DF CONTINUOUS CERAMIC TILE DRINKING FOUNTAIN DIA DIM DN DO DWG DIAMETER DIMENSION DOWN DOOR OPENING DRAWING ELEC ELEV **ELECTRICAL ELEVATION ENAM** ENAMEL (BAKED)

EQ **EQUAL** EXISTING TO REMAIN ETR EXIST, **EXISTING** EXP J **EXPANSION JOINT** EXTERIOR FIBER CEMENT FLOOR DRAIN

FLOOR FINISH FIBERGLASS REINFORCED PLASTIC

FIRE EXTINGUISHER CABINET

FIN FRP GA GC GEN GFRC GAUGE GENERAL CONTRACTOR **GENERAL** 

GLASS FIBER REINFORCED CONCRETE GWB GYPSUM WALL BOARD HDPE HIGH DENSITY POLYETHYLENE HDWD HARDWOOD

НМ HOLLOW METAL HP HIGH POINT HR HOUR

HSS HOLLOW STRUCTURAL SECTION

HVAC HEATING, VENTILATION & AIR CONDITIONING INT INTERIOR IBC INTERNATIONAL BUILDING CODE JANITOR CLOSET

JOINT LAV LOC LAVATORY LOCATION LVL MECH LEVEL

**MECHANICAL** MEP MECHANICAL, ELECTRICAL, AND PLUMBING MGO MAGNESIUM OXIDE (PANEL BOARD)

MTL METAL NA OCC OPNG NOT APPLICABLE OCCUPANTS OPENING OPPOSITE OCCUPANCY SENSOR

PANEL JOINT **PLYWD** PLYWOOD PAINT RB RUBBER BASE

RCP REFLECTED CEILING PLAN REQ/ REQD REQUIRED

RMROOM RO ROUGH OPENING RWC RAIN WATER CONDUCTOR SCHED SCHEDULE SD SMOKE DETECTOR SQUARE FOOTAGE SIM SIMILAR SS STAINLESS STEEL

TOP OF TYPICAL UNO VCT UNLESS NOTED OTHERWISE VINYL COMPOSITE TILE VIF VERIFY IN FIELD WC WATER CLOSET

WINDOW OPENING

EXTRUDED POLYSTYRENE

STORAGE

WOOD

WD

**KEY TO MATERIALS** 

COVERBOARD BATT INSULATION PLYWOOD **RESINOUS FLOORING** 


**RIGID INSULATION** STONE


CONCRETE STEEL


SHIM


WOOD BLOCKING

**SYMBOLS** 














**REVISION SYMBOL** 

**KEYNOTE - CONSTRUCTION** 









**EXISTING DOOR** 

DEMOLITION ITEM




DOOR



FLOOR DRAIN





### **GENERAL NOTES**

#### THE FOLLOWING NOTES APPLY TO ALL DRAWINGS:

- 1. CONTRACTOR SHALL COORDINATE ALL DEMOLITION ACTIVITIES WITH REBUILD/PPR/ TENANT.
- 2. PROTECT ALL EXISTING MATERIALS THROUGH ENTIRE DURATION OF CONSTRUCTION.
- 3. COORDINATE WITH REBUILD/PPR FOR REMOVAL OF EXISTING LIGHT FIXTURES AND ELECT PANELS AND ASSOCIATED SHUT OFFS.
- 4. COORDINATE WITH REBUILD/PPR FOR WORK RESTRICTIONS, WORK TIME RESTRICTIONS AND BUILDING SECURITY.
- 5. ALL ROOFS ARE TO BE MAINTAINED IN WATERTIGHT CONDITION FROM START OF DEMOLITION UNTIL NEW WORK IS COMPLETE.
- 6. CONTRACTOR SHALL COORDINATE ALL GROUND OPERATIONS, INCLUDING LOCATIONS FOR EQUIPMENT SETUP, MATERIAL STORAGE, DEBRIS STORAGE AND REMOVAL, ETC., WITH REBUILD/PPR/TENANT.
- 7. CONTRACTOR SHALL PROTECT ALL BUILDING EXITS AND SIDEWALKS FROM OVERHEAD ROOF WORK.
- 8. CONTRACTOR SHALL COORDINATE REMOVAL/MAINTENANCE/ RELOCATION OF ROOF LIGHTS, ANTENNA, SATELLITE & CAMERAS WITH REBUILD/PPR/TENANT.
- 9. ALL DETAILS SHALL INCORPORATE MANUFACTURER'S RECOMMENDATIONS AND REQUIREMENTS FOR WARRANTY APPROVAL
- 10. ALL NOTES REFER TO NEW WORK UNLESS DESIGNATED (E) EXISTING OR NOTED 'EXIST'.
- 11. ALL DETAILS, INSTRUCTIONS, NOTES, FINISHES, MATERIALS AND DIMENSIONS SHALL BE CONSIDERED TYPICAL FOR SIMILAR CONDITIONS, UNLESS NOTED OTHERWISE.
- 12. CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS AND REPORT ALL DISCREPANCIES TO REBUILD/PPR OR ARCHITECT.

# **ADDITIONAL NOTES**

- 1. THE CONTRACTOR SHALL EXAMINE THE SITE AND VERIFY EXISTING CONDITIONS INCLUDING FLOOR, CEILING AND WALL CONSTRUCTION, STRUCTURAL MEMBERS, AND THE LOCATION OF UTILITIES. ANY INCONSISTENCIES SHALL BE BROUGHT TO THE ARCHITECT'S IMMEDIATE ATTENTION FOR RESOLUTION.
- 2. THE CONTRACTOR IS RESPONSIBLE FOR LAYOUT AND VERIFYING ALL DIMENSIONS. INCLUDING BOTH EXISTING AND NEW WORK, PRIOR TO CONSTRUCTION. ANY DISCREPANCIES SHALL BE BROUGHT TO THE ARCHITECT'S IMMEDIATE ATTENTION FOR RESOLUTION. DO NOT SCALE DRAWINGS.
- 3. THE CONTRACTOR SHALL NOTIFY THE ARCHITECT OF ANY INCONSISTENCY BETWEEN THESE PLANS AND GOVERNING BUILDING CODES AND ORDINANCES. ALL WORK SHALL BE DONE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE, AND LOCAL CODES, AND MANUFACTURER'S SPECIFICATIONS.
- 4. ALL DETAILS, INSTRUCTIONS, NOTES, FINISHES, MATERIALS SIMILAR CONDITIONS, UNLESS NOTED OTHERWISE.
- 5. ALL NOTES DESCRIBE NEW CONSTRUCTION UNLESS STATED OTHERWISE. ALL WORK SHOWN IS NEW UNLESS SHOWN IN A SCREENED LINE OR NOTED AS EXISTING.
- 6. RESPONSIBILITY DEFINITIONS: FURNISH: SUPPLY AND DELIVER TO PROJECT SITE, READY FOR UNLOADING, UNPACKING, ASSEMBLY, INSTALLATION, AND SIMILAR OPERATIONS. **INSTALL**: PERFORM OPERATIONS AT SITE INCLUDING UNLOADING, TEMPORARY STORING, UNPACKING, ASSEMBLING, ERECTING, PLACING, CONNECTING, ANCHORING, APPLYING, WORKING TO DIMENSION, FINISHING, CURING, PROTECTING. CLEANING, AND SIMILAR OPERATIONS. PROVIDE: FURNISH AND INSTALL, COMPLETE AND READY FOR THE INTENDED USE. ALL ITEMS ARE TO BE PROVIDED BY THE CONTRACTOR

UNLESS NOTES OTHERWISE.

- 7. DEMOLITION DEFINITIONS: REMOVE: DETACH ITEMS FROM EXISTING CONSTRUCTION AND DISPOSE OF THEM OFF-SITE UNLESS INDICATED TO BE
- SALVAGED. REMOVE AND SALVAGE: DETACH ITEMS FROM EXISTING CONSTRUCTION IN A MANNER TO PREVENT DAMAGE AND DELIVER TO USING AGENCY READY TO REUSE OR STORE AS INDICATED ON DRAWINGS. INCLUDE FASTENERS OR BRACKETS NEEDED FOR REATTACHMENT ELSEWHERE. REMOVE AND REINSTALL: DETACH ITEMS FROM EXISTING CONSTRUCTION, PREPARE THEM FOR REUSE, AND REINSTALL THEM WHERE INDICATED. EXISTING TO REMAIN: EXISTING ITEMS OF CONSTRUCTION THAT ARE NOT TO BE REMOVED AND THAT ARE NOT OTHERWISE INDICATED TO BE REMOVED, REMOVED AND SALVAGED, OR REMOVED AND REINSTALLED.


### **DEMO GENERAL NOTES**

THE FOLLOWING NOTES APPLY TO ALL DEMO DRAWINGS:

- 1. NOT ALL DEMOLITION WORK REQUIRED IS REFERENCED IN ARCHITECTURAL DRAWINGS. COORDINATE ALL DEMO WORK WITH REQUIREMENTS OF NEW CONSTRUCTION, ALL TRADES.
- 2. COORDINATE WITH OWNER FOR REMOVED ACCESSORIES, PLUMBING FIXTURES, LIGHTING FIXTURES, CEILING DEVICES, TOILET PARTITIONS, AND SIGNAGE TO BE SALVAGED.
- 3. ALL EXIST ITEMS TO REMAIN UNLESS NOTED OTHERWISE
- 4. KEY NOTES ARE TYPICAL FOR ALL SIMILAR SHOWN ITEMS UNLESS NOTED OTHERWISE
- 5. CLEAN/PATCH/REPAIR/FINISH ALL SURFACES TO REMAIN AT LOCATIONS OF DEMOLITION/MATERIAL REMOVAL

**APPROVED:** ARCHITECT/ENGINEER OF RECORD DATE **APPROVED FOR BID:** 

**REBUILD PROJECT MANAGER** DATE CONVERSE **WINKLER ARCHITECTURE** 



DATE DESCRIPTION REVISION

> **DISSTON REC CENTER UPGRADES**

Sheet Title:

**GENERAL INFORMATION** 

100% SUBMISSION RAVIKUMAR JETHANI

**CONVERSE WINKLER ARCHITECTURE** 09/09/2022 PD, MCW

16228E-03-01 CW-1909.01

G-001

rawing No.:

**BID SET - 09-09-22** Sheet No.: 2

63

ASCE 7-16

#### LATERAL LOAD DESIGN SCHEDULE

SNOWLOADS		
GROUND SNOW LOAD	Pg	25 psf
FLAT-ROOF SNOW LOAD	Pf	17.5 psf
EXPOSURE FACT OR	Ce	1.0
THERMAL FACTOR	Ct	1.0
IMPORTANCE FACTOR	ls	1.0
MINIMUM SNOW LOAD FOR LOW-SLOPE ROOFS	Pm	20 psf
SLOPED ROOF SNOW LOAD	Ps	17.5 psf
ROOF SLOPE FACTOR	Cs	1.0
DRIFT SURCHARGE LOAD(S)	Pd	37.82 psf
WIDTH OF SNOW DRIFT (gymnasium to Link)	w	8.77 ft
Ps + Pd	= P1	55.32 psf
SEISMIC LOADS		
SEISMIC IMPORTANCE FACTOR	le	1.0
MAPPED SPECTRAL RESPONSE ACCELERATIONS	Ss	0.2
	S1	0.06

SEISMIC DESIGN CATEGORY BASIC SEISMIC-FORCE RESISTING SYSTEM: DETAILED PLAIN MASONRY SHEAR WALL SEISMIC RESPONSE COEFFICIENT Cs 0.1065 DESIGN SEISMIC BASE SHEAR V 0.1065W

SHORT PERIOD SDS

1-SEC. PERIOD SD1

0.213

0.096

SITE CLASS

DESIGN SPECTRAL RESPONSE COEFFICIENTS

RESPONSE MODIFICATION FACTOR


EFFECTIVE SEISMIC WEIGHT TO BE DETERMINED

WIND LOAD		
DESCRIPTION	SYMBOL	VALUE
RISK CATEGORY	-	II
BASIC WIND SPEED (3-sec. gust)	V	115 mph
INTERNAL PRESSURE COEFFICIENT	GCpi	<del>+/</del> - 0.18
EXPOSURE CATEGORY		В
WIND IMPORTANCE FACTOR		1
MAIN WINDFORCE RESISTING SYSTEM		
MINIMUM DESIGN WIND PRESSURE FOR WALL		16 psf
MINIMUM DESIGN WIND PRESSURE FOR ROOF		8 psf

### COMPONENTS AND CLADDING - NOMINAL DESIGN WIND PRESSURE

		T RIBUT ORY AREA				
AREA	ZONE	10 SF	20 SF	50 SF	100 SF	
ROOF	1	+21.341/-39.125	+18.962/-33.177	+15.816/-25.314	+13.437/-19.365	
ROOF	2	+21.341/-39.125	+18.962/-33.177	+15.816/-25.314	+13.437/-19.365	
ROOF	3	+21.341/-39.125	+18.962/-33.177	+15.816/-25.314	+13.437/-19.365	
WALL	4	+23.317/-25.293	+22.267/-24.243	+20.878/-22.854	+19.828/-21.804	
WALL	5	+23.317/-31.221	+22.267/-29.121	+20.878/-26.344	+19.828/-24.243	
	1	-47.820/-54.934	-41.872/-48.986	-34.008/-41.122	-28.061/-35.176	
ROOF	2e	-47.820/-54.934	-41.872/-48.986	-34.008/-41.122	-28.061/-35.176	
CLADDING -	2r	-47.820/-54.934	-41.872/-48.986	-34.008/-41.122	-28.061/-35.176	
OVERHANG	2n	-51.772/-58.886	-47.200/-54.314	-41.156/-48.270	-36.587/-43.701	
(MAX/MIN)	3e	-61.521/-68.635	-55.507/-62.621	-47.557/-54.671	-41.547/-48.661	
	3r	-51.772/-58.886	-47.200/-54.314	-41.156/-48.270	-36.587/-43.701	

WIND LOADS IN THE SCHEDULE ARE PROVIDED AS ULTIMATE DESIGN WIND PRESSURE



#### 2018 IBC: TABLE 2902.1 MINIMUM NUMBER OF REQUIRED PLUMBING FIXTURES IN PROPOSED AREA OF WORK

OCCUPANCY TYPE	NO OF OCCUPANTS	WC/ URINALS	REQ'D	LAV REQ'D		DRINKING FOUNTAIN
ASSEMBLY (A3)	240	MALE 1 PER 125	FEMALE 1 PER 65	MALE 1 PER 200	FEMALE 1 PER 200	1 PER 500
		1	2	1	1	1
BUSINESS	6	MALE 1 PER 25	FEMALE 1 PER 25	MALE 1 PER 40	FEMALE 1 PER 40	1 PER 100
		1	1	1	1	1
	TOTALS REQUIRED	2	3	2	2	
	EXISTING TOTALS	3, 1 (UNISEX)	2, 1 (UNISEX)	1, 1 (UNISEX)	2, 1 (UNISEX)	1
	PROPOSED TOTALS	3, 2 (UNISEX)	2, 2 (UNISEX)	2, 2 (UNISEX)	2, 2 (UNISEX)	2

#### TOILET ROOMS

#### 2018 IEBC 305.8.10 TOILET ROOMS

WHERE IT IS TECHNICALLY INFEASIBLE TO ALTER EXISTING TOILET & BATHING ROOMS TO BE ACCESSIBLE AN ACCESSIBLE FAMILY OR ASSISTED-USE TOILET IS PERMITTED. THE FAMILY/ ASSISTED USE TOILET SHALL BE LOCATED ON THE SAME FLOOR AND IN THE SAME AREA AS THE EXISTING TOILET.

#### 2018 IBC 1109.2 TOILET & BATHING FACILITIES

EACH TOILET ROOM SHALL BE ACCESSIBLE

2018 IBC 1109.2.2 WATER CLOSET COMPARTMENT

5% OF WC COMPARTMENTS SHALL BE WHEEL CHAIR ACCESSIBLE

2018 IBC 1109.2.3 LAVATORY 5%, NOT LESS THAN ONE, LAVATORY SHALL BE ACCESSIBLE

2018 IBC 2902.1.2 SINGLE USER TOILET ROOMS

SHALL CONTRIBUTE TOWARDS THE TOTAL NO OF PLUMBING FIXTURES REQUIRED. SHALL BE IDENTIFIED FOR USE BY EITHER SEX

### 2018 IBC 2902.3.3 LOCATION OF TOILET

SHALL BE LOCATED NOT MORE THAN ONE STORY ABOVE OR BELOW THE SPACE REQUIRED TO BE PROVIDED WITH TOILET FACILITY. MAX TRAVEL DISTANCE SHALL NOT EXCEED 500 FEET.

2018 IPC 405.3.1 WATER CLOSETS, URINALS, LAVATORIES, BIDETS

FIXTURES SHALL NOT BE SET CLOSER THAN 30" CENTER TO CENTER MIN CLEARANCE IN FRONT OF URINAL/ WC SHALL NOT BE LESS THAN 21" WATER CLOSET COMPARTMENTS SHALL NOT BE LESS THAN 30" IN WIDTH & NOT LESS THAN 60" IN DEPTH FOR FLOOR MOUNT WC WATER CLOSET COMPARTMENTS SHALL NOT BE LESS THAN 30" IN WIDTH & NOT LESS THAN

#### 2018 IPC 405.3.5 URINAL PARTITION

56" IN DEPTH FOR WALL MOUNT WC

THE HORIZONTAL DISTANCE BETWEEN PARTITIONS SHALL NOT BE LESS THAN 30" THE PARTITION HEIGHT SHALL NOT BE MORE THAN 12" AND SHALL EXTEND TO A MIN OF 60" ABOVE THE FINISHED FLOOR PARTITION SHALL EXTEND A MIN OF 18" FROM WALL TO A POINT NOT LESS THAN 6" BEYOND THE OUTER MOST LIP OF URINAL

#### IEBC ALTERATIONS LEVEL 1 AND 2

#### 208 IEBC 305.6 ALTERATIONS.

A FACILITY THAT IS ALTERED SHALL COMPLY WITH IBC CHAPTER 11 TO THE EXTENT TECHNICALLY FEASIBLE EXCEPTIONS:

(1) THE ALTERED ELEMENT OF SPACE IS NOT REQUIRED TO BE ON AN ACCESSIBLE ROUTE UNLES REQUIRED BY IEBC SECTION 305.7. I.E. DOES NOT EFFECT THE PRIMARY FUNCTION, OR THE COSTS OF PROVIDING AN ACCESSIBLE ROUTE EXCEED 20% OF THE COSTS DEDICATED TO THE ALTERATION AFFECTING THE AREA OF PRIMARY FUNCTION

(2) ACCESSIBLE MEANS OF EGRESS REQUIRED BY IBC CHAP 10 ARE NOT REQUIRED TO BE PROVIDED IN EXISTING FACILITIES.

#### 2018 IEBC C503 ALTERATIONS

C 503.1 ALTERATIONS SHALL BE SUCH THAT THE EXISTING BUILDING IS NOT LESS CONFORMING TO THIS CODE THAN THE BUILDING WAS PRIOR TO ALTERATION

#### 2018 IEBC 705 REROOFING

705.1 ROOF REPLACEMENT OF LOW SLOPE ROOFS SHALL NOT BE REQUIRED TO MEET MIN DESIGN SLOPE REQUIREMENT OF 2%.

REPLACING OF AN EXISTING ROOF SHALL NOT BE REQUIRED TO MEET THE REQUIREMENT FOR SECONDARY DRAINS OR SCUPPERS. EXISTING SECONDARY DRAINS OR SCUPPERS SHALL NOT BE REMOVED UNLESS THEY ARE REPLACED BY NEW.

705.2 STRUCTURAL ROOF COMPONENTS SHALL BE CAPABLE OF SUPPORTING THE ROOF COVERING SYSTEMS AND THE MATERIAL AND EQUIPMENT LOADS THAT WILL BE ENCOUNTERED DURING INSTALLATION

705.3 ROOF REPLACEMENT SHALL INCLUDE REMOVAL OF ALL EXISTING LAYERS OF ROOF COVERING DOWN TO THE ROOF DECK

705.6 FLASHINGS SHALL BE RECONSTRUCTED WITH APPROVED MANUFACTURER'S INSTALLATION INSTRUCTIONS. METAL FLASHING TO WHICH BITUMINOUS MATERIALS ARE TO BE ADHERED SHALL BE PRIMED PRIOR TO INSTALLATION

#### 2018 IEBC 705 STRUCTURAL

706.2 ANY EXISTING GRAVITY LOAD-CARRYING STRUCTURAL ELEMENT FOR WHICH AN ALTERATION CAUSES AN INCREASE IN DESIGN DEAD, LIVE OR SNOW LOAD, INCLUDING SNOW DRIFT EFFECTS, OF MORE THAN 5% SHALL BE REPLACED OR ALTERED AS NEEDED TO CARRY THE GRAVITY LOADS REQUIRED BY IBC FOR NEW STRUCTURES

#### 2018 IEBC 707 ENERGY CONSERVATION

LEVEL 1 ALTERATIONS DO NOT REQUIRE THE ENTIRE BUILDING TO COMPLY WITH THE REQUIREMENTS OF THE INTERNATIONAL ENERGY CONSERVATION CODE. THE ALTERATIONS SHALL CONFORM TO THE ENERGY REQUIREMENTS OF THE IECC AS THEY RELATE TO NEW CONSTRUCTION

#### 2018 IEBC 802 BUILDING ELEMENTS AND <u>MATERIALS</u>

802.4 INTERIOR FINISHES OF WALLS AND CEILINGS IN EXITS AND CORRIDORS IN ANY WORK AREA SHALL COMPLY WITH IBC REQUIREMENTS EXCEPT EXISTING MATERIALS THAT DO NOT COMPLY SHALL BE TREATED WITH AND APPROVED

## CODE OVERVIEW

2018 INTERNATIONAL BUILDING CODE **GOVERNING CODES:** 2018 INTERNATIONAL MECHANICAL CODE 2018 INTERNATIONAL EXISTING BUILDING CODE 2017 NATIONAL ELECTRIC CODE (PER 2018 IBC) 2018 INTERNATIONAL PERFORMANCE BUILDING CODE 2018 INTERNATIONAL ENERGY CONSERVATION CODE 2009 INTERNATIONAL FIRE CODE 2018 INTERNATIONAL FUEL GAS CODE

2009 ICC A117.1 ACCESSIBLE AND USABLE BUILDING AND FACILITIES

PENNSYLVANIA DEPARTMENT OF LABOR AND INDUSTRY **REVIEWING AGENCY:** 

DISSTON RECREATION CENTER ADDRESS: 4423 LONGSHORE AVENUE

PHILADELPHIA, PA **CONSTRUCTION DATE:** 1931

NO OF FLOORS: 2 + BASEMENT **USE AND OCCUPANCY**: ASSEMBLY, A3

SPRINKLERED:

**BUILDING AREA:** BASEMENT: 7860 GROSS SF LEVEL 1: 7580 SF LEVEL 2: 2880 SF

TOTAL: 18,320 GROSS SF BASEMENT: 0 GROSS SF

LEVEL 1: 3,480 GROSS SF LEVEL 2: 2,390 GROSS SF TOTAL: 5.879 GROSS SF (<50% BUILDING AREA)

CONSTRUCTION TYPE: IIB (IBC TABLE 601)

**BUILDING OCCUPANTS:** 246 FLOOD HAZARD AREA:

PROJECT WORK AREA:

CLIMATE ZONE: 4A (IECC TABLE C301.1)

#### 2018 IBC TABLE 1004.5 OCCUPANT LOAD CALCULATION

#### **BASEMENT**

APPLICABLE IBC PROVISIONS

2018 IBC CHAP 8 INTERIOR FINISHES

LOBBY AREAS: CLASS 'B'

THAN THE FOLLOWING:

GRADE PLANE.

GRADE PLANE.

ACCESSIBLE LEVELS

803.13 INTERIOR WALL AND CEILING FINISHES

HAVE A FLAME SPREAD INDEX NOT GREATER

FOR OCCUPANCY A-3 NONSPRINKLERED SHALL

ROOMS & ENCLOSED SPACES: CLASS 'C'

804.1 FLOOR FINISHES OF A TRADITIONAL TYPE

RESILIENT FLOOR COVERINGS THAT ARE NOT

COMPOSED OF FIBERS ARE NOT RESTRICTED

BY TESTING REQUIREMENTS OF THIS SECTION.

806.7 INTERIOR TRIM SHALL HAVE A MINIMUM

SUCH AS WOOD, VINYL, LINOLEUM...AND

CLASS 'C' FIRE RATING AND SHALL NOT

2018 IBC 1027 EXTERIOR EXIT STAIRWAYS

1027.2 EXTERIOR EXIT STAIRWAY SHALL BE

REQUIRED MEANS OF EGRESS FOR BUILDINGS

1027.6 SEPARATION FROM THE INTERIOR OF

OCCUPANCIES OTHER THAN R-1 OR R-2 IN

STORIES ABOVE THE GRADE PLANE WHERE A

BUILDINGS THAT ARE NOT MORE THAN 2

LEVEL OF DISCHARGE IS SERVING SUCH

OCCUPANCIES IS THE FIRST STORY ABOVE

PERMITTED AS AN ELEMENT OF THE A

THE BUILDING IS NOT REQUIRED IN

2018 IBC 1104 ACCESSIBLE ROUTE

1104.4 AN ACCESSIBLE ROUTE IS NOT

REQUIRED TO STORIES...THAT HAVE AN

AGGREGATE AREA OF NOT MORE THAN 3000

SF AND ARE LOCATED ABOVE AND BELOW

NOT EXCEEDING SIX STORIES ABOVE THE

EXCEED 10% OF THE WALL AREA.

SPACE	AREA	OCCUPANCY	OCCUPANT LOAD	NO OF OCCUPANTS
ACCESSORY STORAGE ACCESSORY MECHANICAL	3600 SF 2813 SF	S 300 M 300	GROSS GROSS	12 10 22 TOTAL
FIRST FLOOR				
OFFICE 1 OFFICE 2 BASKETBALL COURT FITNESS ROOM LOBBY SECOND FLOOR OCCUPAN	368 SF 375 SF 3134 SF 639 SF 600 SF	B 150 A3 50 ( A3 50 (	GROSS GROSS GROSS GROSS GROSS	3 63 13 12 94 TOTAL
MULTIPURPOSE ROOM ACTIVITY ROOM ACCESSORY STORAGE	1875 SF 230 SF 180 SF	A3 15 N A3 50 O S 300	NET GROSS GROSS	125 5 1

2018 IBC CHANPTER 10: MEANS OF EGRESS						
CODE SECTION	REQUIRED	PROVIDED				
1005.3	REQUIRED CAPACITY OF STAIRWAYS BASED ON OCCUPANCY LOAD = 131X.03 = 39.3"	44", 116"				
1011.2 STAIRWAYS WIDTH	NOT LESS THAN 44"	44", 116"				
1011.5.2 RISER HEIGHT & TREAD DEPTH	RISER HT = 7" TREAD DEPTH = 11"	RISER HT = 7" TREAD DEPTH = 11"				
1011.8 VERTICAL RISE	12' BETWEEN FLOOR LVLS/ LANDINGS					
1014.1 HANDRAIL HT	34"–38"	35"				
1014.6 HANDRAIL EXTENSIONS	12" BEYOND TOP RISER DEPTH OF 1 TREAD BEYOND BOTTOM RISER	YES				
1014.7 CLEARANCE	1.5" FROM WALL OR OTHER SURFACE					
1014.9 INTERMEDIATE HANDRAILS	ALL PORTIONS OF REQ'D WIDTH (44") WITHIN 30" OF HANDRAIL - 30"+44"+30"= 8'-8"	8'-5½" BETWEEN HANDRAILS				
1015.5 GUARDRAIL HT	42" MIN	42"				

APPROVED: ARCHITECT/ENGINEER OF RECORD DATE **APPROVED FOR BID:** REBUILD PROJECT MANAGER DATE CONVERSE

: ARCHITECTURE

WINKLER

REVISION DESCRIPTION DATE

### DISSTON REC CENTER **UPGRADES**

CODE **ANALYSIS** 


100% SUBMISSION RAVIKUMAR JETHANI **CONVERSE WINKLER ARCHITECTURE** DG


09/09/2022 PD, MCW 16228E-03-01 CW-1909.01 G-002


BID SET - 09-09-22 Sheet No.: 3


63


FIRE-RETARDANT COATING.















**DEMO KEY NOTES** 


SEE D-201 FOR KEYNOTES


APPROV	/ED:					
ARCHITI	ECT/ENGINEER	OF RECORD	DATE			
	/ED FOR BID:	UF NEGGRE				
	O PROJECT MA	NAGER	DATE			
Designer:	CONVERSE WINKLER ARCHITECTURE					
Seal:						
	general de la companya de la company					
Key Plan:						
			Å			
REVISION	DESCRIF	PTION	DATE			
Project:						
Sheet Title:						
DEMO ELEVATIONS						
Submisison:	100% SUB	MISSION				
Consultant: CONVERSE WINKLER ARCHITECTURE						
Task No.:	:CIUNL					
Date: <b>09/</b> (	09/2022	Checked By: PDC				
	Work No.: 16228E-03-01 CW-1909.01 Drawing No.:  Drawing No.:					


Z:\CWA Projects\CW—1909 Rebuild Philadelphia On—Call\1909.01 Disston Recreation Center\04 drawings\CAD\D201


BID SET - 09-09-22 Sheet No.: 9 of











- REMOVE DETERIORATED STONE PATCH & PROVIDE NEW. SEE DTL

APPROVED: ARCHITECT/ENGINEER OF RECORD DATE APPROVED FOR BID: REBUILD PROJECT MANAGER DATE

CONVERSE WINKLER ARCHITECTURE

DESCRIPTION


**DISSTON REC CENTER UPGRADES** 


**BUILDING ELEVATIONS** 


RAVIKUMAR JETHANI **CONVERSE WINKLER ARCHITECTURE** 09/09/2022 PDC, MCW 16228E-03-01 CW-1909.01 A-203


**100% SUBMISSION** 


BID SET - 09-09-22 Sheet No.: 14







































5 ROOF DRAIN DETAIL

4 PITCH POCKET DETAIL A308 | SCALE: 3" = 1'-0"

3 NON-PENETRATING SUPPORT BASE DETAIL A308 SCALE: 3" = 1'-0"

APPROVED: ARCHITECT/ENGINEER OF RECORD DATE APPROVED FOR BID: REBUILD PROJECT MANAGER DATE CONVERSE .: ARCHITECTURE DATE REVISION DESCRIPTION **DISSTON REC CENTER UPGRADES ROOF DETAILS** 100% SUBMISSION RAVIKUMAR JETHANI Consultant: **CONVERSE WINKLER ARCHITECTURE** Drawn By: 09/09/2022 PDC, MCW 16228E-03-01 CW-1909.01 A-308

BID SET - 09-09-22 Sheet No.: 24




SIMPSON STRONG-TIE HELIST254000: 1/4" X 40" STITCHING TIE SPECIAL LENGTHS MAY BE AVAILABLE FOR SPECIAL APPLICATIONS.


MATERIAL: TYPE 304 STAINLESS STEEL

GENERAL INSTALLATION NOTES:


- SUBMIT A SUMMARY OF WORK FOR REVIEW BY ARCHITECT/ENGINEER BEFORE PROCEEDING WITH THE INSTALLATION OF HELICAL
- CHASE BED JOINT ON EITHER SIDE OF THE AFFECTED AREA WITH A ROTARY GRINDING WHEEL. FOR 40" TIE, LENGTH OF JOINST SHOULD BE 20" TO EACH SIDE OF CRACK.
- RECOMMENDED DEPTH OF JOINT IS APPROXIMATELY 1 1/4" FOR BRICK AND CMU; FOR STONE AND MASONRY AT DISSTON RECREATION CENTER THIS SHOULD BE CONSIDERED A MINIMUM DEPTH.
- RECOMMENED VERTICAL SPACING OF INSTALLATION SITES IS 12" FOR BRICK OR "EVERY OTHER COURSE" FOR CONCRETE MASONRY UNITS. FINAL SPACING AND EXTENT OF COURSE REINFORCEMENT TO BE REVIEWED AS PART OF THE WORK PLAN.
- CLEAR BED JOINT OF ALL LOOSE DEBRIS.
- MIX NON-SHRINK REPAIR GROUT OR MORTAR PER PRODUCT INSTRUCTIONS AND PLACE INTO THE PREPARED BED JOINT, FILLING THE VOID TO APPROXIMATELY TWO-THIRDS OF ITS DEPTH. USE MANUFACTURER'S RECOMMENDED GROUT.
- EMBED THE TIE AT ONE—HALF THE DEPTH OF THE VOID. TROWEL DISPLACED GROUT TO FULLY ENCAPSULATE THE TIE. REMAINING DEPTH OF JOINT SHOULD BE ADEQUATE TO FACILITATE CONTINUOUS APPLICATIONS OF POINTING COMMENSURATE WITH SURROUNDING MASONRY WORK.
- FILL REMAINING VERTICAL CRACKS AND ASSOCIATED VOIDS WITH NON-SHRINK GROUT. VERTICAL CRACKS SHOULD BE TREATED AS PART OF THE REPOINTING WORK.

#### Installation Sequence







6 DETAIL: TYPICAL HELICAL TIE-ROD STITCHING A310 | SCALE: NTS




### DETAIL: TYPICAL COMPOSITE PATCH REPAIR IN




#### **ELEVATION DETAIL: TYPICAL GROUT** 2C INJECTION CRACK REPAIR A310 | SCALE: NTS




#### 2B DETAIL: ROUT, GROUT & FILL CRACK A310 | SCALE: NTS



2A DETAIL: ROUT AND FILL CRACK A310 SCALE: NTS




#### DETAIL: TYPICAL MASONRY SEALANT JNT @ 4 JUNCTION OF BRICK & CONC



### DETAIL: TYPICAL MASONRY SEALANT JNT @

FOR SPECIFIC LOCATIONS.

3 RETURNS A310 SCALE: NTS



3. POINTING TO MATCH ORIGINAL CONSTRUCTION. PREPARE MORTAR & POINTING SAMPLES IN FIELD AS PER SPECIFICATIONS. COLOR, FINISH, & JOINT PROFILE TO BE REVIEWED IN THE FIELD.

4. TYPE N PORTLAND CEMENT MORTAR, TYP, UNO. AGGREGATE, CEMENT COLOR, FINISH MAY VARY WITH APPLICATION.

1 SECTION DETAIL: TYPICAL EXTERIOR REPOINTING A310 SCALE: NTS

**APPROVED:** ARCHITECT/ENGINEER OF RECORD DATE **APPROVED FOR BID:** REBUILD PROJECT MANAGER DATE

> **CONVERSE** WINKLER ARCHITECTURE

DATE REVISION DESCRIPTION **DISSTON REC CENTER** 

**UPGRADES** 

**MASONRY REPAIR** 


**DETAILS** 


RAVIKUMAR JETHANI **CONVERSE WINKLER ARCHITECTURE** Drawn By: 09/09/2022 PDC, MCW


100% SUBMISSION


16228E-03-01 CW-1909.01 A-310


BID SET - 09-09-22 Sheet No.: 26

































# 1 SECTION DTL: MULTIPURPOSE RM CLNG SCALE: 6" = 1'-0"

LIGHTING FIXTURE SCHEDULE


	SPECIFICATION	MANUFACTURER/ CATALOG NO.	LAMP TYPE	WATTS	NOTES
A	10" DIAMETER X 3' PENDANT MOUNTED CYLINDER 7000 LMNS, 3K COLOR	SPI LIGHTING #SIP12069-L71W-UNV-3000K-NODL-DF_MA01 -DF_PSA-DF_DIM1	LED	71	0-10V DIMMING 1%
В	8" DIAMETER X 13' HIGH SURFACE MOUNTED CYLINDER 1000 LMNS, 3K COLOR, WITH WIDE BEAM DOWNLIGHT	SPI LIGHTING #SIC12100-L10W-UNV-3000K-18W-90-DF _MA01	LED	28	0-10V DIMMING 1%
D1	1.21" WIDE X 4' LONG RECESSED SLOT FIXTURE. 3K COLOR, 632 LMN/FT, FROSTED LENS, REMOTE DRIVER	LUMINII LIGHTING #KRL-48-30K-HO-F-X-WH-B-X/ PDCU-WLXL24	LED	42	0-10V DIMMING 1% CONTRACTOR TO VERIFY LENGTH
D2	1.21" WIDE X 6' LONG RECESSED SLOT FIXTURE. 3K COLOR, 632 LMN/FT, FROSTED LENS, REMOTE DRIVER	LUMINII LIGHTING #KRL-72-30K-HO-F-X-WH-B-X/ PDCU-WLXL24	LED	63	0-10V DIMMING 1% CONTRACTOR TO VERIFY LENGTH
D3	1.21" WIDE X 7' LONG RECESSED SLOT FIXTURE. 3K COLOR, 632 LMN/FT, FROSTED LENS, REMOTE DRIVER	LUMINII LIGHTING #KRL-84-30K-HO-F-X-WH-B-X/ PDCU-WLXL24	LED	73	0-10V DIMMING 1% CONTRACTOR TO VERIFY LENGTH
D4	1.21" WIDE X 8' LONG RECESSED SLOT FIXTURE. 3K COLOR, 632 LMN/FT, FROSTED LENS, REMOTE DRIVER	LUMINII LIGHTING #KRL-96-30K-HO-F-X-WH-B-X/ PDCU-WLXL24	LED	83	0-10V DIMMING 1% CONTRACTOR TO VERIFY LENGTH
D5	1.21" WIDE X 10' LONG RECESSED SLOT FIXTURE. 3K COLOR, 632 LMN/FT, FROSTED LENS, REMOTE DRIVER	LUMINII LIGHTING #KRL-120-30K-HO-F-X-WH-B-X/ PDCU-WLXL24	LED	104	0-10V DIMMING 1% CONTRACTOR TO VERIFY LENGTH
F	2X2 FLAT PANEL TROFFER. 3K COLOR, 4400 LMNS	COLUMBIA LIGHTING #SRP22-30-VL-G-ED-U	LED	41	0-10V DIMMING 1%
G	0.5" WIDE X 8' LONG TAPE LIGHT IN 45 DEGREE CORNER MOUNT CHANNEL. 3K COLOR, 786 LMN/FT, FROSTED LENS, REMOTE DRIVER	LUMINII LIGHTING #LL48HE-HO-30K-X-X-96/ K45R-F/ PDCU-D	LED	48	0-10V DIMMING 1% CONTRACTOR TO VERIFY LENGTH
Н	1.5" DIAMETER X 3' LONG SURFACE MOUNTED LINEAR ADJUSTABLE FIXTURE, 2100 LMNS, 3K COLOR, REMOTE DRIVER	SPI LIGHTING #SIW12138-3FT-L21W-UNV-3000K-DF-BRK -X-DF-FT-X	LED	21	0-10V DIMMING 1%
K	4' DIAMETER SURFACE MOUNTED RING FIXTURE, 8800 LMNS, 3K COLOR, WHITE FINISH	FINELITE #HP-4C-SM-D-4'-H-830-F-96-X-SC- FC10%-X-X-SW	LED	110	0-10V DIMMING 10%
L	4' X SHAPED SURFACE MOUNTED FIXTURE, 5800 LMNS, 3K COLOR, WHITE FINISH	FINELITE #HP-4-SM-D-4'X-H-830-F-96-X-SC- FC10%-X-FE-SW	LED	56	0-10V DIMMING 10%
L1	2' X 2' BACK-LIT SURFACE MNT TROFFER FIXTURE 2970/3358/4385 SWITCHABLE LUMEN, FROSTED LENS W/EVEN ILLUMINATION	COLUMBIA LIGHTING #CBT22-LS35 W/ SRPSMK22 SURFACE MNT KIT	LED	24/28/38	0-10V DIMMING 10%
L2	2' X 4' BACK-LIT SURFACE MNT TROFFER FIXTURE 3633/5014/6037 SWITCHABLE LUMEN, FROSTED LENS W/EVEN ILLUMINATION	COLUMBIA LIGHTING #CBT24-LS35 W/ SRPSMK24 SURFACE MNT KIT	LED	28/38/48	0-10V DIMMING 10%
L3A	4" WIDE X 48' LONG SURFACE RECESSED FIXTURE 725 LMS/FT, 3K COLOR, FLUSH LOW-GLOSS WHITE REFLECTOR	FINELITE #HP-4-R-D-H-830-F-96LG-X-SC- FC10%-X-X-X	LED	_	0-10V DIMMING 10%
L3B	4" WIDE X 48' LONG SURFACE RECESSED FIXTURE 932 LMS/FT, 3K COLOR, FLUSH LOW-GLOSS WHITE REFLECTOR	FINELITE #HP-4-R-D-V-830-F-96LG-X-SC- FC10%-X-X-X	LED	_	0-10V DIMMING 10%
L4A	9" X 18" X 8"D EXTERIOR ARCHITECTURAL WALL SCONCE 8500 LM, 4K COLOR, TYPE 3 DISTRIBUTION SURFACE MOUNT. COLOR BY REBUILD/ARCH	LITHONIA LIGHTING #WDGE3 LED-P2-40K-70CRI-R3-MVOLT-SRM	LED	59	_
L4B	9" X 18" X 8"D EXTERIOR ARCHITECTURAL WALL SCONCE 12,000 LM, 4K COLOR, FORWARD THROW DISTRIBUTION SURFACE MOUNT. COLOR BY REBUILD/ARCH	LITHONIA LIGHTING #WDGE3 LED-P4-40K-70CRI-RFT-MVOLT-SRM	LED	88	
L5	9" X 25" X 10"D EXTERIOR ARCHITECTURAL WALL SCONCE 20,000 LM, 4K COLOR, FORWARD THROW DISTRIBUTION SURFACE MOUNT. COLOR BY REBUILD/ARCH	LITHONIA LIGHTING #WDGE4 LED-P4-40K-70CRI-RFT-MVOLT-SRM	LED	140	_
ML	4" WIDE X 38' LONG SURFACE MOUNTED FIXTURE SHAPED INTO SQUARE. 380 LMS/FT, 3K COLOR, WHITE FINISH	FINELITE #HP-4-SM-D-S-830-F-96-X-SC- FC10%-X-CORNER-SW	LED	137	0-10V DIMMING 10%
1	4" WIDE X 36' LONG SURFACE MOUNTED FIXTURE SHAPED INTO SQUARE. 477 LMS/FT, 3K COLOR, WHITE FINISH	FINELITE #HP-4-SM-D-B-830-F-96-X-SC- FC10%-X-CORNER-SW	LED	166	0-10V DIMMING 10%





2 SECTION DTL: HALL 103/ 104 SOFFIT A602 SCALE: 6" = 1'-0"


APPROVED: ARCHITECT/ENGINEER OF RECORD DATE APPROVED FOR BID: REBUILD PROJECT MANAGER DATE CONVERSE : WINKLER : ARCHITECTURE DATE DESCRIPTION **DISSTON REC CENTER UPGRADES** LIGHT FIXTURE **SCHEDULE** 100% SUBMISSION Engineering Manager: RAVIKUMAR JETHANI CONVERSE WINKLER ARCHITECTURE <sup>e:</sup> 09/09/2022 16228E-03-01 CW-1909.01 A-602

**BID SET - 09-09-22** Sheet No.: 39 of









FINISH SCHEDULE

	2U - 2UU														
ROOM	DOOM NAME	FLO	ORS	l	ASE/ NSITION	DLAN	NORTH	PLAN	WAL I EAST	LS PLAN	SOUTH	DI AN	WEST	CEILI	NG
NO.	ROOM NAME	SUBSTRATE	FIELD	SUBSTRATE	BASE	SUBSTRATE	FINISH	SUBSTRATE	FINISH	SUBSTRATE	FINISH	SUBSTRATE	FINISH	MATERIAL	FINISH
B13	STAIR	(E)CONC	(E)CONC	ETR	(E) GLZ BRK	ETR	(E) GLZ BRK	ETR	(E) GLZ BRK	ETR	(E) GLZ BRK	ETR	(E) GLZ BRK	(E) GWB	P-
101	WOMEN'S	EXIST WD/ TILE	RF-1	ETR	1/A404	CBU	CT-3, CT-6, CT-9, P-2	(E) GWB	P-1						
102	MEN'S	EXIST WD/ TILE	RF-1	ETR	1/A404	CBU	CT-4, CT-7, CT-9, P-2	(E) GWB	P-1						
103	HALL	EXIST WD	WD−1, FG−1	-	WD-2	ETR	P-	GWB	P-	ETR	P-	GWB	P-	ETR	P-2, P-3
104	HALL	EXIST WD	WD-1, FG-1	_	WD-2	ETR	P-	GWB	P-	ETR	P-	GWB	P-	ETR	P-2, P-3
105A	TOILET	EXIST WD	RF-1	CBU	2/A404	CBU	CT-2, CT-5, CT-8, P-2	CBU	CT-2, CT-5, CT-8, P-2	CBU	CT-2, CT-5, CT-8, P2	CBU	CT-2, CT-5, CT-8	GWB	P-1
105B	UTILITY RM	EXIST WD	(E) VCT	ETR	WD-9	ETR	P-2	GWB	P-2	ETR	P-2	ETR	P-2	ACP-1	WHITE
106	LOBBY	EXIST WD	WD-1	ETR	WD-2	ETR	P-	ETR	P-	ETR	P-	ETR	P-	ETR	P-1
107	FITNESS RM	EXIST WD	VCT-	(E) PLASTER	RB-1	ETR	P-	ETR	P-	ETR	P-	ETR	P-	ACP-1	WHITE
108	OFFICE	EXIST WD	WD-1	ETR	WD-9	ETR	P-	ETR	P-	ETR	P-	ETR	P-	ACP-1	WHITE
109A	VESTIBULE	EXIST WD	WD-1, FG-1	ETR	WD-2	ETR	P-	GWB	P-	ETR	P-	GWB	P-	ETR	P-2, P-3
109B	VESTIBULE	EXIST WD	WD-1	ETR	WD-2	ETR	P-	ETR	P-	ETR	P-	ETR	P-	ETR	P-2, P-3
110	HALL	EXIST WD	WD-1	ETR	WD-2	ETR	P-2	ETR	P-2	ETR	P-2	ETR	P-2	ETR	P-2, P-3
111	OFFICE	EXIST WD	WD-1	ETR	WD-9	ETR	P-	ETR	P-	ETR	P-	ETR	P-	ACP-1	WHITE
201	ACTIVITY	EXIST WD	VCT-	ETR	RB-1	ETR	P-	ETR	P-	ETR	P-	ETR	P-	ETR	P-
202	TOILET	EXIST WD	(E) CT	ETR	(E) CT	ETR	P-	ETR	P-	ETR	P-	ETR	P-	ETR	P-
203	STORE	EXIST WD	VCT-	ETR	RB-1	ETR	P-	ETR	P-	ETR	P-	ETR	P-	ETR	P-
204	MULTI-PURPOSE	EXIST WD	WD-1	ETR	WD-5	ETR	P-	ETR	P-	ETR	P-	ETR	P-	AWCP-1, AWCP -2, (E) PLASTER	P-1
205	HALL	EXIST WD	WD-1	GWB	WD-5	ETR	P-	ETR	P-	ETR	P-	ETR	P-	ETR	P-2, P-3
205	STAIRCASE & LANDING	EXIST WD	WD-1	ETR	WD-9	ETR	P-	ETR	P-	ETR	P-	ETR	P-	ETR	P-2, P-3

NOTES:

1. EXIST WALL AND CEILING SURFACES MAY BE PLASTER ON LATHE, GWB W/ VENEER PLASTER, GWB, OR SOME COMBINATION. PATCH AND REPAIR IN KIND, UNO. SEE SPECIFICATION FOR PREP AND FINISH SYSTEMS

2. CLEAN EXIST CT. REPLACE MISSING TILES IN KIND/TO MATCH. IF GROUT IS WORN, DISCOLORED, MISSING OR IN NEED OF REPAIR, CONFER WITH ARCHITECT ABOUT EXTENT OF WORK. NEW GROUT TO MATCH EXISTING.

TILE SCHEDULE


CODE	MATERIAL	SIZE	MANUFACTURER	MODEL	NOTES
CT-2	CERAMIC TILE WALL	1" X 8"	DALTILE	COLOR WHEEL CLASSIC, ARCTIC WHITE 0190 (1)	
CT-3	CERAMIC TILE WALL	3" X 6"	DALTILE	COLOR WHEEL CLASSIC, ARCTIC WHITE 0190 (1)	
CT-4	CERAMIC TILE WALL	3" X 6"	DALTILE	COLOR WHEEL CLASSIC, PLUM CRAZY, 1178 (3)	
CT-5	CERAMIC TILE WALL	3" X 6"	DALTILE	COLOR WHEEL CLASSIC, URBAN PUTTY 0761 (2)	
CT-6	CERAMIC TILE WALL	6" X 6"	DALTILE	COLOR WHEEL CLASSIC, ARCTIC WHITE 0190 (1)	
CT-7	CERAMIC TILE WALL	6" X 6"	DALTILE	COLOR WHEEL CLASSIC, PLUM CRAZY, 1178 (3)	
CT-8	CERAMIC TILE WALL	3" X 6"	DALTILE	COLOR WHEEL CLASSIC, SEA BREEZE, 1174 (3)	
CT-9	CERAMIC TILE WALL	3" X 6"	DALTILE	COLOR WHEEL CLASSIC, MATTE GRAY, 0709 (2)	
CT-10	CERAMIC TILE WALL	6" X 6"	DALTILE	COLOR WHEEL CLASSIC, SEA BREEZE, 1174 (3)	
CT-11	CERAMIC TILE WALL	3" X 6"	DALTILE	COLOR WHEEL CLASSIC, OCEAN BLUE, 1049 (3)	
CT-12	CERAMIC TILE WALL	3" X 6"	DALTILE	COLOR WHEEL CLASSIC, SPA, 0148 (3)	
CT-13	CERAMIC TILE WALL	6" X 6"	DALTILE	COLOR WHEEL CLASSIC, OCEAN BLUE, 1049 (3)	


## FINISH CODE KEY

11 11	SII OODE I			
CODE	MATERIAL	SIZE	SPECIFICATION SECTION	NOTES
FG-1	CARPET INSERT-FOOT GRILLE	AS INDICATED	124813 ENTRANCE FLOOR MATS AND FRAMES	
LS-1	LINOLEUM SHEET	AS INDICATED	096543 LINOLEUM FLOORING	
CT-2	CERAMIC TILE — WALL	1" X 8"	093013 CERAMIC TILING	
CT-3	CERAMIC TILE - WALL	3" X 6"	093013 CERAMIC TILING	
CT-4	CERAMIC TILE - WALL	3" X 6"	093013 CERAMIC TILING	
CT-5	CERAMIC TILE - WALL	3" X 6"	093013 CERAMIC TILING	
CT-6	CERAMIC TILE - WALL	6" X 6"	093013 CERAMIC TILING	
CT-7	CERAMIC TILE - WALL	6" X 6"	093013 CERAMIC TILING	
CT-8	CERAMIC TILE - WALL	3" X 6"	093013 CERAMIC TILING	
CT-9	CERAMIC TILE - WALL	3" X 6"	093013 CERAMIC TILING	
CT-10	CERAMIC TILE - WALL	6" X 6"	093013 CERAMIC TILING	
CT-11	CERAMIC TILE - WALL	3" X 6"	093013 CERAMIC TILING	
CT-12	CERAMIC TILE - WALL	3" X 6"	093013 CERAMIC TILING	
CT-13	CERAMIC TILE - WALL	6" X 6"	093013 CERAMIC TILING	
RF-1	RESILIENT FLOOR		097720 URETHANE CEMENT COMPOSITION FLOORING	
RB-1	RUBBER BASE	4"	096513 RESILIENT BASE & ACCESSORIES	
ACP-1	ACOUSTIC CEILING PANEL	24" X 24"	095113 ACOUSTICAL PANEL CEILINGS	
ACP-2	ACOUSTIC CEILING PANEL	24" X 24"	095113 ACOUSTICAL PANEL CEILINGS	
AWCP-1	ACOUSTIC WD CEILING PANEL	96" X 60"	095426 SUSPENDED WOOD CEILINGS	
AWCP-2	ACOUSTIC WD CEILING PANEL	60" X 60"	095426 SUSPENDED WOOD CEILINGS	
WD-1	EXIST WD FLOOR; NEW CLEAR FINISH	AS INDICATED	099300 STAINING AND TRANSPARENT FINISHES	
WD-2	EXIST WD BASE/ WAINSCOT; NEW CLEAR FINISH	AS INDICATED	099300 STAINING AND TRANSPARENT FINISHES	
WD-3	EXIST WD COL/ PILASTER; NEW CLEAR FINISH	AS INDICATED	099300 STAINING AND TRANSPARENT FINISHES	
WD-4	EXIST WD CLNG COFFER; NEW CLEAR FINISH		099300 STAINING AND TRANSPARENT FINISHES	
WD-5	CLEAR FINISH WD BASE	AS INDICATED	064600 WOOD TRIM	
WD-6	CLEAR FINISH WD BASE & WAINSCOT		064023 INTERIOR ARCHITECTURAL WOODWORK	
WD-7	CLEAR FINISH WOOD TRIM	3/4" X 4"	064600 WOOD TRIM	DOORS, WINDOWS
WD-8	PAINTED WOOD TRIM	3/4" X 2"	064600 WOOD TRIM	WINDOWS, OTHER
	PAINTED WOOD BASE	1X6 NOM+CAP	064600 WOOD TRIM; MATCH EXISTING	1


APPROV	/ED:		
ARCHITI	ECT/ENGINEER	OF RECORD	DATE
APPROV	/ED FOR BID:		
REBUILI	D PROJECT MA	NAGER	DATE
Designer:			
· · ·	CON	VERSE	
	ARC	HITECTL	JRE
Seal:			
		· .	
	· · ·	· · ·	
Key Plan:			
			ĩ
			<b>*</b>
DEMISION	DECCE:	PTION	DATE
Project:	DESCRI	· I I UN	DATE
DI	SSTON R		ER
	UPGR	ADES	
Sheet Title:			
_ SHEEL HUE:			
F	FINISH S	CHEDUL	ES
Submisison:	100% SUB	MISSION	
Engineering Manager:		AR JETHANI	
Consultant:	CONVERSE W	INKLER ARCHIT	ECTURE
Task No.:		Drawn By:	
	09/2022	Checked By: PDC, MCV	V
	28E-03-01	Drawing No.:	^ <u>_</u>
CW	-1909.01	A-7	<b>U</b> 5


BID SET - 09-09-22 Sheet No.: 44 of 63





1 RESTROOM SIGN TYPES
A701 SCALE: 6" = 1'-0"







1 RESTROOM SIGN TYPES
A701 SCALE: 6" = 1'-0"

APPROVED:	
ARCHITECT/ENGINEER OF RECORD	DATE
ARCHITECT/ENGINEER OF RECORD	DATE
APPROVED FOR BID:	
REBUILD PROJECT MANAGER	DATE
Designer:	
····· CONVERSE	
: · · · · · · CONVERSE	
	IRE
: CONVERSE : WINKLER : ARCHITECTU	IRE
	IRE
	IRE
	IRE
· WINKLER · ARCHITECTU	IRE
Seal:	IRE
· WINKLER · ARCHITECTU	IRE
Seal:	IRE

DATE **DISSTON REC CENTER UPGRADES** 

**INTERIOR SIGNAGE** 

**DETAILS** 


100% SUBMISSION

**RAVIKUMAR JETHANI** CONVERSE WINKLER ARCHITECTURE Drawn By:

16228E-03-01 CW-1909.01

A-901

**BID SET - 09-09-22** Sheet No.: 46



<u>ABBRE'</u>	<u>VIATIONS</u>
AC AD AFF AHU AP ABBREV AS	AIR CONDITIONING ACCESS DOOR ABOVE FINISHED FLOOR AIR HANDLING UNIT ACCESS PANEL ABBREVIATIONS AIR SEPERATOR
BHP BLDG BLR BTUH CD CFM CI CLG CO COL CUH CH CHWS	BRAKE HORSEPOWER BUILDING BOILER BRITISH THERMAL UNITS PER HOUR CEILING DIFFUSER CUBIC FEET PER MINUTE CAST IRON CEILING CLEANOUT COLUMN CABINET UNIT HEATER CHILLER CHILLER
CHWS COND DET DIA/Ø DN DWG	CHILLED WATER RETURN CONDENSATE  DETAIL DIAMETER DOWN DRAWING
EA EAT EC EF ESP EWT ET ER	EXHAUST AIR ENTERING AIR TEMPERATURE EXPANSION COMPENSATOR EXHAUST FAN EXTERNAL STATIC PRESSURE ENTER WATER TEMPERATURE EXPANSION TANK EXHAUST REGISTER
FC FCU FD FIL FLEX FLR FPM FPS FT FTR	FLEXIBLE CONNECTION FAN COIL UNIT FIRE DAMPER FILTER FLEXIBLE FLOOR FEET PER MINUTE FEET PER SECOND FEET/FOOT FIN TUBE RADIATION
G GA GAL GPM GR	GAS (NATURAL) GAUGE GALLON GALLONS PER MINUTE GRILLE
HC HD HORIZ HP HR HT HUM HWS HWR HZ	HEATING COIL HEAD HORIZONTAL HORSEPOWER HOUR HEIGHT HUMIDITY HOT WATER SUPPLY (HEATING) HOT WATER RETURN (HEATING) HERTZ
ID INSUL IN/WG KW MAX MBH MIN	INSIDE DIAMETER INSULATION INCHES WATER GAUGE KILOWATT MAXIMUM 1000 BTU PER HOUR MINIMUM
MOD MVD NIC NO NTS	MOTOR OPERATED DAMPER MANUAL VOLUME DAMPER  NOT IN CONTRACT NORMALLY OPEN NOT TO SCALE
OA OD	OUTSIDE AIR

SINGLE LINE	DOUBLE LINE	DESCRIPTION
_	_	
		SUPPLY AIR FLOW
<del>-1 ►</del>	<del>-1 -</del>	RETURN/EXHAUST AIR FLOW
		SUPPLY/OUTSIDE AIR DUCT
		RETURN/EXHAUST AIR DUCT
		RECTANGULAR SUPPLY DUCT ELBOW (UP & DN.)
		RECTANGULAR RETURN/EXHAUST DUCT (UP & DN.)
-12x10	12x10 }	DENOTES RECTANGULAR DUCT SIZE IN INCHES (DIMENSIONS INSIDE CLEAR)
	+	SUPPLY AIR TERMINALS CEILING OR DUCT MOUNTED (SQUARE, RECTANGULAR, CIRCULAR & SIDEWALL W/AIR VOLUME EXTRACTOR) CFM, SIZE & TYPE AS NOTED
		EXHAUST/RETURN AIR TERMINAL CFM, SIZE & TYPE AS NOTED
		DUCT RISING IN DIRECTION OF ARROW
		TRANSITION DUCT CONCENTRIC & ECCENTRIC
·		FLEXIBLE CONNECTION
<u> </u>	MOD	MOTOR OPERATED DAMPER (OPPOSED BLADE)
——————————————————————————————————————		MOTOR OPERATED DAMPER (PARALLEL BLADE)
		SQUARE VANED ELBOW
1 A		RISER DESIGNATION
•		POINT OF CONNECTION TO EXISTING
<b>♦</b>		POINT OF DISCONNECTION
		WALL MOUNTED AIR CONDITIONER
UC"		DOOR UNDERCUT
	\$	REFRIGERANT PIPE
	<u></u>	CONDENSATE PIPE

SINGLE LINE	DESCRIPTION
<b>→</b>	SHUT-OFF VALVE - (SEE SPEC'S FOR TYPE)
->>-	BALANCING VALVE - (SEE SPEC'S FOR TYPE)
1	CHECK VALVE - (SEE SPEC'S FOR TYPE)
	PRESSURE REDUCING VALVE
K	GAS COCK
PITCH	PITCH DOWN IN DIRECTION OF ARROW
O <del> </del>	RISER UP
<del>c+</del>	RISER DOWN
<b>──</b> ○ <b>├</b>	VALVE IN RISER
<b>→</b>	VALVE IN DROP
f <sup>+-</sup>	ELBOW - 90
	ELBOW - 45
	LATERAL CONNECTION
<del></del>	TEE CONNECTION
-++-	CROSS CONNECTION
	BASE ELBOW
—D—	CONCENTRIC REDUCER
	ECCENTRIC REDUCER
	DIRECTION OF FLOW
<del>X</del>	PIPE ANCHOR
	PIPE GUIDE
— <del>—</del> ——————————————————————————————————	3-WAY CONTROL VALVE
P	PRESSURE GAUGE W/GAUGE COCK (SEE SPEC'S FOR RANGE)
τ⊘ †	THERMOMETER-DIAL (SEE SPEC'S FOR RANGE)
T T	THERMOMETER-STEM (SEE SPEC'S FOR RANGE)
<u>-</u>	THERMOMETER-TEST WELL
<u> </u>	PRESSURE TEST FITTING
P/T	COMBINATION PRESSURE/TEMPERATURE TEST WALL
	PUMP
T	THERMOSTAT
***	"Y" TYPE STRAINER (W/HOSE END VALVE)
<u></u>	MANUAL AIR VENT
<u>^</u>	AUTOMATIC AIR VENT
— <u>Ö</u> —	SHUT-OFF & BALANCE VALVE W/PRESSURE TAPS
-\$-	2-WAY CONTROL VALVE

#### GENERAL MECHANICAL NOTES

1. THE SUBMISSION OF A PROPOSAL BY THE CONTRACTOR IS NOTIFICATION THAT HE HAS TOTALLY FAMILIARIZED HIMSELF WITH THE CONTRACT DOCUMENTS AND EXISTING SITE CONDITIONS AND HAS AGREED TO PROVIDE THE NECESSARY LABOR AND MATERIAL FOR THE COMPLETE INSTALLATION OF EACH SYSTEM IN A NEAT AND WORKMANLIKE MANNER IN ACCORDANCE WITH THE BEST PRACTICES OF THE INDUSTRY AND IN COMPLIANCE WITH ALL AUTHORITIES HAVING JURISDICTION.

2. THE CONTRACT DRAWINGS ARE PRESENTED TO THE CONTRACTOR WITH THE UNDERSTANDING THAT HE IS AN EXPERT AND COMPETENT IN THE PREPARATION OF CONTRACT BID PRICES ON THE BASIS OF INFORMATION SUCH AS CONTAINED IN THE CONTRACT DOCUMENTS. IT IS THE INTENT OF THE CONTRACT DRAWINGS AND SPECIFICATIONS TO CALL FOR FINISHED WORK, TESTED AND READY FOR OPERATION AND IN COMPLETE CONFORMANCE WITH ALL APPLICABLE CODES, RULES AND REGULATIONS. MINOR ITEMS NOT USUALLY SHOWN OR SPECIFIED, BUT MANIFESTLY NECESSARY FOR THE PROPER INSTALLATION AND OPERATION OF THE VARIOUS SYSTEMS, SHALL BE INCLUDED IN THE WORK AND IN THE PROPOSAL THE SAME AS IF SPECIFIED OR SHOWN ON THE CONTRACT DRAWINGS. IF ANY DEPARTURES FROM THE CONTRACT DRAWINGS ARE DEEMED NECESSARY, DETAILS OF SUCH DEPARTURES AND THE REASONS THEREFORE SHALL BE SUBMITTED TO THE ENGINEER FOR REVIEW. NO DEPARTURES SHALL BE MADE WITHOUT PRIOR REVIEW OF THE ENGINEER.

3. VISIT THE SITE AND VERIFY ALL DIMENSIONS IN THE FIELD, AND ADVISE THE ARCHITECT/ENGINEER AND THE OWNER OF ANY DISCREPANCIES BEFORE PERFORMING THE WORK.

4. THE CONTRACT DRAWINGS INDICATE ARRANGEMENTS AND APPROXIMATE SIZES AND RELATIVE LOCATIONS OF PRINCIPAL APPARATUS, EQUIPMENT, DEVICES AND SERVICES TO BE PROVIDED. CONTRACT DRAWINGS ARE DIAGRAMMATIC AND ARE A GRAPHIC REPRESENTATION OF CONTRACT REQUIREMENTS TO BEST AVAILABLE STANDARDS AT THE SCALE INDICATED.

5. LAYOUT OF EQUIPMENT INDICATED ON THE CONTRACT DRAWINGS SHALL BE CHECKED AND COMPARED AGAINST ALL DRAWINGS AND SPECIFICATIONS OF ALL TRADES AND EXACT LOCATIONS DETERMINED USING REVIEWED SHOP DRAWINGS OF SUCH EQUIPMENT. WHERE PHYSICAL INTERFERENCE OCCURS, CONSULT WITH ENGINEER AND PREPARE DATED, DIMENSIONED DRAWINGS COORDINATED WITH ALL OTHER TRADES WORK IN THE AREA AND CORRECTING SUCH INTERFERENCES. OBTAIN WRITTEN REVIEW OF ENGINEER FOR SUCH DRAWINGS AND DISTRIBUTE SAME AS REQUIRED.

6. COORDINATE ALL WORK WITH THE OWNER AND ALL OTHER CONTRACTORS. SCHEDULE WORK IN ACCORDANCE WITH THE CONSTRUCTION SCHEDULE SO THAT ALL OF THE WORK CAN BE INSTALLED WITHOUT DELAYING THE PROJECT.

7. PREPARE FULLY DIMENSIONED FIELD INSTALLATION DRAWINGS. THESE DRAWINGS SHALL BE FORWARDED TO ALL CONTRACTORS. EACH CONTRACTOR SHALL SUBSEQUENTLY IN SUCCESSION DELINEATE HIS RESPECTIVE WORK ON THESE COORDINATION DRAWINGS. WHEN ALL WORK HAS BEEN PROPERLY SHOWN ON THE COORDINATION DRAWINGS, AND ALL CONTRACTORS AGREE THAT THEIR RESPECTIVE WORK CAN BE INSTALLED AND WILL PROPERLY FIT TOGETHER, THEY SHALL SO ACKNOWLEDGE BY ENDORSING THE DRAWING(S). ANY WORK DONE PRIOR TO COMPLETION OF ABOVE COORDINATION PROCESS FOUND IN CONFLICT SHALL BE REMOVED AND REPLACED AT CONTRACTOR'S

8. SECURE AND PAY ALL FEES AND PERMITS PERTAINING TO THE CONTRACT.

9. ALL EQUIPMENT SHALL BE INSTALLED IN STRICT COMPLIANCE WITH THE MANUFACTURER'S WRITTEN INSTRUCTIONS.

10. SCHEDULE ALL SHUTDOWNS THAT AFFECT UTILITIES AND PORTIONS OF THE BUILDING THAT MUST REMAIN IN OPERATION WITH THE OWNER.

11. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL RIGGING, HANDLING AND PROTECTION OF MATERIALS. ALL EQUIPMENT AND MATERIALS SHALL BE NEW AND WITHOUT BLEMISH OR DEFECT.

12. WHERE CONDUIT, CABLES, DUCTWORK OR PIPING PASSES THROUGH FIRE RATED FLOORS OR WALLS, THE PENETRATION SHALL BE COMPLETELY SEALED WITH A FIRE STOP MATERIAL THAT IS ULLISTED AND ACCEPTED BY THE BUILDING DEPARTMENT AND FIRE DEPARTMENT AS BEING SUITABLE FOR THIS SERVICE. THIS MATERIAL SHALL BE INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF THE MANUFACTURER TO MAINTAIN THE UL LISTED FIRE RATING OF THE PENETRATED WALL OR FLOOR.

13. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL SLAB OPENINGS, WALL OPENINGS, BEAM PENETRATIONS AND CORING AS IT RELATES TO HIS WORK. CONTRACTOR SHALL SUBMIT SIZE AND LOCATION TO THE STRUCTURAL ENGINEER FOR REVIEW.

14. SUBMIT SCHEDULE OF SUBMITTALS PRIOR TO SUBMITTING ANY SHOP DRAWINGS. THIS SCHEDULE SHALL IDENTIFY ALL PRODUCT DATA, DRAWINGS, ETC. TO BE SUBMITTED FOR THIS PROJECT, INCLUDING THE ANTICIPATED DATE OF EACH SUBMISSION. COMPLY WITH THE REQUIREMENTS OF DIVISION 1 OF THE SPECIFICATIONS. ANY WORK INSTALLED OR EQUIPMENT PURCHASED PRIOR TO RECEIPT OF ENGINEER REVIEWED SHOP DRAWINGS THAT REQUIRES CHANGES SHALL BE REPLACED AT CONTRACTOR EXPENSE.

15. SUBMIT CATALOG INFORMATION, FACTORY ASSEMBLY DRAWINGS AND FIELD INSTALLATION DRAWINGS AS REQUIRED FOR A COMPLETE EXPLANATION AND DESCRIPTION OF ALL ITEMS TO BE PROVIDED. THE CONTRACTOR SHALL REVIEW AND APPROVE ALL SHOP DRAWINGS. NO SUBMISSION WILL BE ACCEPTED WITHOUT THE SIGNED APPROVAL OF THE CONTRACTOR. THE CONTRACTOR SHALL CHECK AND VERIFY ALL FIELD MEASUREMENTS

16. PROVIDE AS-BUILT DOCUMENTS AND OPERATING/MAINTENANCE MANUALS AS SPECIFIED IN DIVISION 1 OF THE SPECIFICATIONS.

17. INSTALLED SYSTEMS SHALL OPERATE UNDER ALL CONDITIONS OF LOAD WITHOUT SOUND OR VIBRATION THAT IS OBJECTIONABLE TO THE ENGINEER, ARCHITECT OR OWNER. OBJECTIONABLE SOUND OR VIBRATION CONDITIONS SHALL BE CORRECTED IN REVIEWED MANNER BY THE CONTRACTOR AT HIS EXPENSE.


18. FURNISH ACCESS DOORS AS REQUIRED FOR OPERATION AND MAINTENANCE OF CONCEALED EQUIPMENT, VALVES, CONTROLS, ETC., AND COORDINATE THEIR DELIVERY WITH THE INSTALLING TRADE.

19. ALL WORK FURNISHED UNDER THE CONTRACT SHALL BE GUARANTEED AGAINST ANY AND ALL DEFECTS IN WORKMANSHIP AND/OR MATERIALS FOR A PERIOD OF NOT LESS THAN ONE (1) YEAR FROM THE DATE OF FINAL ACCEPTANCE OF THE INSTALLATION. ANY DEFECTS OF WORKMANSHIP DEVELOPING DURING THIS PERIOD SHALL BE REMEDIED AND ANY DEFECTIVE MATERIAL REPLACED WITHOUT ADDITIONAL

20. NOTIFY ARCHITECT / ENGINEER OF ESTIMATED DATE OF COMPLETION OF ROUGH-IN WORK AN DATE OF BOTH WALL AND CEILING INSTALLATION. NOTIFICATION SHALL BE MINIMUM OF ONE WEEK PRIOR TO COMPLETION DATE TO ENABLE ARCHITECT / ENGINEER SCHEDULING OF PRELIMINARY PUNCHLIST INSPECTION PRIOR TO WALL AND CEILING INSTALLATION. CONTRACTOR SHALL SIMILARLY NOTIFY ARCHITECT / ENGINEER OF COMPLETION OF ALL WORK, INDICATING THE CONTRACTOR IS READY FOR THE ARCHITECT / ENGINEER TO PERFORM THE FINAL PUNCHLIST INSPECTION.

21. UPON COMPLETION OF ALL UNFINISHED OR FAULTY WORK NOTED IN ARCHITECT / ENGINEER'S FINAL PUNCHLIST, THE CONTRACTOR SHALL SUBMIT TO THE ENGINEER IN WRITING A LETTER OF COMPLETION CERTIFYING THAT ALL PUNCHLIST ITEMS HAVE BEEN COMPLETED AND ALL AS-BUILTS, MANUALS, ETC. HAVE BEEN SUBMITTED.

22. MECHANICAL CONTRACTOR TO BECOME FAMILIAR WITH THE ELECTRICAL SCOPE OF WORK FROM THE ELECTRICAL DRAWINGS INCLUDED IN THIS PACKAGE FOR COORDINATION PURPOSES.



DISSTON REC CENTER **UPGRADES** 

Sheet Title: MECHANICAL SYMBOLS, ABBREVIATIONS & GENERAL NOTES

100% SUBMISSION RAVI JETHANI **CONVERSE WINKLER ARCHITECTURE** WJB/GB

08/12/2021 UJ 16228E-03-01 CW-1909.01

46

BID SET - 09-09-2022

OPNG

PSI

PSIG

PTAC

REV

RPM

TEMP

TSP

VTR

VENT THROUGH ROOF WALL HEATER WITH

WITHOUT

WET BULB

TYPICAL UNIT HEATER

OUTSIDE DIAMETER

PRESSURE DIFFERENTIAL

POUNDS PER SQUARE INCH

POUNDS PER SQUARE INCH GAUGE

PACKAGE TERMINAL AIR CONDITIONER

OPENING

PHASE

REVISION

SUPPLY AIR SUPPLY FAN

SQ. FT./ Ø SQUARE FOOT

SPECIFICATION

THERMOSTAT

TEMPERATURE


SUPPLY REGISTER

RELATIVE HUMIDITY REHEAT COIL

REFRIGERANT-LIQUID REFRIGERANT - SUCTION

REVOLUTIONS PER MINUTE

TOTAL STATIC PRESSURE





APPROVED: ARCHITECT/ENGINEER OF RECORD DATE APPROVED FOR BID: REBUILD PROJECT MANAGER DATE CONVERSE · WINKLER : ARCHITECTURE MARK ULRICK ENGINEERS, INC. DESCRIPTION **DISSTON REC CENTER UPGRADES** Sheet Title: MECHANICAL FIRST FLOOR PLAN DEMOLITION 100% SUBMISSION Engineering Manager: RAVI JETHANI CONVERSE WINKLER ARCHITECTURE WJB/GB 08/12/2021 UJ 16228E-03-01 CW-1909.01

46


BID SET - 09-09-2022

Sheet No.:






### PARTIAL SECOND FLOOR PLAN — HVAC SCALE: $\frac{1}{8}$ "=1'-0"



#### SHEET NOTES

- 1. MECHANICAL CONTRACTOR IS TO ROUTE ALL REFRIGERANT PIPE CONCEALED AND SUPPORT EVERY 10'-0".
- 2. PRE INSULATED LINE ARE ACCEPTABLE MAXIMUM LENGTH TO MEET
- MANUFACTURER RECOMMENDATION.
- 3. MECHANICAL CONTRACTOR TO PIPE CONDENSATE TO NEAREST SANITARY LINE, PROVIDE INDIRECT CONNECTION.




PARTIAL BASEMENT PLAN MECH B14 - HVAC SCALE:  $\frac{1}{8}$ "=1'-0"

#### NOTES

- INSTALL TWO AIR FRAME 2.5 TONS DX COIL IN THE SUPPLY DUCT ON HV-1 SERVING THE GYMNASIUM FOR DEHUMIDIFICATION.
   PROVIDE CONDENSATE PIPING TO THE FLOOR DRAIN FROM BOTH
- A-FRAME COILS. 3. CONNECT A-FRAME COIL TO THE AIR COOLED COMPRESSOR ON ROOF VIA REFRIGERANT PIPING INSULATED WITH ARMA FLEX.
- 4. THERMOSTAT FOR A-FRAME COIL TO BE LOCATED IN THE GYMNASIUM (ONE THERMOSTAT TO CONTROL BOTH A-FRAME COILS.)

APPROVED: ARCHITECT/ENGINEER OF RECORD DATE APPROVED FOR BID: REBUILD PROJECT MANAGER DATE CONVERSE · WINKLER ARCHITECTURE MARK ULRICK ENGINEERS, INC.



DESCRIPTION

**DISSTON REC CENTER UPGRADES** 

Sheet Title: MECHANICAL PARTIAL BASEMENT & SECOND FLOOR PLANS


**RAVI JETHANI CONVERSE WINKLER ARCHITECTURE** WJB/GB 08/12/2021 UJ 16228E-03-01 CW-1909.01


Sheet No.:


46

**100% SUBMISSION** 

PARTIAL BASEMENT PLAN MECH B12 - HVAC SCALE:  $\frac{1}{8}$ "=1'-0"








COOLING COIL DUCT INSTALLATION DETAIL

M2.1 / N.T.S.





FILL GAP COMPLETELY AROUND—PIPE WITH OR WITHOUT INSULATION
USE FILLER ROD PER MFR. AND
FILL FLUSH TO TOP OF PIPE SLEEVE

CORE DRILL

PIPE WITH OR WITHOUT INSULATION


STEEL SLEEVE: EXTEND SLEEVE MINIMUM 1" HIGHER THAN FLOOR

DETAIL-PIPE SLEEVE

M2.1 N.T.S.

4 TOILET VENT SECTION M2.1 N.T.S.





WG\ 1915—Disston recreation\ drawings\ Mechanical\ Sheets\ M=2 1 dwg

08/12/2021

Sheet No.:

16228E-03-01 CW-1909.01

46

- 2. DISCONNECT FURNISH AND INSTALLED BY E.C. LINE VOLTAGE WIRING BY E.C. INDOOR UNIT IS FED VIA OUTDOOR UNIT.
- 3. PROVIDE AS SPECIFIED OR APPROVED (BY EOR) EQUAL BY HITACHI. MITSUBISHI.
- CAPACITIES ABOVE ARE ADJUSTED JOB SPECIFIC.
- 5. PROVIDE PROGRAMMABLE WIRED CONTROLLER.

	VRF SPLIT SYSTEM SCHEDULE (OUTDOOR UNIT)  ELECTRICAL												
SYMBOL	NOM. TONS	SERVICE	REFRIGERANT	CONNECTED INDOOR UNITS	MCA	МОСР	V/PH/HZ	SEER	HSPF	HEAT CAPACITY (MBH)	COOLING CAPACITY (MBH)	BASIS OF DESIGN	NOTES
ODU - 101A	2.0	IDU - 101A	R410A	1	20	30	208 - 230 /1/60	20	12.6	-	24	DIAKIN	1, 2, 3, 4, 5, 6, 7
ODU - 101B	2.0	IDU - 101B	R410A	1	20	30	208 - 230 /1/60	20	12.6	-	24	XX	1, 2, 3, 4, 5, 6, 7
ODU - 102	1.0	IDU - 102	R410A	1	20	30	208 - 230 /1/60	20	12.6	-	12	XX	1, 2, 3, 4, 5, 6, 7
ODU - 103	1.0	IDU - 103	R410A	1	20	30	208 - 230 /1/60	20	12.6	-	12	XX	1, 2, 3, 4, 5, 6, 7
ODU - 201	1.0	IDU - 201	R410A	1	20	30	208 - 230 /1/60	20	12.6	-	12	XX	1, 2, 3, 4, 5, 6, 7
ODU - 204A	1.5	IDU - 204A	R410A	1	20	30	208 - 230 /1/60	20	12.6	-	12	XX	1, 2, 3, 4, 5, 6, 7
ODU - 204B	1.5	IDU - 204B	R410A	1	20	30	208 - 230 /1/60						
DDU - 204C	1.5	IDU - 204C	R410A	1	20	30	208 - 230 /1/60						
DDU - 204D	1.5	IDU - 204D	R410A	1	20	30	208 - 230 /1/60						

- PROVIDE LINESETS SIZES AND ACCESSORIES AS REQUIRED, INSTALL IN STRICK ACCORDANCE WITH MFR's INSTALLATION INSTRUCTIONS.
  PROVIDE EQUIPMENT BASE FOR LEVEL MOUNTING, PROVIDE PIPE PORTAL FOR REFRIGERANT AND POWER.
- DISCONNECT ALL LINE VOLTAGE WIRING BY E.C., LOW VOLTAGE BY M.C.
- PROVIDE AS SPECIFIED OR APPROVED (BY EOR) EQUAL BY HITACHI, MITSUBISHI. CONTRACTOR SHALL COORDINATE ALL'SYSTEM LAYOUT AND SIZING WITH MANUFACTURER, PROVIDE COMPONENTS NOT NECESSARY INDICATED ON PLANS.
- CONTRACTOR SHALL PROVIDE REFRIGERANT CHARGING AS REQUIRED BY MANUFACTURER. PROVIDE LOW AMBIENT WIND BAFFLE KIT. PROVIDE MINI SPLIT STANDS FOR ROOF LOCATION (18" HIGH). AS MANUFACTURER BY QUICK-SLING.

EXHAU	EXHAUST FAN SCHEDULE										
							ELEC.			BASIS OF DESIGN	
EF #	CFM	SP IN. W.G.	NOMINAL RPM	SONES	MOTOR HP /INPUT WATTS	V	RH	HZ	CATALOG NUMBER	DASIS OF DESIGN	NOTES
EF-101	150	0.25	814	2.5	66 W	115	1	60	GC-186	COOK-GEMINI CEILING FAN 100 SERIES	1, 2, 3
EF-102	225	0.25	1251	2.5	78 W	115	1	60	GC-422	COOK-GEMINI CEILING,200-700 SERIES	1, 2, 3
EF-105A	75	0.25	754	.9	30 W	115	1	60	GC-148	COOK-GEMINI CEILING FAN 100 SERIES	1, 2, 3
EF-105B	40	0.25	754	.9	30 W	115	1	60	GC-148	COOK-GEMINI CEILING FAN 100 SERIES	1, 2, 3
EF-202	75	0.25	754	.9	30 W	115	1	60	GC-148	COOK-GEMINI CEILING FAN 100 SERIES	1, 2, 3

- 1. EXHAUST FAN NUMBERS ARE THE SAME AS ROOM NUMBERS.
- 2. PROVIDE WALL CAP, COLOR SELECTED BY ARCHITECT.
- 3. FAN SPEED CONTROLLER 5 AMP 120 VOLT, GEMINI ISOLATOR KIT-ISOLATORS.

**APPROVED:** ARCHITECT/ENGINEER OF RECORD DATE APPROVED FOR BID: REBUILD PROJECT MANAGER DATE CONVERSE · WINKLER ARCHITECTURE MARK ULRICK ENGINEERS, INC. DESCRIPTION **DISSTON REC CENTER UPGRADES** MECHANICAL SCHEDULES **100% SUBMISSION RAVI JETHANI CONVERSE WINKLER ARCHITECTURE** WJB/GB

08/12/2021

Sheet No.:

16228E-03-01 CW-1909.01

46

### **GENERAL NOTES**

- 1. THE SUBMISSION OF A PROPOSAL BY THE CONTRACTOR IS NOTIFICATION THAT HE HAS TOTALLY FAMILIARIZED HIMSELF WITH THE CONTRACT DOCUMENTS AND EXISTING SITE CONDITIONS AND HAS AGREED TO PROVIDE THE NECESSARY LABOR AND MATERIAL FOR THE COMPLETE INSTALLATION OF EACH SYSTEM IN A NEAT AND WORKMANLIKE MANNER IN ACCORDANCE WITH THE BEST PRACTICES OF THE INDUSTRY AND IN COMPLIANCE WITH ALL AUTHORITIES HAVING JURISDICTION.
- 2. THE CONTRACT DRAWINGS ARE PRESENTED TO THE CONTRACTOR WITH THE UNDERSTANDING THAT HE IS AN EXPERT AND COMPETENT IN THE PREPARATION OF CONTRACT BID PRICES ON THE BASIS OF INFORMATION SUCH AS CONTAINED IN THE CONTRACT DOCUMENTS, IT IS THE INTENT OF THE CONTRACT DRAWINGS AND SPECIFICATIONS TO CALL FOR FINISHED WORK. TESTED AND READY FOR OPERATION AND IN COMPLETE CONFORMANCE WITH ALL APPLICABLE CODES, RULES AND REGULATIONS, MINOR ITEMS NOT USUALLY SHOWN OR SPECIFIED, BUT MANIFESTED NECESSARY FOR THE PROPER INSTALLATION AND OPERATION OF THE VARIOUS SYSTEMS SHALL BE INCLUDED IN THE WORK AND IN THE PROPOSAL THE SAME AS SPECIFIED OR SHOWN ON THE CONTRACT DRAWINGS. IF ANY DEPARTURES FROM THE CONTRACT DRAWINGS ARE DEEMED NECESSARY, DETAILS OF SUCH DEPARTURES AND THE REASON THEREFORE SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL, NO DEPARTURES SHALL BE MADE WITHOUT PRIOR APPROVAL OF THE ENGINEER.
- 3. VISIT THE SITE AND VERIFY ALL DIMENSIONS IN THE FIELD. AND ADVISE THE ARCHITECT / ENGINEER AND THE OWNER OF ANY DISCREPANCIES BEFORE PERFORMING THE WORK.
- 4. THE CONTRACT DOCUMENTS INDICATE ARRANGEMENTS AND APPROXIMATE SIZES AND RELATIVE LOCATIONS OF PRINCIPAL APPARATUS, EQUIPMENT. DEVICES AND SERVICES TO BE PROVIDED. CONTRACT DRAWINGS ARE DIAGRAMMATIC AND ARE A GRAPHIC REPRESENTATION OF CONTRACT REQUIREMENTS TO BEST AVAILABLE STANDARDS AT THE SCALE INDICATED.
- 5. LAYOUT OF EQUIPMENT INDICATED ON THE CONTRACT DRAWINGS SHALL BE CHECKED AND COMPARED AGAINST ALL DRAWINGS AND SPECIFICATIONS OF ALL TRADES AND EXACT LOCATIONS USING APPROVED SHOP DRAWINGS OF SUCH EQUIPMENT. WHERE PHYSICAL INTERFERENCE OCCURS, CONSULT WITH ENGINEER AND PREPARE DATED, DIMENSIONED DRAWINGS COORDINATED WITH ALL OTHER TRADES WORK IN THE AREA AND CORRECTING SUCH INTERFERENCES. OBTAIN WRITTEN APPROVAL OF ENGINEER FOR SUCH DRAWINGS AND DISTRIBUTE SAME AS REQUIRED.
- 6. COORDINATE ALL WORK WITH THE OWNER AND ALL OTHER CONTRACTORS. SCHEDULE WORK IN ACCORDANCE WITH THE CONSTRUCTION SCHEDULE SO THAT ALL THE WORK CAN BE INSTALLED WITHOUT DELAYING THE PROJECT.
- 7. PREPARE FULLY DIMENSIONED FIELD INSTALLATION DRAWINGS. THESE DRAWINGS SHALL BE FORWARDED TO ALL CONTRACTORS. EACH CONTRACTOR SHALL SUBSEQUENTLY IN SUCCESSION DELINEATE HIS RESPECTIVE WORK ON THESE COORDINATION DRAWINGS. WHEN ALL WORK HAS BEEN PROPERLY SHOWN ON THE COORDINATION DRAWINGS. AND ALL CONTRACTORS AGREE THAT THEIR RESPECTIVE WORK CAN BE INSTALLED AND WILL PROPERLY FIT TOGETHER, THEY SHALL SO ACKNOWLEDGE BY ENDORSING THE DRAWING(S). ANY WORK DONE PRIOR TO COMPLETION OF ABOVE COORDINATION PROCESS FOUND IN CONFLICT SHALL BE REMOVED AND REPLACED AT CONTRACTOR'S EXPENSE.
- 8. SECURE AND PAY ALL FEES AND PERMITS PERTAINING TO THE CONTRACT.
- 9. ALL EQUIPMENT SHALL BE INSTALLED IN STRICT COMPLIANCE WITH THE MANUFACTURER'S WRITTEN INSTRUCTIONS.
- 10. SCHEDULE ALL SHUTDOWNS THAT EFFECT UTILITIES AND PORTIONS OF THE BUILDING THAT MUST REMAIN IN OPERATION WITH THE OWNER.
- 11. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL RIGGING. HANDLING AND PROTECTION OF MATERIALS. ALL EQUIPMENT AND MATERIALS SHALL BE NEW AND WITHOUT BLEMISH OR DEFECT.
- 12. WHERE PIPING PASSES THROUGH FIRE RATED FLOORS AND WALLS. THE PENETRATION SHALL BE COMPLETELY SEALED WITH A FIRE STOP MATERIAL THAT IS ULLISTED AND ACCEPTED BY THE BUILDING DEPARTMENT AND FIRE DEPARTMENT AS BEING SUITABLE FOR THIS SERVICE. THIS MATERIAL SHALL BE INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF THE MANUFACTURER TO MAINTAIN THE ULLISTED FIRE RATING OF THE PENETRATED WALL OR FLOOR.
- 13. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL SLAB OPENINGS, WALL OPENINGS, AND CORING AS IT RELATES TO HIS WORK. CONTRACTOR SHALL SUBMIT SIZE AND LOCATION TO THE STRUCTURAL ENGINEER FOR REVIEW AND APPROVAL, STRUCTURAL ELEMENTS SHALL NOT BE PENETRATED WITHOUT PRIOR APPROVAL OF STRUCTURAL ENGINEER.
- 14. SUBMIT SCHEDULE OF SUBMITTALS PRIOR TO SUBMITTING ANY SHOP DRAWINGS. THIS SCHEDULE SHALL IDENTIFY ALL PRODUCT DATA, DRAWINGS, ETC. TO BE SUBMITTED FOR THIS PROJECT, INCLUDING ANY ANTICIPATED DATE OF EACH SUBMISSION. COMPLY WITH THE REQUIREMENTS OF DIVISION 1 OF THE SPECIFICATIONS. ANY WORK INSTALLED OR EQUIPMENT PURCHASED PRIOR TO RECEIPT OF ENGINEER REVIEWED SHOP DRAWINGS THAT REQUIRES CHANGES SHALL BE REPLACED AT CONTRACTOR EXPENSE.
- 15. SUBMIT CATALOG INFORMATION, FACTORY ASSEMBLY DRAWINGS AND FIELD INSTALLATION DRAWINGS AS REQUIRED FOR A COMPLETE EXPLANATION AND DESCRIPTION OF ALL ITEMS PROVIDED. THE CONTRACTOR SHALL REVIEW AND APPROVE ALL SHOP DRAWINGS, NO SUBMISSION SHALL BE ACCEPTED WITHOUT THE SIGNED APPROVAL OF THE CONTRACTOR, THE CONTRACTOR SHALL CHECK AND VERIFY ALL FIELD MEASUREMENTS.
- 16. PROVIDE AS-BUILT DOCUMENTS AND OPERATING / MAINTENANCE MANUALS AS SPECIFIED IN DIVISION 1 OF THE SPECIFICATIONS.
- 17. INSTALLED SYSTEMS SHALL OPERATE UNDER ALL CONDITIONS OF LOAD WITHOUT SOUND OR VIBRATION THAT IS OBJECTIONABLE TO THE ENGINEER, ARCHITECT OR OWNER, OBJECTIONABLE SOUND OR VIBRATION CONDITIONS SHALL BE CORRECTED IN APPROVED MANNER BY THE CONTRACTOR AT HIS EXPENSE.
- 18. FURNISH ACCESS DOORS AS REQUIRED FOR OPERATION AND MAINTENANCE OF CONCEALED EQUIPMENT, VALVES AND CONTROLS, ETC., AND COORDINATE THEIR DELIVERY WITH THE INSTALLING TRADE.
- 19. ALL WORK FURNISHED UNDER THE CONTRACT SHALL BE GUARANTEED AGAINST ANY AND ALL DEFECTS IN WORKMANSHIP AND/OR MATERIALS FOR A PERIOD OF NOT LESS THAN ONE (1) YEAR FROM THE DATE OF FINAL ACCEPTANCE OF THE INSTALLATION. ANY DEFECTS OF WORKMANSHIP DEVELOPING DURING THIS PERIOD SHALL BE REMEDIED AND ANY DEFECTIVE MATERIAL REPLACED WITHOUT ADDITIONAL COST.
- 20. NOTIFY ENGINEER OF ESTIMATED DATE OF COMPLETION OF ROUGH-IN WORK AND DATE OF BOTH WALL AND CEILING INSTALLATION. NOTIFICATION SHALL BE A MINIMUM OF ONE WEEK PRIOR TO COMPLETION DATE TO ENABLE ENGINEER SCHEDULING OF PRELIMINARY PUNCHLIST INSPECTION PRIOR TO WALL AND CEILING INSTALLATION. CONTRACTOR SHALL SIMILARLY NOTIFY ENGINEER OF COMPLETION OF ALL WORK, INDICATING THE CONTRACTOR IS READY FOR THE ENGINEER TO PERFORM THE FINAL PUNCHLIST INSPECTION.
- 21, UPON COMPLETION OF ALL UNFINISHED OR FAULTY WORK NOTED IN ENGINEER'S PUNCHLIST, THE CONTRACTOR SHALL SUBMIT TO THE ENGINEER IN WRITING A LETTER OF COMPLETION CERTIFYING THAT ALL PUNCHLIST ITEMS HAVE BEEN COMPLETED AND ALL AS-BUILTS. MANUALS, ETC. HAVE BEEN SUBMITTED.

ABBREVIATIONS									
AAV ABV AD AFF AFG ALUM AP	AUTOMATIC AIR VENT ABOVE ACCESS DOOR ABOVE FINISHED FLOOR ABOVE FINISHED GRADE ALUMINUM ACCESS PANEL	ID I.E. IN INV KS L	INDIRECT DRAIN INVERT ELEVATION INCH INVERT KITCHEN SINK LENGTH						
ATC AUTO AV BLDG BLW BOT	AUTOMATIC TEMPERATURE CONTROL AUTOMATIC AIR VENT, ACID VENT BUILDING BELOW BOTTOM	LAV LWT MAX MBH MH MIN	LAVATORY LEAVING WATER TEMPERATURE  MAXIMUM THOUSAND BTU PER HOUR MANHOLE MINIMUM						
BFP BFF BTU BV CAP CFH CFM	BACKFLOW PREVENTOR BELOW FLOOR BRITISH THERMAL UNIT BALANCING VALVE CAPACITY CUBIC FEET PER HOUR CUBIC FEET PER MINUTE	N (N) NA NC NO NTS	NORTH NEW NOT APPLICABLE NORMALLY CLOSED NUMBER, NORMALLY OPEN, NOT TO SCALE						
CI CLG CO	CAST IRON CEILING CLEAN OUT	OF OPER	OVERFLOW DRAIN OPERATING						
CONT. CW D DCW DD DEG DELIV DEMO	CONTINUED COLD WATER  DRAIN  DOMESTIC COLD WATER  DIRECT DRIVE  DEGREE  DELIVERY  DEMOLITION	P PG PH PLBG PRS PRV PSI PSIG	PUMP PRESSURE GAUGE PHASE PLUMBING PRESSURE REDUCING STATION PRESSURE REDUCING VALVE POUNDS PER SQUARE INCH POUNDS PER SQUARE INCH GAUGE						
DHW DHWR DIA. DISC DN DS DWG	DOMESTIC HOT WATER DOMESTIC HOT WATER HEATER DOMESTIC HOT WATER RETURN DIAMETER DISCONNECT DOWN DOWNSPOUT DRAWING	R RAC RED REL RD RBF RM RPZ	TO BE REMOVED RUN AT CEILING REDUCER RELIEF ROOF DRAIN RUN BELOW FLOOR ROOM REDUCE FLOW BACKFLOW PREVENTOR						
E (E) EFF ELEC EL. ENCL	EAST EXISTING EFFICIENCY ELECTRIC ELEVATION ENCLOSE (ENCLOSURE)	RWC RWL S SAN SD	RAINWATER CONDUCTOR RAIN WATER LEADER SOUTH SANITARY STORM DRAIN						
ENCL ENT EQ. ESPP ETR EWC EWT	ENCLOSE (ENCLOSORE) ENTERING EQUIPMENT ELEVATOR SUMP PIT PUMP EXISTING TO REMAIN ELECTRIC WATER COOLER ENTERING WATER TEMPERATURE	SH SP SPEC SQ SS STW	SHOWER SUMP PUMP SPECIFICATIONS SQUARE SERVICE SINK STORM WATER						
F FA FCO FD FDS FIN	FAHRENHEIT, DEGREE FAHRENHEIT FROM ABOVE FLOOR CLEANOUT FLOOR DRAIN FLOOR DRAIN SUMP FINISHED	STR T TD TH TYP	STRAINER  TEMPERED WATER TRENCH DRAIN THERMOMETER TYPICAL						
FL FM FPM FPS FT FU	FLOOR FLOOR MOUNTED FEET PER MINUTE FEET PER SECOND FEET FIXTURE UNIT	UDS UL UN V	UNDER DRAIN SUMP UNDERWRITER'S LABORATORY UNION VENT						
FV GPH GPM GTV HB	FLUSH VALVE  GALLONS PER HOUR  GALLONS PER MINUTE  GATE VALVE  HOSE BIBB  HANDICARPED	VERT VTR W WC WCO WH	VERTICAL VENT THROUGH ROOF  WASTE WATER CLOSET WALL CLEAN OUT WALL HYDRANT						

WASHING MACHINE

WATER PRESSURE DROP

HANDICAPPED

**HUB DRAIN** 

HORIZONTAL

HOT WATER

HOT WATER GENERATOR


HOT WATER HEATER HOT WATER RETURN


HOUR

HEIGHT

**HORSEPOWER** 

### PLUMBING SYMBOLS





DISSTON REC CENTER **UPGRADES** 

Sheet Title:


PLUMBING **COVER SHEET** 

**RAVI JETHANI CONVERSE WINKLER ARCHITECTURE** WJB/GB 08/12/2021 UJ 16228E-03-01 P-0.0 CW-1909.01

Sheet No.:


46

100% SUBMISSION



PARTIAL FIRST SANITARY FLOOR PLAN

SCALE: \(\frac{1}{4}\)"=1'-0"



PARTIAL FIRST FLOOR DOMESTIC WATER PLAN SCALE: \(\frac{1}{2}\)"=1'-0"

#### PLUMBING NOTES

- 1. PLUMBING DRAWINGS ARE DIAGRAMMATIC IN NATURE, PLUMBING CONTRACTOR SHALL SURVEY AND VERIFY EXISTING CONDITIONS PRIOR TO CONSTRUCTION
- ALL DOMESTIC WATER AND VENT PIPING ASSUMED TO BE ABOVE THE CEILING. SANITARY PIPING ASSUMED TO BE BELOW FLOOR UNLESS OTHERWISE NOTED.
   RAIL CURBS FOR CONDENSING UNITS INTERFERE WITH DRAINAGE
- . RAIL CURBS FOR CONDENSING UNITS INTERFERE WITH DRAINAGE
  AT THE ROOF OF THE LINK. ADDITIONAL DRAIN LOCATIONS MAYBE
  REQUIRED.
- 4. ALL INTERIOR ROUTED RAIN WATER CONDUCTORS ARE BEING RELOCATED TO EXTERIOR CONDITIONS

APPROVED: ARCHITECT/ENGINEER OF RECORD DATE APPROVED FOR BID: REBUILD PROJECT MANAGER DATE CONVERSE · WINKLER : ARCHITECTURE MARK ULRICK ENGINEERS, INC. DESCRIPTION **DISSTON REC CENTER UPGRADES** PLUMBING PARTIAL **FLOOR PLAN 100% SUBMISSION RAVI JETHANI CONVERSE WINKLER ARCHITECTURE** WJB/GB 08/12/2021 16228E-03-01 CW-1909.01

46

2" V----

PLAN	MBING FIXTURE	1 454	DECORIDE ON THE STATE OF THE ST	CONNECTIONS				
MARK	FIXTURE TYPE	ADA	DESCRIPTION	MANUFACTURER & MODEL NUMBER	SAN.	VENT	C.W.	H.W.
WC	WATER CLOSET	NO	ELONGATED, 1.1 GPF SELECTRONIC FLUSH VALVE, SIPHON JET, VITREOUS CHINA, WALL HUNG, REAR OUTLET 1-1/2" INLET SPUD	AMERICAN STANDARD AFWALL MODEL 2257.711	4"	2"	1 1/4"	
WC-A	WATER CLOSET	WATER CLOSET YES VALVE, SIPHON JET, VITREOUS CHINA, WALL AFWALL		AMERICAN STANDARD AFWALL MODEL 2257.711	4"	2"	1/2"	
UR	URINAL YES		1.0 GPF, ELONGATED RIM, VITREOUS CHINA, BLOW-OUT FLUSH, 1-1/4" INLET SPUD, 5/8" DRAIN PLUG.	KOHLER STANWELL K-4972-ET		2"	3/4"	
LAV	LAVATORY		SOLID SURFACE WITH INTEGRAL BOWLS, PROVIDE FAUCET ONLY. AMERICAN STANDARD LAV. FOR PUBLIC RESTROOMS	CHICAGO FAUCETS ELECTRONIC FAUCETS 116.606.21.1	1 1/2"	1 1/2"	1/2"	1/2*
LAV	LAVATORY YES FAUCET TO MATCH LAV FOR STAFF RESTROOM ONI		FAUCET TO MATCH LAV FOR STAFF RESTROOM ONLY	AMERICAN STANDARD LUCERNE WALL HUNG 0356	1 1/2"	1 1/2"	1/2"	1/2"
EWC-1	DRINKING FOUNTAIN			ELKAY — #EZS8WSVRSK, 115V/ 60HZ, 8 GPH BOTTLE FILLER W/ COOLER	3"	1 1/2"	1/2"	
MR	MOP RECEPTOR		FLOOR MOUNTED, BUMPER GUARDS T&S — B-0665-BTSR CHROME FAUCET	FIAT - #MSB-2424 24"X24"X10"	3"	1 1/2"	1/2"	1/2'

1. SUPPLY FIXTURE WITH ¼" TURN SHUT OFF VALVES ON DOMESTIC WATER LINES AT AN ACCESSIBLE LOCATION TO THE FIXTURE 2. FIXTURE PROVIDED WITH CABINETRY AND INSTALLED BY THE GENERAL CONTRACTOR — SEE ARCHITECTURAL DRAWINGS AND SPECIFICATION FOR FIXTURE THIS CONTRACTOR TO PROVIDE ALL MATERIAL NECESSARY TO FULLY PLUMB FIXTURE AND ALL

ACCESSORIES SHOWN PER MANUFACTURER'S RECOMMENDATIONS.

3. PROVIDE WITH CLOSET FLANGE AND EXTRA WAX RING.


BUILDING SYSTEM SERVED	
SANITARY AND VENT- ABOVE GROUND	CAST IRON- NO HUB
SANITARY AND VENT 2" AND UNDER	COPPER DRAINAGE TUBE, DWV
DOMESTIC WATER	COPPER WATER TUBE, TYPE K, L, M (PRESS FIT)

ACCEPTABLE MATERIAL

PIPE SCHEDULE


	PLUMBING DE	JMBING DRAINAGE SPECIALTY SCHEDULE								
	SYMBOL	LOCATION	DESCRIPTION	BASIS OF DESIGN						
	STIVIBOL			MANUFACTURER	TYPE	MODEL NUMBER	STRAINER	RECEPTOR	REMARKS	
	FD-1	COMMON AREA	FLOOR DRAIN	J.R. SMITH	ROUND BODY WITH FLASHING COLLAR	2005Y	BRONZE, ADJUSTABLE	DUCO, CAST IRON BODY	OUTLET SAME SIZE AS DRAINAGE PIPE INDICATED WITH DEEP SEAL TRAP AND PROVENT PROSET TRAP	

APPROVED: ARCHITECT/ENGINEER OF RECORD DATE APPROVED FOR BID: REBUILD PROJECT MANAGER DATE CONVERSE · WINKLER : ARCHITECTURE MARK ULRICK ENGINEERS, INC. **DISSTON REC CENTER UPGRADES** PLUMBING DIAGRAMS AND SCHEDULES 100% SUBMISSION Engineering Manager: RAVI JETHANI CONVERSE WINKLER ARCHITECTURE WJB/GB 08/12/2021 16228E-03-01 CW-1909.01 46



NOTES:

- 1. NO STRUCTURAL STRAIN SHOULD BE TRANSMITTED FROM ANY WALL TO THE PIPING SYSTEM. THE SLEEVING, RELIEVING ARCH, OR STRUCTURAL BEAM SUPPORT METHODS
  PROTECT THE PIPING FROM SUPERIMOSED LOADS. THE "PACKING" MATERIAL AROUND THE
  PIPE IS FLEXIBLE ENOUGH TO RESPOND TO SETTLING IN THE STRUCTURE OR PIPING.
- 2. FIRE RATED PACKING MATERIAL TO BE BY 3M. CAULK CP 25N/S
- 3. FOR ALL PIPING PASSING THRU MEZZANINE FLOOR PACK WITH 3M, CAULK CP255/L
- 4. SEE ARCHITECTURAL DRAWINGS FOR FIRE RATED WALLS.




CONCRETE AND FOUNDATION WALLS


SEDIMENT BUCKET, WHERE APPLICABLE -FIN. FLOOR (ALLOW - FOR MATERÌALS) FLOOR DRAIN -PROVIDE PROSET TRAP GUARDS ON ALL FLOOR DRAINS AS AN ALTERNATE TRAP PRIMER.



NO STRUCTURAL STRAIN SHOULD BE TRANSMITTED FROM ANY WALL TO THE PIPING SYSTEM. THE SLEEVING, RELIEVING ARCH, OR STRUCTURAL BEAM SUPPORT METHODS PROTECT THE PIPING FROM SUPERIMOSED LOADS. THE "PACKING" MATERIAL AROUND THE PIPE IS FLEXIBLE ENOUGH TO RESPOND TO SETTLING IN THE STRUCTURE OR PIPING.







SIZE OF CLEANOUT

NOMINAL

CLEANOUT SIZE

(INCHES)

1-1/4

1-1/2

NOMINAL


PIPING SIZE


(INCHES)

1-1/2

4 AND 6 8 AND 10


TYPICAL PIPE HANGER DETAIL






5 FLOOR AND WALL CLEANOUT DETAIL

NTS





**DISSTON REC CENTER UPGRADES** 

PLUMBING DETAILS

Engineering Manager:					
Consultant:	CONVERSE WINKLER ARCHITECTUR				
Task No.:		Drawn By:	WJB/GB		
Date: 08/12	2/2021	Checked By:	UJ		

100% SUBMISSION

16228E-03-01 CW-1909.01

### ELECTRICAL LEGEND HOMERUN TO DESIGNATED PANEL IN MINIMUM 3/4" CONDUIT WITH AN INSULATED GROUND WIRE. U.O.N. "X-1" INDICATES PANELBOARD AND CIRCUIT NO. RESPECTIVELY. CIRCUIT (IN MINIMUM 3/4"C, UON) CONCEALED IN WALL OR ABOVE CEILING WITH MINIMUM INSULATED GROUND WIRE (MINIMUM #12 AWG, UON) FOR EACH CONDUIT RUN #12 AWG WIRE. NO. OF HATCHES INDICATE NO. OF PHASE & NEUTRAL WIRES. DISCONNECT SWITCH IN NEMA TYPE-1 ENCLOSURE, NONFUSED, LOCKABLE HANDLE, AMP/VOLTAGE/POLE 2/40 AS NOTED ON DRAWING. (2 POLE 60 SWITCH 40A FUSES) PANELBOARD 120/208V. WALL MOUNTED. TOP CB IN PANEL SHALL BE MAXIMUM 72" AFF. 20A,120-277V,1P TOGGLE SWITCH, MH = 48"AFF 20A,1P,3WAY 120-277V TOGGLE SWITCH, MH = 48"AFF FRACTIONAL HORSE POWER MANUAL STARTER SWITCH MELTING ALLOY TYPE THERMAL OVERLOAD, 2 POLES, 125V WITH RED PILOT LIGHT IN NEMA 3R ENCLOSURE, WALL MOUNTED AT 48"AFF. 20A,1P,3-WAY,120-277V DIMMER SWITCH, 1500 W, MH = 48" AFF. COMBINATION MAGNETIC MOTOR STARTER. FURNISHED BY MECHANICAL, INSTALLED BY ELECTRICAL. DENOTES DRAWING NOTES. RECESSED LIGHTING FIXTURE. LETTER DESIGNATIONS CORRESPOND TO LIGHTING FIXTURE SCHEDULE. CROSS HATCHING IN FIXTURE INDICATES A FIXTURE ON AN EMERGENCY CIRCUIT. WALL MOUNTED LIGHTING FIXTURE. LETTER DESIGNATIONS CORRESPOND WITH LIGHTING FIXTURE SCHEDULE. UNIVERSAL MOUNTED EMERGENCY EXIT SIGN, CEILING MOUNTED, WALL MOUNTED. SELF CONTAINED EMERGENCY LIGHTING - SINGLE HEAD UNIT, DUAL HEAD UNIT 2'X2' LED FIXTURE. LETTER DESIGNATIONS CORRESPOND TO LIGHTING FIXTURE SCHEDULE. 2'X4' LED FIXTURE. LETTER DESIGNATIONS CORRESPOND TO LIGHTING FIXTURE SCHEDULE. LED FIXTURE. LETTER DESIGNATIONS CORRESPOND TO LIGHTING FIXTURE SCHEDULE. 4' LED FIXTURE. DIAGONAL LINE INDICATED FIXTURE WITH INTEGRAL BATTERY PACK. UPPER CASE LETTER DESIGNATIONS CORRESPOND TO LIGHTING FIXTURE SCHEDULE $\bigcirc$ EXHAUST FAN WALL MOUNTED OCCUPANCY SENSOR SWITCH MH=48" A.F.F. CEILING MOUNTED OCCUPANCY SENSOR FIRE ALARM SYSTEM SMOKE DETECTOR

### GENERAL ELECTRICAL NOTES

1. ALL ELECTRICAL MATERIAL AND INSTALLATION SHALL BE IN CONFORMITY WITH THE APPLICABLE CURRENT STANDARDS, RULES, REGULATIONS, AND SPECIFICATIONS OF THE FOLLOWING AUTHORITIES:

-NFPA 70 (NATIONAL ELECTRICAL CODE)
-NFPA 101 (LIFE SAFETY CODE)
-NBFU (NATIONAL BOARD OF FIRE UNDERWRITERS)
-ADA (AMERICANS WITH DISABILITIES ACT)
-NEMA (NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION)

2. THE ELECTRICAL CONTRACTOR SHALL FURNISH ALL LABOR AND MATERIALS AS REQUIRED TO MEET THE DESIGN INTENT OF THESE DOCUMENTS. COORDINATE WITH FIELD CONDITIONS AT THE JOB SITE AND ALL OTHER TRADES TO DETERMINE ALL ELECTRICAL CONNECTIONS THAT MAY BE REQUIRED. ALL ELECTRICAL MATERIAL AND WORK SHALL HAVE A MINIMUM ONE YEAR GUARANTEE PERIOD TO BEGIN AT THE DATE OF FINAL ACCEPTANCE BY THE OWNER.

3. THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR SECURING ALL REQUIRED PERMITS AND INSPECTIONS FROM THE AUTHORITY HAVING JURISDICTION.

4. ALL WIRING INSTALLED WITHIN A RETURN AIR PLENUM SHALL BE RATED FOR SUCH AN APPLICATION.

5. INSTALL CONDUIT AND JUNCTION BOXES CONCEALED IN FINISHED SPACES.

6. ALL EQUIPMENT SHALL BE UL LISTED AND LABELED.

-IEEE (INSTITUTE OF ELECTRICAL AND ELECTRONIC ENGINEERS

-ANSI (AMERICAN NATIONAL STANDARDS INSTITUTE)

-ALL LÒCAL AUTHORITIES HAVING JURISDICTION

7. ALL CONDUCTORS SHALL BE IDENTIFIED. ALL CONDUCTORS SHALL BE COPPER WITH 600V INSULATION. CONDUCTORS #10 AWG AND SMALLER SHALL BE SOUD COPPER WITH TYPE THHN/THWN, 90\*C INSULATION. ALL CONDUCTORS 8 AWG AND LARGER SHALL BE STRANDED COPPER WITH TYPE THHN/THWN INSULATION RATED AT 9CTC. AMPACITY OF CONDUCTORS SHALL BE AT 75\*C RATING OR RATING OF TERMINATION, WHICHEVER IS LESS.

8. ELECTRICAL CONTRACTOR SHALL USE CONDUIT AND WIRE FOR INTERIOR. DRY, FURRED LOCATIONS WHEN PERMITTED BY THE LOCAL AUTHORITY HAVING JURISDICTION.

9. PROVIDE "HACR" CIRCUIT BREAKERS FOR HVAC EQUIPMENT.

10. CIRCUIT NUMBERS ARE FOR IDENTIFICATION PURPOSES ONLY. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING FOR CORRECT PHASING WITHIN THE PANELS THEMSELVES. DO NOT INSTALL MORE THAN (3) SINGLE PHASE CIRCUITS WITHIN ANY ONE CONDUIT. AT COMPLETION OF WORK, ALL PANELS SHALL BE LOAD BALANCED UNDER NORMAL OPERATING CONDITIONS; PROVIDE TYPEWRITTEN PANEL DIRECTORY FOR ALL PANELBOARDS. DIRECTORY SHALL INCLUDE TYPE OF LOAD SERVED AND ROOM NUMBERS OF CIRCUIT LOCATION.

11. THE QUANTITY OF WIRES FOR CIRCUITS SHALL BE AS INDICATED AT THOSE AREAS WHERE CLARIFICATION IS REQUIRED IN ORDER TO INSURE THE PROPER OPERATION OF THE SYSTEM.

12. WIRING SHALL BE #12 AWG MINIMUM UNLESS OTHERWISE INDICATED; CONDUIT SHALL BE EMT WITH COMPRESSION FITTINGS, 3/4\* MINIMUM SIZE UNLESS OTHERWISE INDICATED.

13. COORDINATE ALL LIGHT FIXTURE TYPES WITH THE ARCHITECTURAL DRAWINGS. SHOULD THERE BE A DISCREPANCY BETWEEN THE TWO, CONTACT THE ARCHITECTURAL PRIOR TO THE

MINIMUM. ALL WRITTEN DIMENSIONS ON THESE PLANS SHALL TAKE PRIORITY OVER SCALED DIMENSIONS. CONTACT ARCHITECT SHOULD THERE BE ANY DISCREPANCIES BETWEEN WHAT IS SHOWN ON THE PLANS AND WHAT EXISTS IN THE FIELD PRIOR TO COMMENCEMENT OF WORK SHOULD EXACT DIMENSIONS BE REQUIRED, REFER TO THE ARCHITECTURAL PLANS.

15. MOUNTING HEIGHTS OF DEVICES. UNLESS NOTED OTHERWISE, ARE TO THE CENTERLINE OF THE EQUIPMENT. THE EXCEPTION TO THIS IS LIGHTING FIXTURES; MOUNTING HEIGHTS INDICATED ARE TO THE BOTTOM OF THE FIXTURE. COORDINATE ALL MOUNTING HEIGHTS OF THE VARIOUS DEVICES IN ORDER TO PROVIDE FOR A FINAL INSTALLATION THAT IS CONSISTENT.

16. ANY CUTTING AND PATCHING SHALL BE PERFORMED IN A MANNER THAT IS ACCEPTABLE TO THE ARCHITECT AND SHALL MATCH THE SURROUNDING SURFACES.

17. VERIFY DOOR SWINGS PRIOR TO LIGHT SWITCH INSTALLATION. GENERALLY, INSTALL SWITCHES ON LATCH SIDE OF DOOR.

18. GANG MULTIPLE SWITCHES UNDER ONE COVER PLATE.

19. COORDINATE WITH THE ARCHITECTURAL DRAWINGS FOR EXACT LOCATIONS OF ALL OUTLETS. SWITCHES, AND LIGHTING FIXTURES; DO NOT USE ENGINEERING PLANS FOR LOCATING DEVICES. SHOULD A CONTRACTOR PLACE A DEVICE BASED ON THE ENGINEER'S PLANS AND IT IS NOT LOCATED AS PER THE ARCHITECT'S PLANS, THE CONTRACTOR SHALL BE RESPONSIBLE FOR ITS RELOCATION AT HER/HIS COST.

20. OUTLET BOXES SHALL BE INSTALLED SUCH THAT THEY ARE NOT BACK—TO—BACK; PROVIDE AN 8" MINIMUM OFFSET. ALL ELECTRICAL OUTLETS SHALL HAVE A TAG BEHIND THE COVERPLATE INDICATING THE PANELBQARD AND CIRCUIT NUMBER FROM WHICH THEY ARE FED.

COVERPLATE INDICATING THE PANELBQARD AND CIRCUIT NUMBER FROM WHICH THEY ARE FED.

21. ELECTRICAL CONTRACTOR SHALL SUBMIT SHOP DRAWINGS FOR ALL EQUIPMENT. IF APPROVED SUBMITTALS ARE FOR EQUIPMENT THAT DIFFERS WITH WHAT WAS SPECIFIED BY THE DESIGN ENGINEER, THE CONTRACTOR SHALL BE ENTIRELY RESPONSIBLE FOR INSURING THAT THIS EQUIPMENT IS EQUIVALENT TO THE ORIGINAL SPECIFIED EQUIPMENT AND ANY ADDITIONAL WORK OR COST AS A RESULT OF USING DIFFERING EQUIPMENT SHALL BE ABSORBED BY THE CONTRACTOR.

22. THE ELECTRICAL SYSTEM SHALL BE FULLY GROUNDED; PROVIDE SEPARATE GROUND WIRE IN FEEDER AND EACH BRANCH CIRCUIT WHETHER INDICATED ON THE PLANS OR NOT.
 23. WIRING FOR 20A BRANCH CIRCUITS SHALL BE SIZED AS INDICATED BELOW.
 120V

CIRCUIT LENGTH (FT.) AWG CIRCUIT LENGTH (FT.) AWG 0-75 #12 0-150 #12 75-150 #10 151-300 #10 151-200 #8 301-400 #8

24. WORK AREA SHALL BE LEFT CLEAN AT THE END OF EACH BUSINESS DAY.

25. ALL PENETRATIONS OF FIRE RATED WALL ASSEMBLES SHALL BE PROTECTED WITH AN APPROVED FIRESTOP SYSTEM OR IN ACCORDANCE WITH IBC SECTION 712.3.1 WHERE APPLICABLE.

26. ALL DISCONNECT SWITCH CURRENT CARRYING COMPONENTS SHALL BE COPPER.

27. THE CONTRACTOR SHALL VERIFY THAT ALL THE LIGHTING FIXTURES, RECEPTACLES, DEVICES, WIRING, EQUIPMENT, AND THEIR INSTALLATION COMPLY WITH ALL THE NEC AND LOCAL CODE REQUIREMENTS FOR THE TYPE OF CONSTRUCTION AND OCCUPANCY REQUIREMENTS FOR THIS PROJECT. PROVIDE HANGERS AS PROJUBED BY CODE

28. THE CONTRACTOR SHALL FURNISH AND INSTALL THE LIGHTING FIXTURES AS SHOWN ON THE ARCHITECTURAL REFLECTED CEILING PLAN. IF THERE IS NO ARCHITECTURAL REFLECTED PLAN, CONTRACTOR SHALL COORDINATE LOCATION OF FIXTURES SHOWN ON THE ELECTRICAL PLANS WITH ARCHITECT AND OTHER TRADES AND FIELD CONDITIONS.

29. THE CONTRACTOR SHALL FURNISH AND INSTALL ALL LAMPS REQUIRED (ALL LAMPS FOR SIMILAR FIXTURES SHALL MATCH). VERIFY MANUFACTURER AND MODEL OF BASE BUILDING FIXTURES WITH THE BUILDING OWNER'S REPRESENTATIVE.

30. THE FINAL LOCATION OF SWITCHES, OUTLETS AND OTHER DEVICES SHALL BE FIELD COORDINATED AND SHALL MEET ALL LOCAL CODE REQUIREMENTS (INCLUDING ALL HANDICAPPED CODES AND ADA REQUIREMENTS).

31. THE CONTRACTOR SHALL BE RESPONSIBLE! FOR TESTING ALL CIRCUITS. LIGHTING FIXTURES, OUTLETS AND ALL OTHER DEVICES FOR THEIR PROPER OPERATION (INCLUDING ALL GROUNDING).

32. THE CONTRACTOR SHALL BE RESPONSIBLE FOR SCHEDULING AND PERFORMING ALL TEST AND INSPECTIONS REQUIRED BY THE LOCAL CODES AND AUTHORITIES HAVING JURISDICTION.

33. THE CONTRACTOR SHALL REFER TO THE MANUFACTURER'S INSTALLATION INSTRUCTIONS FOR ALL LIGHTING FIXTURES, RECEPTACLES, DEVICES AND EQUIPMENT, THE CONTRACTOR SHALL FURNISH AND INSTALL ALL HARDWARE, PARTS, AND ACCESSORIES REQUIRED FOR THEIR PROPER INSTALLATION AND OPERATION (INCLUDING ALL PARTS, ACCESSORIES, AND SAFETY DEVICES REQUIRED BY CODE).

34. THE CONTRACTOR SHALL REFER TO ALL DRAWINGS, DETAILS, AND SPECIFICATIONS RELATED TO THIS PROJECT FOR ADDITIONAL REQUIREMENTS.

35. THE CONTRACTOR SHALL INSTALL ALL WIRING AND CONDUIT CONCEALED IN PARTITIONS AND ABOVE THE CEILING, UNLESS OTHERWISE INDICATED.

36. THE CONTRACTOR SHALL COORDINATE ALL ELECTRICAL WORK WITH ALL FIELD CONDITIONS AT THE JOB—SITE AND ALL OTHER TRADES INVOLVED.

37. ALL WIRING, CONDUIT, AND JUNCTION BOXES SHALL BE COLOR CODED, IDENTIFIED, AND LABELED. ALL WORK AND INSTALLATION SHOWN ON THESE DRAWINGS SHALL BE DONE BY A LICENSED CONTRACTOR WITH EXPERIENCE IN THE TYPE OF WORK REQUIRED FOR THIS PROJECT.

38. THE CONTRACTOR SHALL COORDINATE THE MANUFACTURER MODEL. COLOR AND FINISH FOR ALL NEW

38. THE CONTRACTOR SHALL COORDINATE THE MANUFACTURER, MODEL, COLOR AND FINISH FOR ALL NEW RECEPTACLES, OUTLETS AND COVERPLATES WITH THE ARCHITECT (UNLESS A SPECIFIC COLOR CODING IS REQUIRED BY CODE).

39. THE CONTRACTOR SHALL IDENTIFY AND LABEL ALL CIRCUITS.

40. COORDINATE THE LOCATION AND INSTALLATION OF EXIT SIGN LIGHTING FIXTURES AT THE JOB-SITE AS REQUIRED TO INDICATE THE EXIT PATH AS REQUIRED BY CODE AND TO ASSURE PROPER VISIBILITY.

41. PROVIDE CAST METAL JUNCTION BOXES AND CONDUIT FOR CIRCUITS BEING INSTALLED IN EXPOSED VISIBLE LOCATIONS.

42. PROVIDE CAST METAL JUNCTION BOXES AND CONDUIT WITH PULL STRING FOR TELEPHONE AND DATA CIRCUITS BEING INSTALLED IN EXPOSED VISIBLE AREAS.

43. ELECTRICAL

A. INSTALL ALL ROUGH ELECTRIC

ELECTRICAL TO ENSURE CORRECT PLACEMENT AND TYPE OF SERVICE FOR EACH
PIECE OF EQUIPMENT.

CONCEAL ALL WIRING AND CONDUIT IN WALLS, CHASES, UTILITY SPACES OR ABOVE CEILINGS.

C. LABEL ALL BREAKER LOCATIONS ON SERVICE PANEL.

D. INSTALL PLUG CLAMPS ON 30 AMP AND LARGER RECEPTACLES TO RELIEVE TENSION IF NEUTRAL IS ON TOP.

SWITCHED, RECEPTACLES AND COVER PLATES

 ALL TOGGLE SWITCHES AND RECEPTACLES SHALL BE FLUSH WITH THE WALL FINISH.
 INTERIOR FLUSH BOXES SHALL BE CODE GRADE STEEL, SECURELY FASTENED WITH APPROVED DEVICES TO STUDS OR MASONRY.

3. TOGGLE SWITCHES, INDOOR OUTLETS AND SWITCH PLATES SHALL BE WHITE IN COLOR.

F. LIGHTING:

FURNISH AND INSTALL ALL LIGHTING FIXTURES AS SPECIFIED ON ARCHITECTURAL DRAWINGS.

 LIGHTING FIXTURES, INCLUDING LAMPS SHALL BE AS SPECIFIED. NO SUBSTITUTIONS WILL BE

3. PROVIDE AND INSTALL ALL LIGHTING FIXTURES AND LAMPS IN ACCORDANCE WITH THE FIXTURE SCHEDULE SHOWN ON THE DRAWINGS, COMPLETE WITH NECESSARY COMPONENTS, MOUNTING AND HANGING DEVICES REQUIRED TO INSTALL THE PARTICULAR FIXTURE IN ITS DESIGNATED LOCATION, COMPLETELY WIRED AND READY FOR OPERATION.

PERMITTED,
PROVIDE AND INSTALL THE EMERGENCY LIGHTING AND REMOTE HEADS AS
SHOWN. SEE DRAWINGS FOR LOCATION AND TYPE.

UNLESS APPROVED BY ARCHITECT/ENGINEER.

ELECTRICAL ABBREVIATIONS EXISTING TO REMAIN EXISTING TO BE RELOCATED RELOCATION POINT AMPERE ALTERNATING CURRENT AMP FRAME ABOVE FINISHED FLOOR ABOVE FINISHED GRADE AMP TRIP AMERICAN WIRE GAUGE BKR BREAKER BUILDING C, COND CONDUIT CIRCUIT BREAKER CB CKT CIRCUIT CEILING DIA DIAMETER DISC DISCONNECT DOWN DRAWING **EMPTY CONDUIT** ENCLOSED CIRCUIT BREAKER EQUIPMENT GROUND ELECTRICAL **EMERGENCY EMERG** EQUIPMENT ENERGY SAVING BALLAST ETR EXISTING TO REMAIN **EXISTNG** ELECTRIC WATER COOLER EWC F/A, FA FIRE ALARM FIRE ALARM ANNUCIATOR PANEL FACP FIRE ALARM CONTROL PANEL FULL LOAD AMPS FLA F/N FULL NEUTRAL FUSED SAFETY SWITCH GROUND FAULT INTERRUPTER HORSEPOWER HPF HIGH POWER FACTOR ISOLATOR GROUND INCAND INCANDESCENT JUNCTION BOX KAIC THOUSANDS OF AMPS INTERRUPTING CAPACITY KCMIL, MCM THOUSANDS CIRCULAR MILS KILOVOLT KILOVOLT AMPS KILOWATT LIGHTING MAXIMUM MAIN CIRCUIT BREAKER MOTOR CONTROL CENTER MECH MECHANICAL MINIMUM MIN MAIN LUGS ONLY MOCP MAXIMUM OVERCURRENT PROTECTION NOT APPLICABLE NEUTRAL NORMALLY CLOSED NATIONAL ELECTRICAL CODE NEC NEMA NATIONAL ELECTRICAL MANUFACTURER'S ASSOCIATION NOT IN CONTRACT NIGHT LIGHT NON-FUSABLE NON-FUSED SAFETY SWITCH NORMALLY OPEN NTS NOT TO SCALE PHASE POLE PANELBOARD PRIMARY **QUANTITY** 

REC, RECEPT

REQ'D

SCHED

SW

UON

RECEPTACLE

REQUIRED ROOM

SCHEDULE

SWITCH

TYPICAL UNFUSED

T, XFMR, T/F TRANSFORMER

REMOVE EXISTING

SMOKE DETECTOR

UNLESS OTHERWISE NOTED

SINGLE POLE

TELEPHONE

VOLT, VOLTAGE VOLT AMP

WATT, WIRE WEATHERPROOF

WITH NUMBER

ARCHITECT/ENGINEER OF RECORD APPROVED FOR BID: DATE REBUILD PROJECT MANAGER **CONVERSE WINKLER ∠** ∴ ARCHITECTURE MARK ULRICK ENGINEERS, INC. **DESCRIPTION** DATE REVISION **DISSTON REC CENTER UPGRADES** 

**APPROVED:** 

Sheet Title:

ELECTRICAL LEGEND & GENERAL NOTES

Submission: 100% SUBMISSION

Consultant:

CONVERSE WINKLER ARCHITECTURE

Task No.:


Drawn By:


Work No.: REBUILD-CW-1909.01

08/12/2022

: of


E-0.01






BID SET - 09-09-2022

ARCHITECT/ENGINEER OF RECORD DATE




#### **DEMOLITION DRAWING NOTES:**

- 1 CONTRACTOR SHALL REMOVE EXISTING LIGHT FIXTURE AND RETAIN WIRING TO BE REUSED IN NEW WORK.
- 2 CONTRACTOR SHALL REMOVE EXISTING LIGHT SWITCH AND RETAIN WIRING TO BE REUSED IN NEW WORK..



SECOND FLOOR PLAN-LIGHTING-NEW WORK SCALE: 1/8"=1'-0"

- 3 CONTRACTOR SHALL REMOVE EXISTING SMOKE DETECTOR AND RETAIN WIRING FOR REUSE IN NEW WORK.




#### **GENERAL NOTE:**

1. REFER ARCHITECTURAL DRAWING A-602 FOR LIGHT FIXTURE SCHEDULE.

#### **NEW WORK DRAWING NOTES:**

- 1) CONTRACTOR SHALL CONNECT NEW LIGHTING TO AN EXISTING LIGHTING CIRCUIT FROM DEMOLITION.
- 2 CONTRACTOR SHALL PROVIDE A NEW LIGHT SWITCH IN WHERE THE EXISTING SWITCH WAS REMOVED IN DEMOLITION.
- 3 CONTRACTOR SHALL CONNECT OCCUPANCY SENSORS TOGETHER IN AREA WHERE MORE THAN ONE IS INSTALLED.
- 4 CONTRACTOR SHALL PROVIDE A NEW LED LIGHT FIXTURE AS SPECIFIED AND CONNECT TO EXISTING LIGHTING CIRCUIT AS INDICATED.
- 5 CONTRACTOR SHALL PROVIDE A NEW EXTERIOR LED LIGHT FIXTURE AS SPECIFIED AND CONNECT TO EXISTING WIRING FROM DEMOLITION..
- 6 CONTRACTOR SHALL CONNECT NEW EMERGENCY LIGHT TO LIGHTING CIRCUIT IN AREA AHEAD OF LOCAL SWITCHING.

APPROVED: ARCHITECT/ENGINEER OF RECORD APPROVED FOR BID: REBUILD PROJECT MANAGER DATE Designer: **CONVERSE** WINKLER **ARCHITECTURE** MARK ULRICK ENGINEERS, INC.



DESCRIPTION DATE

DISSTON REC CENTER **UPGRADES** 

SHeet Title: SECOND FLOOR PLAN **LIGHTING - DEMOLITION** AND NEW WORK

**100% SUBMISSION** 

Engineering Manager: RAVI JETHANI CONVERSE WINKLER ARCHITECTURE

ote: 08/12/2022

**REBUILD-**CW-1909.01


SECOND FLOOR PLAN-LIGHTING-DEMOLITION NORTH SCALE: 1/8"=1'-0"

STORAGE

MULTI-PURPOSE

ACTIVITY

201



APPROVED: ARCHITECT/ENGINEER OF RECORD DATE APPROVED FOR BID: REBUILD PROJECT MANAGER DATE CONVERSE WINKLER . : ARCHITECTURE MARK ULRICK ENGINEERS, INC. REVISION DESCRIPTION **DISSTON REC CENTER UPGRADES** SECOND FLOOR PLAN POWER - NEW WORK 100% SUBMISSION Engineering Manager: RAVI JETHANI CONVERSE WINKLER ARCHITECTURE e: 08/12/2022

**REBUILD-**CW-1909.01

63

