




DEMOLITION LEGEND

- EXISTING MASONRY WALL
- EXISTING MASONRY WALL TO BE REMOVED TO UNDERSIDE OF STRUCTURE ABOVE UNLESS OTHERWISE NOTED
- REMOVE EXISTING DOOR, FRAME AND HARDWARE UNLESS OTHERWISE NOTED
- EXISTING DOOR, FRAME AND HARDWARE TO REMAIN
- EXISTING WINDOW
- EXISTING WINDOW, FRAME AND HARDWARE TO BE REMOVED

ADDITIONAL INTERIOR DEMOLITION WORK NOTES

1. ALL EXISTING MECHANICAL BASEBOARD HEATERS TO BE REMOVED. ALL EXISTING WINDOW AIR CONDITIONERS TO BE REMOVED AND SALVAGED. RETURN TOWER, REFER TO MECHANICAL DRAWINGS.
2. INVESTIGATE ALL CEILINGS FOR LOCATIONS OF WATER INTRUSION DURING DEMOLITION. REMOVE WATER DAMAGED MATERIALS AND PREPARE FOR REPAIR OF ASSOCIATED ROOF.
3. ALL EXISTING LIGHT FIXTURES IN AREAS WITH SCHEDULED REPLACEMENT TO BE SALVAGED AND RETURNED TO OWNER. REFER TO ELECTRICAL DRAWINGS.



GENERAL DEMOLITION NOTES

1. SUBCONTRACTORS MUST REVIEW ALL DRAWINGS OF NEW & EXISTING WORK COORDINATE DEMOLITION SCOPE PRIOR TO SUBMITTING BIDS. SEE DRAWINGS FOR MORE INFORMATION.
2. THIS IS A SELECTIVE RENOVATION. ALL FINISHES, FLOORING, CEILINGS, LIGHTS, INTERIOR PARTITIONS, ELECTRICAL DEVICES, PLUMBING FIXTURES, ETC. ARE TO BE REMOVED TO STRUCTURE AS INDICATED ON PLANS UNLESS NOTED OTHERWISE. SEE STRUCTURAL DRAWINGS. COORDINATE ALL DEMOLITION WITH DRAWINGS OF NEW CONSTRUCTION TO IDENTIFY SCOPE OF REMOVAL. REMOVE ALL FLOORING ADHESIVES AND CLEAN SLAB AS REQUIRED TO INSTALL NEW FINISH FLOOR.
3. ENGAGE EXPERIENCED PERSONNEL THAT HAS SPECIALIZED IN DEMOLITION WORK SIMILAR IN MATERIAL AND EXTENT TO THAT INDICATED FOR THIS PROJECT. COMPLY WITH GOVERNING EPA NOTIFICATION REGULATIONS BEFORE BEGINNING SELECTIVE DEMOLITION. COMPLY WITH HAULING AND DISPOSAL REGULATIONS OF AUTHORITIES HAVING JURISDICTION.
4. CONTRACTOR IS TO SURVEY EXISTING CONDITIONS AND CORRELATE WITH REQUIREMENTS INDICATED TO DETERMINE EXTENT OF SELECTIVE DEMOLITION. PRIOR TO SUBMITTING BIDS, NOTIFY ARCHITECT OF DISCREPANCIES BETWEEN EXISTING CONDITIONS AND DRAWINGS BEFORE PROCEEDING WITH SELECTIVE DEMOLITION. WHEN UNANTICIPATED MECHANICAL, ELECTRICAL, OR STRUCTURAL ELEMENTS THAT CONFLICT WITH INTENDED FUNCTION OR DESIGN ARE ENCOUNTERED, INVESTIGATE AND MEASURE THE NATURE AND EXTENT OF CONFLICT. PROMPTLY SUBMIT A WRITTEN REPORT TO ARCHITECT. AREAS OF MATERIALS DIRECTED AS BEING REMOVED ARE APPROXIMATE. CONTRACTOR IS RESPONSIBLE TO CONFIRM EXTENT BY COORDINATION WITH DRAWINGS FOR NEW CONSTRUCTION AND BY VISITING SITE PRIOR TO SUBMITTING A BID.
5. IF MATERIALS SUSPECTED OF CONTAINING HAZARDOUS MATERIALS ARE ENCOUNTERED, DO NOT DISTURB. IMMEDIATELY NOTIFY OWNER. OWNER WILL REMOVE HAZARDOUS MATERIALS UNDER A SEPARATE CONTRACT.
6. STORAGE OR SALE OF REMOVED ITEMS OR MATERIALS ON-SITE IS NOT PERMITTED.
7. MAINTAIN EXISTING UTILITIES AND PROTECT THEM AGAINST DAMAGE DURING SELECTIVE DEMOLITION OPERATIONS. VERIFY THAT UTILITIES HAVE BEEN DISCONNECTED AND CAPPED. MAINTAIN FIRE-PROTECTION FACILITIES IN SERVICE DURING SELECTIVE DEMOLITION OPERATIONS.
8. REMOVE, REPLACE, PATCH, AND REPAIR MATERIALS AND SURFACES CUT OR DAMAGED DURING SELECTIVE DEMOLITION, BY METHODS AND WITH MATERIALS SO AS NOT TO VOID EXISTING WARRANTIES.
9. PERFORM SURVEYS AS THE WORK PROGRESSES TO DETECT HAZARDS RESULTING FROM SELECTIVE DEMOLITION ACTIVITIES.
10. CONDUCT DEBRIS-REMOVAL OPERATIONS TO ENSURE MINIMUM INTERFERENCE WITH DRIVEWAYS, STREETS, WALKWAYS, AND OTHER ADJACENT OCCUPIED AND USED FACILITIES.
11. PROVIDE TEMPORARY BARRICADES AND OTHER PROTECTION REQUIRED TO PREVENT INJURY TO PEOPLE AND DAMAGE TO ADJACENT BUILDINGS AND FACILITIES TO REMAIN. PROVIDE AND MAINTAIN SHORING, BRACING, AND STRUCTURAL SUPPORTS AS REQUIRED TO PRESERVE STABILITY AND PREVENT MOVEMENT, SETTLEMENT, OR COLLAPSE OF CONSTRUCTION AND FINISHES TO REMAIN, AND TO PREVENT UNEXPECTED OR UNCONTROLLED MOVEMENT OR COLLAPSE OF CONSTRUCTION BEING DEMOLISHED.
12. DEMOLISH AND REMOVE EXISTING CONSTRUCTION ONLY TO THE EXTENT REQUIRED BY NEW CONSTRUCTION AND AS INDICATED. DO NOT DEMOLISH BUILDING ELEMENTS BEYOND WHAT IS INDICATED ON DRAWINGS WITHOUT ARCHITECT'S APPROVAL. REFER TO FLOOR PLANS AND REFLECTED CEILING PLANS TO COORDINATE PRECISE LIMITS OF DEMOLITION WORK.
13. NEATLY CUT OPENINGS AND HOLES PLUMB, SQUARE, AND TRUE TO DIMENSIONS REQUIRED. USE CUTTING METHODS LEAST LIKELY TO DAMAGE CONSTRUCTION TO REMAIN OR ADJOINING CONSTRUCTION. USE HAND TOOLS OR SMALL POWER TOOLS DESIGNED FOR SAWING OR GRINDING, NOT HAMMERS AND CHOPPING, TO MINIMIZE DISTURBANCE OF ADJACENT SURFACES. TEMPORARILY COVER OPENINGS TO REMAIN, CUT OR DRILL FROM THE EXPOSED OR FINISHED SIDE INTO CONCEALED SURFACES TO AVOID MARRING EXISTING FINISHED SURFACES. DO NOT USE CUTTING TORCHES UNTIL WORK AREA IS CLEARED OF FLAMMABLE MATERIALS. AT CONCEALED SPACES, SUCH AS DUCT AND PIPE INTERIORS, VERIFY CONDITION AND CONTENTS OF HIDDEN SPACE BEFORE STARTING FLAME-CUTTING OPERATIONS. MAINTAIN PORTABLE FIRE-SUPPRESSION DEVICES DURING FLAME-CUTTING OPERATIONS. LOCATE SELECTIVE DEMOLITION EQUIPMENT AND REMOVE DEBRIS AND MATERIALS SO AS NOT TO IMPOSE EXCESSIVE LOADS ON SUPPORTING WALLS, FLOORS, OR FRAMING. DISPOSE OF DEMOLISHED ITEMS AND MATERIALS PROMPTLY.
14. EXCEPT FOR ITEMS OR MATERIALS INDICATED TO BE RECYCLED, REUSED, SALVAGED, REINSTALLED, OR OTHERWISE INDICATED TO REMAIN OWNER'S PROPERTY, REMOVE DEMOLISHED MATERIALS FROM PROJECT SITE AND LEGALLY DISPOSE OF THEM IN AN EPA-APPROVED LANDFILL. TRANSPORT DEMOLISHED MATERIALS OFF OWNER'S PROPERTY AND LEGALLY DISPOSE OF THEM. DO NOT BURN DEMOLISHED MATERIALS. EXISTING LIGHT FIXTURES SHOULD BE MARKED AS SALVAGE AND RETURNED TO OWNER.
15. CLEAN ADJACENT STRUCTURES AND IMPROVEMENTS OF DUST, DIRT, AND DEBRIS CAUSED BY SELECTIVE DEMOLITION OPERATIONS. RETURN ADJACENT AREAS TO CONDITION EXISTING BEFORE SELECTIVE DEMOLITION OPERATIONS BEGAN.
16. FILL IN EXISTING PIPE, DUCT, CONDUIT HOLES, OR ANY OTHER FLOOR/WALL PENETRATIONS RESULTING FROM DEMOLITION WITH A UL APPROVED FIRE AND SMOKE RATED INTUMESCENT MATERIAL TO MAINTAIN THE EXISTING FIRE RATED ASSEMBLY. IN ALL CASES FILL WITH MIN. 1HR RATING IF REQUIRED. IDENTIFY ALL CONDITIONS THAT REQUIRE FIRE STOPPING. FURNISH A PLAN WITH CONDITIONS KEYED AND PROVIDE MANUFACTURER'S PRODUCT DATA FOR MATERIALS USED AT EACH LOCATION.
17. WHERE EXISTING CONCRETE SLAB IS DISTURBED BY THE REMOVAL OF EXISTING PARTITIONS AND WALLS OR ANY OTHER SELECTIVE DEMOLITION, PATCH AND REPAIR EXISTING SURFACES WITH LEVELING COMPOUND, TO PRODUCE A SMOOTH, LEVEL SURFACE TO RECEIVE NEW FINISHES. WHERE FLOORING IS BEING REMOVED, REMOVE EXISTING FLOORING MATERIALS DOWN TO EXISTING DECK/SLAB TO A CONDITION READY TO INSTALL NEW FINISHES. PATCH AND REPAIR ALL EXISTING SLAB SURFACES WITH LEVELING COMPOUND TO PRODUCE A SMOOTH, LEVEL SURFACE.
18. WALL MATERIALS ARE SUPPOSED. CONTRACTOR TO VERIFY MATERIALS BEING REMOVED PRIOR TO SUBMITTING BID.

DEFINITIONS

REMOVE: DETACH ITEMS FROM EXISTING CONSTRUCTION AND LEGALLY DISPOSE OF THEM OFF-SITE, UNLESS INDICATED TO BE REMOVED AND SALVAGED OR REMOVED AND REINSTALLED.

REMOVE AND SALVAGE: DETACH ITEMS FROM EXISTING CONSTRUCTION AND DELIVER THEM TO OWNER, READY FOR REUSE, PACK OR CRATE ITEMS AFTER CLEANING. IDENTIFY CONTENTS OF CONTAINERS. STORE ITEMS IN A SECURE AREA UNTIL DELIVERY TO OWNER. TRANSPORT ITEMS TO OWNER'S STORAGE AREA DESIGNATED BY OWNER. PROTECT ITEMS FROM DAMAGE DURING TRANSPORT AND STORAGE. INVENTORY AND RECORD THE CONDITION OF ITEMS TO BE REMOVED AND SALVAGED.

REMOVE AND REINSTALL: DETACH ITEMS FROM EXISTING CONSTRUCTION. PREPARE THEM FOR REUSE, AND REINSTALL THEM WHERE INDICATED. CLEAN AND REPAIR ITEMS TO FUNCTIONAL CONDITION ADEQUATE FOR INTENDED REUSE. REINSTALL ITEMS IN LOCATIONS INDICATED. COMPLY WITH INSTALLATION REQUIREMENTS FOR NEW MATERIALS AND EQUIPMENT. PROVIDE CONNECTIONS, SUPPORTS, AND MISCELLANEOUS MATERIALS NECESSARY TO MAKE ITEM FUNCTIONAL FOR USE INDICATED. INVENTORY AND RECORD THE CONDITION OF ITEMS TO BE REMOVED AND REINSTALLED.

EXISTING TO REMAIN: EXISTING ITEMS OF CONSTRUCTION THAT ARE NOT INDICATED TO BE REMOVED, REMOVED AND SALVAGED, OR REMOVED AND REINSTALLED. PROTECT CONSTRUCTION INDICATED TO REMAIN AGAINST DAMAGE AND SOILING DURING SELECTIVE DEMOLITION. WHEN PERMITTED BY ARCHITECT, ITEMS MAY BE REMOVED TO A SUITABLE PROTECTED STORAGE LOCATION DURING SELECTIVE DEMOLITION, CLEANED, AND REINSTALLED IN THEIR ORIGINAL LOCATIONS AFTER SELECTIVE DEMOLITION OPERATIONS ARE COMPLETE.



PROJECT NAME & ADDRESS:
ZIEHLER PLAYGROUND & RECREATION CENTER

200-64 E. OLNEY AVENUE
PHILADELPHIA, PA 19120

PROJECT NUMBER:
16640E-01-02



161 LEVERING AVE, SUITE 1005
PHILADELPHIA, PA 19127
www.saltdesignstudio.com

CIVIL ENGINEERING:
MELORA DESIGN
259 MORGAN STREET
PHOENIXVILLE, PA 19460
www.meloraengine.com

ARCHITECTURE:
IAN SMITH DESIGN GROUP
322 E. THOMPSON STREET
PHILADELPHIA, PA 19125
www.is-dg.com

LIGHTING DESIGN:
MILLER DESIGN GROUP
www.millerdesigngroup.com

MEP DESIGN:
MARK ULRIK ENGINEERS, INC.
622 COOPER STREET, #200
CAMDEN, NJ 08102
www.markulrik.com

STRUCTURAL ENGINEERING:
D'HUY ENGINEERING, INC.
1 EAST BROAD STREET, SUITE 310
BETHLEHEM, PA 18018
www.dhuy.com

DRAWING PHASE:
ISSUE FOR BIDDING



SHEET TITLE:
EXISTING BUILDING PROPOSED DEMOLITION FLOOR PLAN

REV	DATE	DESCRIPTION

SCALE:
AS NOTED

DATE: 08/15/2022 DRAWN BY:
CHECKED BY:

SHEET NUMBER:
AD1.00

SALT DESIGN STUDIO FILE NO:
2003


CONSTRUCTION DOCUMENTS

DEMOLITION FLOOR PLAN
SCALE: 1/4" = 1'-0"




MATERIAL LEGEND

- EXISTING BRICK MASONRY
- EXISTING CMU MASONRY



1 PROPOSED DEMOLITION
EAST ELEVATION
SCALE: 1/4" = 1'-0"



2 PROPOSED DEMOLITION
SOUTH ELEVATION
SCALE: 1/4" = 1'-0"



SHEET TITLE:
EXISTING BUILDING PROPOSED DEMOLITION BLDG ELEVS

REV	DATE	DESCRIPTION


SCALE:
AS NOTED

DATE: 08/15/2022 DRAWN BY:
CHECKED BY:

SHEET NUMBER:


AD2.00

CONSTRUCTION DOCUMENTS




MATERIAL LEGEND

- EXISTING BRICK MASONRY
- EXISTING CMU MASONRY



1 PROPOSED DEMOLITION
WEST ELEVATION
SCALE: 1/4" = 1'-0"



2 PROPOSED DEMOLITION
NORTH ELEVATION
SCALE: 1/4" = 1'-0"



SHEET TITLE:
EXISTING BUILDING PROPOSED DEMOLITION BLDG ELEVS

REV	DATE	DESCRIPTION

SCALE:
AS NOTED


DATE: 08/15/2022 DRAWN BY:
CHECKED BY:

SHEET NUMBER:

AD2.01


CONSTRUCTION DOCUMENTS

P1 NON-RATED NON-BEARING EXTERIOR INFILL




1. CONCRETE BLOCKS* - VARIOUS DESIGNS. SEE CONCRETE BLOCKS CATEGORY FOR LIST OF ELIGIBLE MANUFACTURERS.
2. MORTAR - BLOCKS LAID IN FULL BED OF MORTAR, NOM. 3/8" THICK, OF NOT LESS THAN 2-1/4 AND NOT MORE THAN 3-1/2 PARTS OF CLEAN SHARP SAND TO 1 PART PORTLAND CEMENT (PROPORTION BY VOLUME) AND NOT MORE THAN 50 PERCENT HYDRATED LIME (BY CEMENT VOLUME). VERTICAL JOINTS STAGGERED.
3. LOOSE MASONRY FILL - IF ALL CORE SPACES ARE FILLED WITH LOOSE DRY EXPANDED SLAG, EXPANDED CLAY OR SHALE (ROTARY KILN PROCESS), WATER REPELLANT VERMICULITE MASONRY FILL INSULATION, OR SILICONE TREATED PERLITE LOOSE FILL INSULATION ADD 2HR TO CLASSIFICATION.
4. FULLY GROUTED, REINFORCED WITH VERTICAL #4 @ 16 O.C. HORIZONTAL GAGE 9 JOINT REINFORCED @ 16" (TYP).
5. FINISH - PAINT BOTH SIDES. PROVIDE WATERPROOFING SEALER ON EXTERIOR FACE.

P2 NON-RATED NON-BEARING INTERIOR WALL




1. CONCRETE BLOCKS* - VARIOUS DESIGNS. SEE CONCRETE BLOCKS CATEGORY FOR LIST OF ELIGIBLE MANUFACTURERS.
2. MORTAR - BLOCKS LAID IN FULL BED OF MORTAR, NOM. 3/8" THICK, OF NOT LESS THAN 2-1/4 AND NOT MORE THAN 3-1/2 PARTS OF CLEAN SHARP SAND TO 1 PART PORTLAND CEMENT (PROPORTION BY VOLUME) AND NOT MORE THAN 50 PERCENT HYDRATED LIME (BY CEMENT VOLUME). VERTICAL JOINTS STAGGERED.
3. LOOSE MASONRY FILL - IF ALL CORE SPACES ARE FILLED WITH LOOSE DRY EXPANDED SLAG, EXPANDED CLAY OR SHALE (ROTARY KILN PROCESS), WATER REPELLANT VERMICULITE MASONRY FILL INSULATION, OR SILICONE TREATED PERLITE LOOSE FILL INSULATION ADD 2HR TO CLASSIFICATION.
4. FULLY GROUTED, REINFORCED WITH VERTICAL #4 @ 16 O.C. HORIZONTAL GAGE 9 JOINT REINFORCED @ 16" (TYP).
5. FINISH - PAINT BOTH SIDES (EXCLUDING WALLS FACING STORAGE AREAS)


P3 NON-RATED NON-BEARING EXTERIOR INFILL



1. WOOD STUDS - 2" X 6" WOOD STUDS AT 16" WITH DOUBLE TOP PLATES, SINGLE BOTTOM PLATE.
2. GYPSUM BOARD - INTERIOR SIDE COVERED WITH 5/8" IMPACT RESISTANT GYPSUM WALLBOARD, 4' WIDE, APPLIED VERTICALLY WITH ALL JOINTS OVER FRAMING OR BLOCKING AND FASTENED WITH 2 1/4" TYPE S DRYWALL SCREWS, SPACED 12" ON CENTER.
3. BATTS AND BLANKETS* - R-21 MINERAL FIBER INSULATION INSTALLED IN STUD CAVITY.
4. SHEATHING - EXTERIOR SIDE TO BE 5/8" EXTERIOR GRADE APPLICATION WATER RESISTANT GYPSUM CORE, 4' WIDE, APPLIED VERTICALLY WITH ALL JOINTS OVER FRAMING OR BLOCKING AND FASTENED WITH 2 1/4" TYPE S DRYWALL SCREWS, SPACED 12" ON CENTER.
5. VAPOR RETARDER, WATER BARRIER OR WEATHER RESISTIVE BARRIER.
6. FINISH - PAINT INTERIOR GYPSUM FACE. PROVIDE IMPACT RESISTANT METAL PANEL SYSTEM ON EXTERIOR FACE.
7. JOINT TAPE AND COMPOUND - JOINTS TO BE COVERED WITH TAPE AND JOINT COMPOUND. LEVEL 4 FINISH.



P4 NON-RATED FURRING PARTITION ONE-SIDED



1. FLOOR WOOD STUD PLATES AND CEILING DOUBLE PLATES - ATTACHED TO FLOOR AND CEILING WITH FASTENERS 24 IN. OC MAX.
2. WOOD STUDS - 2"x4", MIN. SPACING 16" O.C.
3. GYPSUM BOARD - 1 LAYER, 1/2 IN. THICK GYPSUM PANELS WITH BEVELED, SQUARE OR TAPERED EDGES, APPLIED VERTICALLY OR HORIZONTALLY. VERTICAL JOINTS CENTERED OVER STUDS AND STAGGERED ONE STUD CAVITY ON OPPOSITE SIDES OF STUDS. HORIZONTAL JOINTS NEED NOT BE BACKED BY STEEL FRAMING. HORIZONTAL EDGE JOINTS AND HORIZONTAL BUTT JOINTS ON OPPOSITE SIDES OF STUDS NEED NOT BE STAGGERED. EXTEND STUDS AND GWB ON BOTH SIDES TO STRUCTURE. SCRIBE GWB TO STRUCTURE AND FIRE CAULK, AS REQUIRED FOR DETERMINED FIRE RATING.
4. FASTENERS - (NOT SHOWN) - 1 IN. LONG TYPE S OR S-12 STEEL SCREWS USED TO ATTACH PANELS TO STUDS (ITEM 2), SPACED 8 IN. OC WHEN PANELS ARE APPLIED HORIZONTALLY, OR 8 IN. OC ALONG VERTICAL AND BOTTOM EDGES AND 12 IN. OC IN THE FIELD WHEN PANELS ARE APPLIED VERTICALLY.
5. JOINT TAPE AND COMPOUND - VINYL OR CASEIN, DRY OR PREMIXED JOINT COMPOUND APPLIED IN TWO COATS TO JOINTS AND SCREW HEADS OF OUTER LAYERS. PAPER TAPES, NOM 2 IN. WIDE, EMBEDDED IN FIRST LAYER OF COMPOUND OVER ALL JOINTS OF OUTER LAYER PANELS. PAPER TAPE AND JOINT COMPOUND MAY BE OMITTED WHEN GYPSUM PANELS ARE SUPPLIED WITH A SQUARE EDGE.
6. SCHEDULED CEILING




SHEET TITLE:
PARTITION
TYPES

REV	DATE	DESCRIPTION

SCALE:
AS NOTED

DATE: 08/15/2022	DRAWN BY:
SHEET NUMBER:	CHECKED BY:

A0.01



CONSTRUCTION TYPE	ALLOWED	EXISTING	PROPOSED	BUILDING ELEMENT	TYPE 5A REQ. RATING ⁴
OCCUPANCY CLASSIFICATION		A3 - COMM. HALL	A3 - COMM. HALL	PRIMARY STRUCTURAL FRAME ¹ (see Section 202)	0
BUILDING HEIGHT	40 FEET	15.5 FEET	15.5 FEET	BEARING WALLS EXTERIOR ^{6,7}	0
BUILDING NO. STORIES	1 STORIES	1 STORIES	1 STORIES	INTERIOR	0
GROSS FLOOR AREA	6,000 SF	3,600 SF	3,600 SF	NONBEARING WALLS AND PARTITIONS EXTERIOR	SEE TABLE 602
				NONBEARING WALLS AND PARTITIONS INTERIOR ⁴	0
				FLOOR CONSTRUCTION AND SECONDARY MEMBERS (see Section 202)	0
				ROOF CONSTRUCTION AND SECONDARY MEMBERS (see Section 202)	0

USE	CONST. TYPE	ALLOW. STD.	ALLOWED AREA (sq ft)	EXISTING AREA	OCCUPANCY RATIO	CODE ESTABLISHED OCC.	SEE NOTE	PROP. REDUCED
GROUND FLOOR (A-3)	A-3	5B	1	6,000 GSF				
GYM				750 GSF	50 GR	15 OCC.		
MULTI-PURPOSE ROOM				850 GSF	15 NET	57 OCC.		
ACTIVITY ROOM				370 GSF	15 NET	25 OCC.		
OFFICE				130 GSF	150 GR	1 OCC.		
ACCESSORY AREAS				1,500 GSF	300 GR	5 OCC.		

	REQUIRED (5B)
CORRIDOR FIRE RESISTANCE RATING (TABLE 1020.1)	USE A-3; OCCUPANT LOAD GREATER THAN 30 OCCUPANTS / WITHOUT SPRINKLER SYSTEM = 1 HR
CORRIDOR MINIMUM WIDTH	44" (TABLE 1020.2)
COMMON PATH OF EGRESS TRAVEL	A-3; 7'5" WITHOUT SPRINKLER SYSTEM (TABLE 1006.2.1)
DEADEND	A-3; 20' WITHOUT SPRINKLER SYSTEM (1020.4 EX.2)
EXIT ACCESS TRAVEL DISTANCE (TABLE 1017.2)	A-3; 200' WITHOUT SPRINKLER SYSTEM
EXIT REMOTENESS	1/2 DIAGONAL, 1007.1.1
NUMBER OF EXITS	TABLE 1006.3.2 - 1-500 OCC. (2) EXITS MINIMUM
EGRESS CAPACITY	0.3 PER INCH OF STAIR = 36" STAIR/0.3" = 120 MAX. (SECTION 1009.1.1) 0.2 PER INCH OF DOOR AND OTHER COMPONENTS 34" DOOR OPENING/0.2" = 170 MAX. 34" DOOR OPENING = 34" CLEAR OPENING BETWEEN DOOR AND JAMB (SECTION 1005)
ACCESSIBLE MEANS OF EGRESS	PROVIDED
DOOR SWING	A-3; SWING IN THE DIRECTION OF EGRESS TRAVEL PER (SECTION 1010.1.2)

PROJECT NARRATIVE


PROPOSED EXISTING (1) STORY COMMUNITY HALL PARK BUILDING TO BE RENOVATED. RENOVATIONS TO INCLUDE ACCESSIBILITY UPGRADES, TOILET ROOM IMPROVEMENTS AND CODE COMPLIANCE UPGRADES. NO CHANGES TO EXISTING USES.

BUILDING DATA

THIS BUILDING IS NOT PROPOSED TO BE EQUIPPED THROUGHOUT WITH AN APPROVED AUTOMATIC SPRINKLER SYSTEM IN ACCORDANCE WITH 903.3.1.1 NFPA 13 SPRINKLER SYSTEMS. (AASS) SPRINKLER DESIGN - BUILDING IS NOT REQUIRED TO BE EQUIPPED WITH CLASS I STANDPIPES IN THE EXIT STAIRWAYS PER SECTION 905.3 OF THE 2018 IBC.

PHILADELPHIA ZONING DISTRICT	SP-PO-A RECREATION
PHILADELPHIA APPLICABLE CODE	
PHILADELPHIA ADMINISTRATIVE CODE	
PHILADELPHIA BUILDING CODE	2018 INTERNATIONAL BUILDING CODE (IBC 2018) ACCESSIBILITY - (IBC 2018 - CH. 11 ACCESSIBILITY REFERENCE STANDARD - (ICC ANSI A117.1-2009)
PHILADELPHIA EXISTING BUILDING CODE	2018 INTERNATIONAL EXISTING BUILDING CODE (IEBC 2018) ACCESSIBILITY - (IEBC 2018 - SECTION 305 ACCESSIBILITY REFERENCE STANDARD - (ICC ANSI A117.1-2009)
PHILADELPHIA RESIDENTIAL CODE	2015 INTERNATIONAL RESIDENTIAL CODE (IRC 2015)
PHILADELPHIA MECHANICAL CODE	2018 INTERNATIONAL MECHANICAL CODE (IMC 2018)
PHILADELPHIA ELECTRICAL CODE	2017 NATIONAL ELECTRIC CODE (PER IBC 2018)
PHILADELPHIA PERFORMANCE CODE	2018 INTERNATIONAL PERFORMANCE BUILDING CODE (IPBC 2018)
PHILADELPHIA ENERGY CONSERVATION CODE	2018 INTERNATIONAL ENERGY CONSERVATION CODE (IECC 2018)
PHILADELPHIA FIRE CODE	2009 INTERNATIONAL FIRE CODE (IFC 2018)
PHILADELPHIA FUEL GAS CODE	2018 INTERNATIONAL FUEL GAS CODE (IFGC 2018)
PHILADELPHIA ZONING CODE	PER MOST RECENT AMENDMENT THROUGH PHILA. CITY COUNCIL 2ND EDITION SIXTH PRINTING FEB. 2019 (358.1); JAN. 03. 2019
PHILADELPHIA PLUMBING CODE	
PHILADELPHIA PROPERTY MAINTENANCE CODE	PER MOST RECENT AMENDMENT (358.1); JAN. 03. 2019

EGRESS LEGEND



PROPOSED EGRESS PLAN
SCALE: 1/4" = 1'-0"

CLIENT: **PHILADELPHIA PARKS & RECREATION**

Rebuild PHILADELPHIA

PROJECT NAME & ADDRESS:
ZIEHLER PLAYGROUND & RECREATION CENTER
200-64 E. OLNEY AVENUE
PHILADELPHIA, PA 19120

PROJECT NUMBER:
16640E-01-02

PRIME CONSULTANT (LANDSCAPE ARCHITECTURE):
SALT DESIGN STUDIO
LANDSCAPE ARCHITECTURE
PLANNING & URBAN DESIGN

161 LEVERINGTON AVE, SUITE 1005
PHILADELPHIA, PA 19127
www.saltdesignstudio.com

CIVIL ENGINEERING:
MELIORA DESIGN
259 MORGAN STREET
PHOENIXVILLE, PA 19460
www.melioradesign.com

ARCHITECTURE:
IAN SMITH DESIGN GROUP
322 E. THOMPSON STREET
PHILADELPHIA, PA 19125
www.is-dg.com

LIGHTING DESIGN:
MILLER DESIGN GROUP
www.millerdesigngrouplighting.com

MEP DESIGN:
MARK ULTRICK ENGINEERS, INC.
622 COOPER STREET, #200
CAMDEN, NJ 08102
www.markultrick.com

STRUCTURAL ENGINEERING:
D'HUY ENGINEERING, INC.
1 EAST BROAD STREET, SUITE 310
BETHLEHEM, PA 18018
www.dhuy.com

DRAWING PHASE:
ISSUE FOR BIDDING


SCALE:
AS NOTED

DATE: 08/15/2022
DRAWN BY:
CHECKED BY:

SHEET NUMBER:
A0.10

SALT DESIGN STUDIO FILE NO.:
2003

CONSTRUCTION DOCUMENTS



- GENERAL INTERIOR PROPOSED WORK NOTES**
1. ALL ROOMS BESIDES MECHANICAL AND STORAGE SPACES TO RECEIVE NEW WALL BASE, NEW WALL PAINT, AND NEW FLOOR FINISH.
 2. ALL DOORS TO RECEIVE PANIC HARDWARE AND ILLUMINATED EGRESS SIGNAGE AS REQUIRED BY CODE.
 3. ALL INTERIOR LIGHTING TO BE UPGRADED. REFER TO LIGHTING DRAWINGS FOR LIGHTING LAYOUT AND FIXTURE TYPES.
 4. SEE DRAWING A0.01 FOR PARTITION TYPES.
 5. SEE DRAWING A0.10 FOR FIRE EXTINGUISHER LOCATIONS.
 6. TEST ALL OPERABLE WINDOWS IN MULTI-PURPOSE ROOM FOR FUNCTIONALITY.
 7. PATCH ALL WALLS, FLOORS, AND CEILINGS WHERE MECHANICAL BASEBOARD HEATERS HAVE BEEN DEMOLISHED.

- SYMBOL NOTES**
- (A) PROVIDE 3/4" WOOD SILL AT CMU WINDOW SILL WITH 1/2" OVERHANG EDGE. FINISH WITH WOOD STAIN. SEE 12/A9.02.
 - (B) MASONRY INFILL EXISTING ALUMINUM INTAKE GRILLE LOCATION.
 - (C) EXISTING OPERABLE WINDOW TO REMAIN. VERIFY PROPER OPERATION. CLEAN WINDOW.
 - (D) EXISTING FIXED WINDOW TO REMAIN. CLEAN WINDOW.
 - (E) EXISTING OPERABLE WINDOW TO REMAIN. REPAIR BROKEN WINDOW PANE. CLEAN WINDOW.
 - (F) EXISTING OPERABLE WINDOW TO REMAIN. VERIFY PROPER OPERATION. CLEAN WINDOW. ADD PRIVACY FILM.
 - (G) PROPOSED NEW FIXED WINDOW. SEE SCHEDULES.
 - (H) PROVIDE NEW INTAKE / EXHAUST LOUVER.

PROPOSED FLOOR PLAN
SCALE: 1/4" = 1'-0"



REV	DATE	DESCRIPTION

SCALE:
AS NOTED

DATE: 08/15/2022 DRAWN BY:
CHECKED BY:





SHEET NUMBER:

A1.00

CONSTRUCTION DOCUMENTS



HATCH LEGEND

-  PERFORATED METAL CANOPY PM-1
-  FLAT TRUSS ROOF W/ 3-PLY SBS MODIFIED BITUMEN
-  SLOPED STANDING SEAM ROOF SS-1
-  FOOTPRINT OF BUILDING BELOW

HATCH INDICATES EXTENT OF GABLED ROOF AREA WHERE ROOFING MEMBRANE TO BE REPLACED WITH STANDING SEAM METAL ROOFING ASSEMBLY SS-1

LOW-PROFILE PAD-TYPE SNOW GUARDS TO BE PROVIDED AT THIS EDGE. (1) PER SEAM, CLAMP TO SEAMS, STAGGERED PLACEMENT

RESET BENT / DAMAGED ROOF FLASHING, ESPECIALLY AT ENDS, 40 LF

EXG. SLOPE 6'/FT

REPLACE MISSING ROOF DRAIN COVER

EXG. SLOPE 6'/FT

REPAIR DAMAGED ROOF, INVESTIGATE FOR DECKING DAMAGE

EXG. SLOPE 6'/FT

EXG. SLOPE 6'/FT

EXG. SLOPE 6'/FT

EXG. SLOPE 6'/FT

EXG. SLOPE 6'/FT

EXG. SLOPE 6'/FT

LOW-PROFILE PAD-TYPE SNOW GUARDS TO BE PROVIDED AT THIS EDGE. (1) PER SEAM, CLAMP TO SEAMS, STAGGERED PLACEMENT

LOW-PROFILE PAD-TYPE SNOW GUARDS TO BE PROVIDED AT THIS EDGE. (1) PER SEAM, CLAMP TO SEAMS, STAGGERED PLACEMENT

RESET BENT / DAMAGED ROOF FLASHING, ESPECIALLY AT ENDS, 40 LF

EXG. SLOPE 6'/FT

REPLACE MISSING ROOF DRAIN COVER

EXG. SLOPE 6'/FT

REPAIR DAMAGED ROOF, INVESTIGATE FOR DECKING DAMAGE

EXG. SLOPE 6'/FT


EXG. SLOPE 6'/FT

EXG. SLOPE 6'/FT

EXG. SLOPE 6'/FT

EXG. SLOPE 6'/FT

EXG. SLOPE 6'/FT




GENERAL ROOF PROPOSED WORK NOTES

1. INVESTIGATE ALL ROOF SURFACES FOR LOCATIONS OF WATER INTRUSION OR DAMAGE. REPLACE DAMAGED DECKING WHERE DISCOVERED.
2. CLEAR ALL GUTTER AND DOWNSPOUT OBSTRUCTIONS.
3. ENTIRE ROOF TO RECEIVE NEW REPLACEMENT ROOFING MEMBRANE. 3-PLY SBS MODIFIED BITUMEN.
- 3A. INSTALL NEW LIGHT ROOF SUPER STRUCTURE TO CORRECT SLOPING AND DRAINING SYSTEM IF THE ENTIRE BUILDING STRUCTURE IS TO SUSTAIN AN ADDITIONAL (20) YEARS OF USE. THE CURRENT CAPACITY FOR ROOF DRAINAGE IS UNDER SIZED AND POORLY SLOPED FOR DIRECTING STORM WATER TO (1 OF 2) INTERNAL ROOF DRAIN LOCATIONS.
4. REMOVE AND PATCH ALL UNUSED AND ABANDONED PLUMBING VENTS AND PENETRATIONS.



HATCH INDICATES EXTENT OF FLAT ROOF AREA WHERE EXISTING DAMAGED CONTINUOUS TIMBER LAMINATED WOOD STRUCTURE AND BITUMINOUS MEMBRANE TO BE REPLACED WITH ENGINEERED WOOD TRUSS FRAMING, 3/4" PLYWOOD DECKING, AND WATERPROOFING MEMBRANE TO BE 3-PLY SBS MODIFIED BITUMEN.

1 PROPOSED ROOF PLAN
SCALE: 1/4" = 1'-0"

2 SECURITY EQUIPMENT CAGE DETAIL PLAN
SCALE: 1/4" = 1'-0"




3 SECURITY EQUIPMENT CAGE DETAIL ELEVATIONS
SCALE: 1/4" = 1'-0"




REV	DATE	DESCRIPTION


CONSTRUCTION DOCUMENTS




1 | STANDING SEAM - GUTTER EDGE
DETAIL SECTION
SCALE: 3" = 1'-0"




2 | STANDING SEAM - PEAK EDGE
DETAIL SECTION
SCALE: 3" = 1'-0"




3 | STANDING SEAM - VENTED RIDGE
DETAIL SECTION
SCALE: 3" = 1'-0"




4 | STANDING SEAM - VALLEY
DETAIL SECTION
SCALE: 3" = 1'-0"




5 | STANDING SEAM - FASCIA EDGE
DETAIL SECTION
SCALE: 3" = 1'-0"




6 | STANDING SEAM - MASONRY RAKE
DETAIL SECTION
SCALE: 3" = 1'-0"



7 | STANDING SEAM TO BITUMINOUS ROOFING TRANSITION
DETAIL SECTION
SCALE: 3" = 1'-0"



7 | BITUMINOUS ROOFING - GUTTER EDGE
DETAIL SECTION
SCALE: 3" = 1'-0"



8 | BITUMINOUS ROOFING - EDGE
DETAIL SECTION
SCALE: 3" = 1'-0"

CLIENT:
 PHILADELPHIA PARKS & RECREATION
 Rebuild PHILADELPHIA

PROJECT NAME & ADDRESS:
ZIEHLER PLAYGROUND & RECREATION CENTER
 200-64 E. OLNEY AVENUE
 PHILADELPHIA, PA 19120

PROJECT NUMBER:
16640E-01-02

PRIME CONSULTANT (LANDSCAPE ARCHITECTURE):
SALT DESIGN STUDIO
 LANDSCAPE ARCHITECTURE
 PLANNING & URBAN DESIGN
 161 LEVERINGTON AVE, SUITE 1005
 PHILADELPHIA, PA 19127
 www.saltdesignstudio.com

CIVIL ENGINEERING:
MELIORA DESIGN
 259 MORGAN STREET
 PHOENIXVILLE, PA 19460
 www.melioradesign.com

ARCHITECTURE:
IAN SMITH DESIGN GROUP
 322 E. THOMPSON STREET
 PHILADELPHIA, PA 19125
 www.is-dg.com

LIGHTING DESIGN:
MILLER DESIGN GROUP
 www.millerdesigngrouplighting.com

MEP DESIGN:
MARK ULTRICK ENGINEERS, INC.
 622 COOPER STREET, #200
 CAMDEN, NJ 08102
 www.markultrick.com

STRUCTURAL ENGINEERING:
D'HUY ENGINEERING, INC.
 1 EAST BROAD STREET, SUITE 310
 BETHLEHEM, PA 18018
 www.dhuy.com

DRAWING PHASE:
ISSUE FOR BIDDING

REGISTERED ARCHITECT
 IAN SMITH

SHEET TITLE:
EXISTING BUILDING PROPOSED ROOF DETAILS

REV	DATE	DESCRIPTION

SCALE:
 AS NOTED

DATE: 08/15/2022 DRAWN BY:
 CHECKED BY:

SHEET NUMBER:
A1.02

SALT DESIGN STUDIO FILE NO:
 2003

CONSTRUCTION DOCUMENTS




CEILING FINISH LEGEND

- PROPOSED GYPSUM BOARD
- EXISTING GYPSUM BOARD / PLASTER TO REMAIN
- EXISTING UNDERSIDE OF DECK / STRUCTURE

GENERAL PROPOSED WORK NOTES

1. INSTALLATION OF PROPOSED GYPSUM BOARD CEILINGS MAY REQUIRE ADDITIONAL STEEL STUD FRAMING. ANCHOR PROPOSED STUD FRAMING TO EXISTING CMU AND/OR EXISTING/PROPOSED ROOF DECK STRUCTURE.



PROPOSED REFLECTED CEILING PLAN
SCALE: 1/4" = 1'-0"



REV	DATE	DESCRIPTION


SCALE:
AS NOTED

DATE: 08/15/2022	DRAWN BY:
SHEET NUMBER:	CHECKED BY:




PAINT LEGEND

- BRICK/CMU; PNT-6
- BRICK/CMU; PNT-7



1 PROPOSED
EAST ELEVATION
SCALE: 1/4" = 1'-0"



2 PROPOSED
SOUTH ELEVATION
SCALE: 1/4" = 1'-0"

GENERAL EXTERIOR PROPOSED WORK NOTES

1. ALL EXISTING AND PROPOSED MASONRY SURFACES TO RECEIVE PRIMER, PAINT AND ANTI-GRAFFITI COATING.
2. ALL EXISTING METAL FRAMING SURFACES TO RECEIVE PRIMER AND PAINT, PNT-8 TYPICAL.
3. ALL EXISTING AND PROPOSED DOORS AND FRAMES TO RECEIVE PRIMER AND PAINT. EXISTING STAINLESS SURFACES TO REMAIN UNFINISHED (FLASHING, FASCIA, SOFFIT PANELS, AND GUTTERS).



EXISTING BUILDING PROPOSED BUILDING ELEVATIONS

REV DATE DESCRIPTION

REV	DATE	DESCRIPTION

SCALE:
AS NOTED

DATE: 08/15/2022 DRAWN BY:
CHECKED BY:


SHEET NUMBER:

A2.00




PAINT LEGEND


- BRICK/CMU: PNT-6
- BRICK/CMU: PNT-7



1 PROPOSED
WEST ELEVATION
SCALE: 1/4" = 1'-0"



2 PROPOSED
NORTH ELEVATION
SCALE: 1/4" = 1'-0"





SHEET TITLE:
EXISTING BUILDING PROPOSED BUILDING ELEVATIONS

REV	DATE	DESCRIPTION


SCALE:
AS NOTED

DATE: 08/15/2022	DRAWN BY:
SHEET NUMBER:	CHECKED BY:


A2.01



1 PROPOSED SECTION LOOKING SOUTH
SCALE: 1/4" = 1'-0"



2 PROPOSED SECTION LOOKING SOUTH
SCALE: 1/4" = 1'-0"



3 PROPOSED SECTION LOOKING WEST
SCALE: 1/4" = 1'-0"

GENERAL NOTES:
1. (E) INDICATES EXISTING ITEM.
(P) INDICATES PROPOSED ITEM.



SHEET TITLE:
EXISTING BUILDING PROPOSED BUILDING SECTIONS

REV	DATE	DESCRIPTION

SCALE:
AS NOTED

DATE: 08/15/2022 DRAWN BY:
CHECKED BY:

SHEET NUMBER:

A3.00

CONSTRUCTION DOCUMENTS



DOOR SCHEDULE

DOOR #	ROOM NAME	DOOR			FRAME		H'WARE SET	LOCK SET	RATING	UNDERCUT
		TYPE	MAT'L	SIZE	TYPE	MAT				
GROUND FLOOR										
00	VESTIBULE	[2]FG	IHM	(2)36" x 84"	F1	IHM	HW1	LS1 / LS2 / LS3	-	
01	GYM	EXIST	EXIST	EXIST	EXIST	EXIST	HW6	LS1 / LS3	EXIST	
02	MEN'S TOILET ROOM	EXIST	EXIST	EXIST	EXIST	EXIST	HW5	LS1 / LS2 / LS3	EXIST	
03	WOMEN'S TOILET ROOM	EXIST	EXIST	EXIST	EXIST	EXIST	HW5	LS1 / LS2 / LS3	EXIST	
04	CORRIDOR	FG	W	36" x 84"	F2	HM	HW6B	LS1 / LS2	-	
04A	CORRIDOR	EXIST	EXIST	EXIST	EXIST	EXIST	HW2	LS1 / LS2	EXIST	
05	STAFF OFFICE	EXIST	EXIST	EXIST	EXIST	EXIST	HW6A	LS1	EXIST	
05A	CLOSET	EXIST	EXIST	EXIST	EXIST	EXIST	HW4	LS1	EXIST	
06	JANITOR CLOSET	EXIST	EXIST	EXIST	EXIST	EXIST	HW4	LS1 / LS2	EXIST	REQUIRED [EXISTING]
07	UNISEX TOILET	EXIST	EXIST	EXIST	EXIST	EXIST	HW5A	LS1 / LS2	EXIST	REQUIRED [EXISTING]
08	MULTIPURPOSE ROOM	FG	W	36" x 84"	F3	HM	HW6B	LS1 / LS2	-	
08A	MULTIPURPOSE ROOM	EXIST	EXIST	EXIST	EXIST	EXIST	HW2	LS1 / LS2	EXIST	
09	KITCHEN	EXIST	EXIST	EXIST	EXIST	EXIST	HW6	LS1 / LS2	EXIST	
09A	STORAGE	EXIST	EXIST	EXIST	EXIST	EXIST	HW4	LS1	EXIST	
10	LOUNGE	EXIST	EXIST	EXIST	EXIST	EXIST	HW6	LS1*	EXIST	
10A	LOUNGE	EXIST	EXIST	EXIST	EXIST	EXIST	HW7	LS1*	EXIST	
11	STORAGE	EXIST	EXIST	EXIST	EXIST	EXIST	HW4	LS1	EXIST	
12	STORAGE ROOM	EXIST	EXIST	EXIST	EXIST	EXIST	HW4	LS1	EXIST	REQUIRED [EXISTING]
13	MECHANICAL ROOM	EXIST	EXIST	EXIST	EXIST	EXIST	HW4	LS1	EXIST	
13A	MECHANICAL ROOM	EXIST	EXIST	EXIST	EXIST	EXIST	HW3	LS1	EXIST	

NOTES:

- DOOR HARDWARE TO BE DETERMINED BY OWNER.
- DOOR FINISH DETAILS AND FINISH SPECIFICATIONS TO BE DETERMINED BY OWNER.
- DOOR FRAME DETAILS TO BE DETERMINED BY OWNER.

KEY:

- HM - HOLLOW METAL
- IHM - INSULATED HOLLOW METAL
- W - WOOD










HARDWARE SETS

- HW1 - DOUBLE EGRESS FUNCTION**
KEY LOCKABLE OUTSIDE
KEY LOCKABLE INSIDE
ALLOW PANIC BAR LOCK OVERRIDE FROM INSIDE
- HW2 - SINGLE EGRESS FUNCTION**
KEY LOCKABLE OUTSIDE
KEY LOCKABLE INSIDE
ALLOW PANIC BAR LOCK OVERRIDE FROM INSIDE
- HW3 - EXTERIOR DOOR FUNCTION**
KEY LOCKABLE OUTSIDE
KEY LOCKABLE INSIDE
ALLOW PASSAGE LOCK OVERRIDE FROM INSIDE
- HW4 - STORAGE ROOM FUNCTION**
KEY LOCKABLE OUTSIDE
ALLOW PASSAGE LOCK OVERRIDE FROM INSIDE
- HW5 - TOILET ROOM FUNCTION**
KEY LOCKABLE OUTSIDE
ALLOW PASSAGE LOCK OVERRIDE FROM INSIDE
- HW5A - TOILET ROOM FUNCTION (SINGLE)**
KEY LOCKABLE OUTSIDE
TURN LOCK INSIDE
ALLOW PASSAGE LOCK OVERRIDE FROM INSIDE
- HW6 - CLASSROOM FUNCTION**
KEY LOCKABLE OUTSIDE
KEY LOCKABLE INSIDE
ALLOW PASSAGE LOCK OVERRIDE FROM INSIDE
- HW6A - OFFICE FUNCTION**
KEY LOCKABLE OUTSIDE
TURN LOCK INSIDE
ALLOW PASSAGE LOCK OVERRIDE FROM INSIDE
- HW6B - CORRIDOR EGRESS FUNCTION**
KEY LOCKABLE OUTSIDE
KEY LOCKABLE INSIDE
ALLOW PANIC BAR OVERRIDE FROM INSIDE
- HW7 - DOUBLE DOOR CLASSROOM FUNCTION**
KEY LOCKABLE OUTSIDE
KEY LOCKABLE INSIDE
ALLOW PASSAGE BAR OVERRIDE FROM INSIDE


LOCK SETS

- LS1 - MASTER / STAFF KEY
 - LS2 - PUBLIC / MULTI-PURPOSE ROOM AREA ACCESS KEY
 - LS3 - PUBLIC / GYM AREA ACCESS KEY
- *LOUNGE LS2 ACCESS TO BE DETERMINED BY PPR


FRAME TYPES




DOOR TYPES



WINDOW TYPES



LOUVER TYPES



WINDOW NOTES:


- ALL GLAZING SHALL BE TESTED IN ACCORDANCE WITH CPSC 16 CFR 1201.
- ALL GLAZING MUST PASS THE IMPACT TEST REQUIREMENTS AT 2406.2.
- SPECIFICATION SHEETS HAVE BEEN PROVIDED FOR THE WINDOW TYPES. THE SHEET IS A GENERAL SHEET THAT ADDRESSES THE MAXIMUM SIZE WINDOW TESTED. IT IS IN THE LOWER SECTION OF THE PROVIDED SECTION OF THE PROVIDED SHEET WITH THE HEADING A:AAA/WDMA/CSA 101/LS.2/A440 PER 2009 INTERNATIONAL BUILDING CODE (IBC) SECTION 1405.13 AND 1715.5.1.

- GLASS TYPE - 1:
- A. GLASS: PROVIDE MANUFACTURER'S STANDARD INSULATED GLASS (3/4" OVERALL). GLAZING SEAL IS SILICONE BEDDING ON EXTERIOR SURFACES AND GLAZING SEAL ON THE INTERIOR OF THE PANEL. ALL GLASS TO COMPLY WITH SAFETY GLAZING REQUIREMENTS OF ANSI Z97.1 AND CPSC 16CFR 1201.
 - 1. LOW-E 272 (ARGON FILLED)
 - 2. CLEAR INSULATED.




REV	DATE	DESCRIPTION


CONSTRUCTION DOCUMENTS




2 #02 MEN'S ROOM - WEST
DETAIL ELEVATION
SCALE: 1/2" = 1'-0"




3 #02 MEN'S ROOM - NORTH
DETAIL ELEVATION
SCALE: 1/2" = 1'-0"




4 #02 MEN'S ROOM - EAST
DETAIL ELEVATION
SCALE: 1/2" = 1'-0"




5 #02 MEN'S ROOM - SOUTH
DETAIL ELEVATION
SCALE: 1/2" = 1'-0"




6 #03 WOMEN'S ROOM - WEST
DETAIL ELEVATION
SCALE: 1/2" = 1'-0"




7 #03 WOMEN'S ROOM - NORTH
DETAIL ELEVATION
SCALE: 1/2" = 1'-0"



8 #03 WOMEN'S ROOM - EAST
DETAIL ELEVATION
SCALE: 1/2" = 1'-0"




9 #03 WOMEN'S ROOM - SOUTH
DETAIL ELEVATION
SCALE: 1/2" = 1'-0"



10 TYPICAL ADA MOUNTING
DETAIL ELEVATION
SCALE: 1/2" = 1'-0"

GENERAL TOILET ROOM PROPOSED WORK NOTES
1. SEE MEP DRAWINGS FOR TOILET ROOM PLUMBING FIXTURES.
2. SEE MEP DRAWINGS FOR WALL MOUNTED HAND DRYERS.




1 PROPOSED TOILET ROOM
DETAIL PLAN
SCALE: 1/2" = 1'-0"

TOILET ROOM ACCESSORIES SCHEDULE

NUMBER #	DESCRIPTION
1	GRAB BAR 18" SIDE VERTICAL MOUNT (GB-1)
2	GRAB BAR 36" REAR MOUNT (GB-2)
3	GRAB BAR 42" SIDE MOUNT (GB-3)
4	SURFACE-MOUNTED TOILET TISSUE DISPENSER (ITD)
5	18" X 30" MIRROR UNIT (MU)
6	UNDERLAVATORY PROTECTIVE PIPE GUARD (PG)
7	TOWEL PIN (TP)
8	SURFACE-MOUNTED LIQUID SOAP DISPENSER (SD)
9	SURFACE-MOUNTED HAND DRYER (HD)
10	SEMI-RECESSED WASTE RECEPTACLE (WR)

CLIENT: PHILADELPHIA PARKS & RECREATION
Rebuild PHILADELPHIA
 PROJECT NAME & ADDRESS: ZIEHLER PLAYGROUND & RECREATION CENTER
 200-64 E. OLNEY AVENUE PHILADELPHIA, PA 19120
 PROJECT NUMBER: 16640E-01-02
 PRIME CONSULTANT (LANDSCAPE ARCHITECTURE): SALT DESIGN STUDIO
 161 LEVERINGTON AVE, SUITE 1005 PHILADELPHIA, PA 19127
 CIVIL ENGINEERING: MELIORA DESIGN
 ARCHITECTURE: IAN SMITH DESIGN GROUP
 LIGHTING DESIGN: MILLER DESIGN GROUP
 MEP DESIGN: MARK ULTRICK ENGINEERS, INC.
 STRUCTURAL ENGINEERING: D'UY ENGINEERING, INC.
 DRAWING PHASE: ISSUE FOR BIDDING
 REGISTERED ARCHITECT PENNSYLVANIA
 PROPOSED TOILET ROOM DETAILS AND SCHEDULES
 REV DATE DESCRIPTION
 SCALE: AS NOTED
 DATE: 08/15/2022 DRAWN BY: AS NOTED
 SHEET NUMBER: A6.01
 SALT DESIGN STUDIO FILE NO.: 2003

CONSTRUCTION DOCUMENTS



- ROOM FINISH SCHEDULE LEGEND:**
- ACT ACOUSTIC CEILING TILE
 - CPT CARPET TILE
 - EX EXISTING
 - FF FITNESS FLOORING
 - GWB GYPSUM BOARD
 - PNT PAINTED
 - LVT LUXURY VINYL TILE
 - VCT VINYL COMPOSITION TILE
 - VB VINYL BASE
 - CT CERAMIC TILE
 - WD WOOD
 - SV SHEET VINYL
 - NIC NOT IN CONTRACT

- ROOM FINISHES GENERAL NOTES:**
1. ALL FINISHES SHALL BE CLASS "A".
 2. PATCH EXISTING FINISHES TO MATCH EXISTING ADJACENT FINISH WHERE AFFECTED BY WORK.
 3. COORDINATE WITH CASEWORK ELEVATIONS FOR ADDITIONAL DETAIL FOR FINISHES WHERE PROVIDED.

PROPOSED FINISHES PLAN
SCALE: 1/4" = 1'-0"

ROOM #	ROOM NAME	WALL				DOOR		FLOOR	WALL BASE	CEILING
		NORTH	EAST	SOUTH	WEST	FR.	PAN.			
GROUND FLOOR										
00	VESTIBULE	PNT-1	PNT-1	PNT-1	PNT-1	PNT-2	PNT-3/WD	VCT-1	VB-1	PNT-4
01	GYM	PNT-1/BRICK	PNT-1/BRICK	PNT-1/BRICK	PNT-1/BRICK	PNT-2	EXIST	VCT-1	VB-1	PNT-4
02	MEN'S TOILET ROOM	PNT-1/WT-1	PNT-1/WT-1	PNT-1/WT-1	PNT-1/WT-1	PNT-2	EXIST	CT-1	VB-1	PNT-4
03	WOMEN'S TOILET ROOM	PNT-1/WT-1	PNT-1/WT-1	PNT-1/WT-1	PNT-1/WT-1	PNT-2	EXIST	CT-1	VB-1	PNT-4
04	CORRIDOR	PNT-1	PNT-1	PNT-1	PNT-1	PNT-2	EXIST	VCT-1	VB-1	PNT-4
05	STAFF OFFICE	EXIST	EXIST	EXIST	EXIST	EXIST	EXIST	EXIST (VCT)	EXIST	PNT-4
05A	CLOSET	EXIST	EXIST	EXIST	EXIST	EXIST	EXIST	EXIST (VCT)	EXIST	EXIST
06	JANITOR CLOSET	EXIST	EXIST	EXIST	EXIST	EXIST	EXIST	EXIST (VCT)	EXIST	PNT-4
07	UNISEX TOILET	EXIST	EXIST	EXIST	EXIST	EXIST	EXIST	EXIST (VCT)	EXIST	PNT-4
08	MULTIPURPOSE ROOM	PNT-1	PNT-1	PNT-1	PNT-1	PNT-2	PNT-3/WD	VCT-1	VB-1	EXIST
09	KITCHEN	PNT-1	PNT-1	PNT-1	PNT-1	PNT-2	PNT-3/WD	VCT-1	VB-1	PNT-4
09A	STORAGE	EXIST	EXIST	EXIST	EXIST	EXIST	EXIST	EXIST (VCT)	EXIST	EXIST
10	LOUNGE	PNT-1	PNT-1	PNT-1	PNT-1	PNT-2	PNT-3/WD	CPT-1	VB-2	PNT-4
11	STORAGE	EXIST	EXIST	EXIST	EXIST	EXIST	EXIST	EXIST (CONC)	EXIST	EXIST
11A	STORAGE	EXIST	EXIST	EXIST	EXIST	EXIST	EXIST	EXIST (CONC)	EXIST	EXIST
12	UTILITY TOILET	EXIST	EXIST	EXIST	EXIST	EXIST	EXIST	EXIST (CONC)	EXIST	EXIST
13	MECHANICAL ROOM	EXIST	EXIST	EXIST	EXIST	EXIST	EXIST	EXIST (CONC)	EXIST	EXIST

PAINTING INSTRUCTIONS

1. ALL DUST, DIRT, RUST, SCALE, ERECTION MARKS, ETC SHALL BE REMOVED FROM METAL WORK BEFORE APPLYING PRIMER OR PAINT.
2. WOOD & METAL SURFACES TO BE FINISHED SHALL BE SANDED SMOOTH. ALL NAIL HOLES, INTERSECTIONS & JOINTS SHALL BE PUTTIED FLUSH WITH ADJOINING SURFACES.
3. WOODWORK SHALL BE SANDED BEFORE EACH COAT IS APPLIED. ALWAYS APPLY PUTTY AFTER FIRST COAT OF PAINT.
4. SPACKLE ALL DENTS, HOLES, CRACKS ETC IN GYPSUM AND/OR PLASTER WORK BEFORE APPLYING FINISH, IN EXISTING AND NEW AREAS.
5. ALL SAP WOOD & KNOTS SHALL RECEIVE A THIN COAT OF SHELLAC BEFORE PRIMING.
6. BACK PRIME ALL SURFACES THAT WILL BE CONCEALED OR INACCESSIBLE INCLUDING BUT NOT LIMITED TO MULLINS, TRIM, WOODWORK, CABINETS, ETC.
7. ALL FRAMES TO BE PAINTED WITH PAINT FINISH PNT-3
8. ALL NOTED PAINTED TRIM TO BE PAINTED WITH PAINT FINISH PNT-3

FINISH SPEC. & NOTES

1. USE ONLY PREMIUM GRADE PAINT. FILL WITH ONLY BLOCK FILLERS AND PRIME ALL SURFACES BEFORE APPLYING TWO FINISH COATS.
2. PRIME ALL NEW GWB AND PLASTER SURFACES. SPOT PRIME ALL TAPED JOINTS & SPACKLED SCREW HEADS AT GWB PRIOR TO APPLYING THE THREE SPECIFIED COATS. APPLY 2 FINISH COATS TO ALL PAINTED SURFACES.
3. PRIME AND PAINT METAL ACCESS PANELS. COLOR TO MATCH WALLS. PRIME WITH OIL BASED RUST INHIBITING F&H PRIMER. DO NOT PAINT STAINLESS STEEL PANELS.
6. DO NOT PAINT EMERGENCY DEVICES OR FIRE ENUNCIATOR PANELS.
8. PROVIDE ATTIC STOCK FOR ALL FINISHES MATERIALS INCLUDING ACT AND INCLUDING BUT NOT LIMITED TO: (1) GALLON UNOPENED CONTAINER OF EACH PAINT COLOR, 50 SQ FT MIN OF EACH VCT, 12 SQUARE YARDS OF EACH CARPET, 50 SF MIN OF ACT, 20SF OF EACH TILE (1) UNOPENED GALLON CONTAINER OF EACH PRIMER. CLEARLY LABEL ALL ATTIC STOCK TO MATCH SYMBOL LEGEND.
9. VINYL BASE IS TO BE ROLL GOODS, NO SEAMS PERMITTED.
10. PROVIDE AND INSTALL VINYL REDUCER STRIP AT JOINTS BETWEEN CARPET AND CONCRETE, CONCRETE AND VINYL, CARPET AND VINYL, ETC. COLOR TO BE SELECTED BY ARCHITECT. PROVIDE VINYL TRANSITION STRIPS BETWEEN TILE AND CARPET.
11. THE CONTRACTOR IS RESPONSIBLE FOR THE APPLICATION OF ALL SEALERS AND WAXES TO TILE, SHEET VINYL AND VCT PER MANUFACTURERS SPECIFICATIONS.
12. ALL FLOOR TILE IS TO MEET ADA COEFFICIENTS FOR FRICTION.
13. STAIN GRADE WOOD TRIM : NO KNOTS, NO FILLERS, NO VARIATION IN COLOR. ALL JOINING PIECES SHALL BE BISCUITED TOGETHER AND HAVE SIMILAR GRAIN PATTERN. IN AREAS WHERE BLOCKING CAN NOT BE INSTALLED, COUNTER SINK FASTENERS AND FILL HOLES WITH PLUGS MADE FROM SAME WOOD SPECIES AND SIMILAR GRAIN. PLUGS GRAIN SHOULD BE ORIENTED TO ALIGN WITH TRIMS GRAIN.
14. WOOD TRIM THAT IS RECEIVING POLYURETHANE WILL GET 2-COATS AND BE APPLIED PER MANUFACTURERS RECOMMENDATIONS.
15. FURNITURE AND EQUIPMENT THAT IS NOT MILLWORK (CHAIRS, TABLES, DESKS, FILES, SHELVING, COPIER) ARE TO BE PROVIDED BY OWNER, UNLESS NOTED OTHERWISE.
16. APPLIANCES (REFRIGERATOR ETC.) ARE EXISTING AND TO BE PROVIDED BY OWNER.
17. AT CASEWORK, TILE BASE IS FLUSH WITH P-LAM, A COVE AT FLOOR AND A SQUARE AT TOP. IN VESTIBULE USE BULLNOSE AT TOP, AND A SQUARE EDGE AT FLOOR. USE MANUFACTURED TILE SPECIFICALLY FOR INSIDE AND OUTSIDE CORNERS.
18. INSTALL ALL FINISH FLOORING PER MANUFACTURERS RECOMMENDATIONS. GENERAL CONTRACTOR TO PERFORM MOISTURE TESTS TO ALL NEW CONCRETE WORK PRIOR TO INSTALLING FINISH FLOORING. MOISTURE TESTS TO BE CONDUCTED PER MANUFACTURERS RECOMMENDATIONS.
19. CONCRETE SURFACE TO BE FINISHED PER FINISH FLOORING MANUFACTURER'S REQUIREMENTS.
20. USE ONLY FLOORING & ADHESIVES PROVIDED BY THE FINISH FLOORING MANUFACTURER FOR THE MATERIAL BEING INSTALLED.
21. FINAL FINISHES AND FURNISHINGS TO BE CONFIRMED BY OWNER PRIOR TO PURCHASE.

MATERIALS SCHEDULE LEGEND

SYMBOL	MATERIAL	MANUFACTURER	NOTE	SYMBOL	MATERIAL	MANUFACTURER	NOTE	SYMBOL	MATERIAL	MANUFACTURER	NOTE
[Hatching]	EXISTING VINYL TILE	EXISTING		VB-2	VINYL BASE	MFR: JOHNSONITE STYLE: 4" TRAD. VINYL TOELESS BASE COLOR: 192 TIDEWATER	FLAMESPREAD = 82 SMOKE DEVELOPMENT = 420	PNT-1	WALL PAINT (TYPICAL)	MFR: SHERWIN WILLIAMS FINISH: SEMI-GLOSS COLOR: SW6385 DOVER WHITE	FLAME SPREAD = 8
[Hatching]	VCT-1	VINYL TILE	MFR: ARMSTRONG STYLE: 12"x12" STANDARD EXCELON COLOR: FAIRE WHITE 52520	WT-1	CERAMIC WALL TILE	MFR: AMERICAN OLEAN OR EQ. STYLE: BRIGHT & MATTE, 6"x6", 3/16" COLOR: ALMOND 0087	* ROUNDED EDGES AT ALL OUTSIDE CORNERS.	PNT-2	WALL PAINT (DOOR)	MFR: SHERWIN WILLIAMS FINISH: EGGSHELL COLOR: SW6497 BLUE HORIZON	FLAME SPREAD = 8
[Hatching]	EXISTING CONCRETE	EXISTING		L-1	CASEWORK COUNTERTOP	MFR: DUPONT STYLE: CORIAN QUARTZ, MATTE COLOR: CARBON CEMENT	PASSES ASTM E-648 CLASS 1 EXCEEDS REQUIREMENT OF ASTM E SMOKE < 450	PNT-3	WALL PAINT (FRAME)	MFR: SHERWIN WILLIAMS FINISH: EGGSHELL COLOR: SW6500 OPEN SEAS	FLAME SPREAD = 8
[Hatching]	CT-1	CERAMIC FLOOR TILE	MFR: AMERICAN OLEAN OR EQ. STYLE: UNGLAZED MOSAICS, 2"x2", 3/16", COLOR: BUFF GRANITE 0A52	L-2	CASEWORK FINISHED VERTICAL FACING	SOLID HARD MAPLE, STAINED	PASSES ASTM E-648 CLASS 1 EXCEEDS REQUIREMENT OF ASTM E SMOKE < 450	PNT-4	WALL PAINT (CEILING)	MFR: SHERWIN WILLIAMS FINISH: EGGSHELL COLOR: SW6385 DOVER WHITE	FLAME SPREAD = 8
[Hatching]	CPT-1	CARPET TILE	MFR: SHAW CONTRACT STYLE: 2'X2', PURPOSE ST209, 1/4" COLOR: SKYLIGHT 08530, ASHLAR	SS-1	STANDING SEAM ROOFING	MFR: MBCI STYLE: ULTRA-DEK, 24" COLOR: HAWAIIAN BLUE		PNT-5	ACCENT WALL PAINT	MFR: SHERWIN WILLIAMS FINISH: MATTE COLOR: SW6401 INDEPENDENT GOLD	FLAME SPREAD = 8
[Hatching]				PM-1	PERFORATED METAL SCREENING	MFR: McNICHOLS; STYLE: 1634011641 PERF. METAL ROUND, CARBON STEEL, COLD ROLLED, 16GA, 3/4" ROUND ON 1" CENTERS, 51% OPEN; COLOR: PAINT PNT-8		PNT-6	EXTERIOR WALL PAINT (FIELD)	MFR: SHERWIN WILLIAMS FINISH: MATTE COLOR: SW6400 LUCENT YELLOW	FLAME SPREAD = 8
[Hatching]	CTB-1	CERAMIC TILE BASE	MFR: AMERICAN OLEAN OR EQ. STYLE: BRIGHT & MATTE, 6"x6", 3/16" COLOR: ALMOND 0087	PF-1	PRIVACY FILM	MFR: ULINE STYLE: S-18274 COLOR: FROSTED WHITE		PNT-7	EXTERIOR WALL PAINT (STRIFE)	MFR: SHERWIN WILLIAMS FINISH: MATTE COLOR: SW6401 INDEPENDENT GOLD	FLAME SPREAD = 8
[Hatching]	VB-1	VINYL BASE	MFR: JOHNSONITE STYLE: 4" TRAD. VINYL COVE BASE COLOR: 192 TIDEWATER					PNT-8	EXTERIOR WALL PAINT (FRAMES AND METALS)	MFR: SHERWIN WILLIAMS FINISH: EGGSHELL COLOR: SW6500 OPEN SEAS	FLAME SPREAD = 8

CLIENT: PHILADELPHIA PARKS & RECREATION

Rebuild PHILADELPHIA

PROJECT NAME & ADDRESS:
ZIEHLER PLAYGROUND & RECREATION CENTER
200-64 E. OLNEY AVENUE
PHILADELPHIA, PA 19120

PROJECT NUMBER:
16640E-01-02

PRIME CONSULTANT (LANDSCAPE ARCHITECTURE):
SALT DESIGN STUDIO
LANDSCAPE ARCHITECTURE
PLANNING & URBAN DESIGN
161 LEVERINGTON AVE, SUITE 1005
PHILADELPHIA, PA 19127
www.saltdesignstudio.com

CIVIL ENGINEERING:
MELIORA DESIGN
259 MORGAN STREET
PHOENIXVILLE, PA 19460
www.melioradesign.com

ARCHITECTURE:
IAN SMITH DESIGN GROUP
322 E. THOMPSON STREET
PHILADELPHIA, PA 19125
www.is-dg.com

LIGHTING DESIGN:
MILLER DESIGN GROUP
www.millerdesigngrouplighting.com

MEP DESIGN:
MARK ULTRICK ENGINEERS, INC.
622 COOPER STREET, #200
CAMDEN, NJ 08102
www.markultrick.com

STRUCTURAL ENGINEERING:
D'HUY ENGINEERING, INC.
1 EAST BROAD STREET, SUITE 310
BETHLEHEM, PA 18018
www.dhuy.com

DRAWING PHASE:
ISSUE FOR BIDDING

SEAL: [Professional Engineer Seal for Ian Smith, No. 1000000000, State of Pennsylvania]

SHEET TITLE:
EXISTING BUILDING PROPOSED FINISHES PLAN

REV	DATE	DESCRIPTION




SCALE:
AS NOTED

DATE: 08/15/2022 DRAWN BY: [Signature]
CHECKED BY: [Signature]









SHEET NUMBER:
A9.00

SALT DESIGN STUDIO FILE NO.:
2003

CONSTRUCTION DOCUMENTS



GENERAL NOTES
1. REFER TO SPEC SECTION 064100 FOR CASEWORK, TYP.



CLIENT:
FIND YOUR PATH PHILADELPHIA PARKS & RECREATION

Rebuild PHILADELPHIA

PROJECT NAME & ADDRESS:
ZIEHLER PLAYGROUND & RECREATION CENTER
200-64 E. OLNEY AVENUE
PHILADELPHIA, PA 19120

PROJECT NUMBER:
16640E-01-02

PRIME CONSULTANT (LANDSCAPE ARCHITECTURE):
SALT DESIGN STUDIO
LANDSCAPE ARCHITECTURE
PLANNING & URBAN DESIGN

161 LEVERING AVE, SUITE 1005
PHILADELPHIA, PA 19127
www.saltdesignstudio.com

CIVIL ENGINEERING:
MELIORA DESIGN
259 MORGAN STREET
PHOENIXVILLE, PA 19460
www.melioradesign.com

ARCHITECTURE:
IAN SMITH DESIGN GROUP
322 E. THOMPSON STREET
PHILADELPHIA, PA 19125
www.is-dg.com

LIGHTING DESIGN:
MILLER DESIGN GROUP
www.millerdesigngrouplighting.com

MEP DESIGN:
MARK ULRIK ENGINEERS, INC.
622 COOPER STREET, #200
CAMDEN, NJ 08102
www.markulrik.com

STRUCTURAL ENGINEERING:
D'HY ENGINEERING, INC.
1 EAST BROAD STREET, SUITE 310
BETHLEHEM, PA 18018
www.dhy.com

DRAWING PHASE:
ISSUE FOR BIDDING

SCALE:
REGISTERED ARCHITECT
IAN SMITH REGISTERED

SHEET TITLE:
EXISTING BUILDING PROPOSED MILLWORK ELEVATIONS

REV	DATE	DESCRIPTION

SCALE:
AS NOTED


DATE: 08/15/2022 DRAWN BY:
SHEET NUMBER: CHECKED BY:

A9.01


SALT DESIGN STUDIO FILE NO.:
2003

CONSTRUCTION DOCUMENTS


0' 1' 2'
1" = 1'-0"




1 DOOR BASE CABINET / DOOR WALL CABINET
DETAIL SECTION
SCALE: 1" = 1'-0"




2 DRAWER BASE CABINET / DOOR WALL CABINET
DETAIL SECTION
SCALE: 1" = 1'-0"




3 DRAWER BASE CABINET / OPEN WALL CABINET
DETAIL SECTION
SCALE: 1" = 1'-0"




4 DRAWER BASE CABINET
DETAIL SECTION
SCALE: 1" = 1'-0"




5 SINK BASE CABINET / SINK WALL CABINET
DETAIL SECTION
SCALE: 1" = 1'-0"




6 SINK BASE CABINET / OPEN SINK WALL CABINET
DETAIL SECTION
SCALE: 1" = 1'-0"




7 FRIDGE WALL CABINET
DETAIL SECTION
SCALE: 1" = 1'-0"




8 DESK SUPPORT
DETAIL SECTION
SCALE: 1" = 1'-0"



9 BOOK SHELF PARTITION
DETAIL SECTION
SCALE: 1" = 1'-0"



10 BULLETIN BOARD
DETAIL SECTION
SCALE: 1" = 1'-0"



11 #00 VESTIBULE - EAST
DETAIL ELEVATION
SCALE: 1/2" = 1'-0"

GENERAL NOTES
1. REFER TO SPEC SECTION 064100 FOR CASEWORK, TYP.

MATERIALS LEGEND		
SYMBOL	MATERIAL	MANUFACTURER
VB-1	VINYL BASE	MFGR: JOHNSONITE STYLE: 4" TRAD. VINYL COVE BASE COLOR: 192 TIDEWATER
L-1	CASEWORK COUNTERTOP	MFGR: DUPONT STYLE: CORIAN QUARTZ, MATTE COLOR: CARBON CEMENT
L-2	CASEWORK FINISHED VERTICAL FACING	SOLID HARD MAPLE, STAINED

CLIENT:
PHILADELPHIA PARKS & RECREATION
Rebuild PHILADELPHIA

PROJECT NAME & ADDRESS:
ZIEHLER PLAYGROUND & RECREATION CENTER
200-64 E. OLNEY AVENUE
PHILADELPHIA, PA 19120

PROJECT NUMBER:
16640E-01-02

PRIME CONSULTANT (LANDSCAPE ARCHITECTURE):
SALT DESIGN STUDIO
LANDSCAPE ARCHITECTURE
PLANNING & URBAN DESIGN
161 LEVERINGTON AVE, SUITE 1005
PHILADELPHIA, PA 19127
www.saltdesignstudio.com

CIVIL ENGINEERING:
MELIORA DESIGN
259 MORGAN STREET
PHOENIXVILLE, PA 19460
www.melioradesign.com

ARCHITECTURE:
IAN SMITH DESIGN GROUP
322 E. THOMPSON STREET
PHILADELPHIA, PA 19125
www.is-dg.com

LIGHTING DESIGN:
MILLER DESIGN GROUP
www.millerdesigngroup.com

MEP DESIGN:
MARK ULTRICK ENGINEERS, INC.
622 COOPER STREET, #200
CAMDEN, NJ 08102
www.markultrick.com

STRUCTURAL ENGINEERING:
D'HUY ENGINEERING, INC.
1 EAST BROAD STREET, SUITE 310
BETHLEHEM, PA 18018
www.dhuy.com

ISSUE FOR BIDDING




EXISTING BUILDING PROPOSED MILLWORK DETAILS

REV	DATE	DESCRIPTION

A9.02


CONSTRUCTION DOCUMENTS

SALT DESIGN STUDIO FILE NO.: 2003



SIGN SCHEDULE				
REF. DOOR #	SIGN TEXT	SIGN ROOM NUMBER	SIGN TYPE	PICTOGRAM
GROUND FLOOR				
01	COMMUNITY GYM	N/A	A	N/A
02	MEN'S RESTROOM	N/A	C	MALE / WHEELCHAIR
03	WOMEN'S RESTROOM	N/A	C	FEMALE / WHEELCHAIR
05	STAFF OFFICE	N/A	A	N/A
06	JANITOR	N/A	B	N/A
07	RESTROOM	N/A	D	MALE / FEMALE / WHEELCHAIR
08	COMMUNITY SPACE	N/A	A	N/A
09	KITCHEN	N/A	B	N/A
10	COMMUNITY LOUNGE	N/A	A	N/A
10A	COMMUNITY LOUNGE	N/A	A	N/A
10A (REVERSE)	COMMUNITY SPACE	N/A	A	N/A
11	STORAGE	N/A	B	N/A

SIGNAGE TYPES - 3" = 1'-0"



- SIGNAGE GENERAL NOTES:**
1. COORDINATE WITH SPEC SECTION 101423.
 2. ALL SIGNS TO FEATURE RAISED TEXT AND PICTOGRAMS WITH LIGHT CONTRASTING COLOR TO DARK BACKGROUND.
 3. ALL SIGNS TO FEATURE GRADE 2 BRAILLE.
 4. SIGN MATERIAL TO BE ACRYLIC WITH SECURITY FASTENERS.
 5. PPR TO FINALIZE ALL SIGNAGE CONTENT.




REV	DATE	DESCRIPTION

SCALE:
 AS NOTED


DATE:	08/15/2022	DRAWN BY:	
CHECKED BY:			

CONSTRUCTION DOCUMENTS



EXISTING FOUNDATION PLAN
 SCALE: 1/4" = 1'-0"


- ALL FOUNDATION DIMENSIONS SHOWN ARE ESTIMATES. FOUNDATIONS ARE NOT CURRENTLY OBSERVABLE.



NEW FOUNDATION PLAN
 SCALE: 1/4" = 1'-0"


- NEW FOUNDATION TO BEAR 36" MIN BELOW ADJACENT FINISHED GRADE.
- SOIL BEARING CAPACITY TO BE VERIFIED IN EXCESS OF 2,000 PSF BY INSPECTION FIRM OR GEOTECHNICAL CONSULTANT.

DIMENSIONS AND ELEVATIONS ARE SHOWN FOR CONVENIENCE ONLY. CONTRACTOR SHALL FIELD VERIFY AND COORDINATE WITH ARCHITECTURAL DRAWINGS ALL DIMENSIONS AND ELEVATIONS PRIOR TO FABRICATION OR START OF CONSTRUCTION.




ROOF PLAN
 SCALE: 1/4" = 1'-0"


- SEE GENERAL NOTES FOR TREATED LUMBER NOTES
- VERIFY ALL EXISTING DIMENSIONS AND CONDITIONS WITH OTHER DISCIPLINE DRAWINGS, EXISTING DIMENSIONS ARE PROVIDED FOR CONVENIENCE ONLY



1 EXIST / DEMO SECTION
 SCALE: 3/8"=1'-0"




2 SECTION
 SCALE: 3/8"=1'-0"
 COORD THE SUNSCREEN DETAILS WITH ARCH DRAWINGS AND SUNSCREEN MFR



ROOF PLAN

- SCALE: 1/4" = 1'-0"
1. ROOF TRUSSES TO BE AT 16" o.c.
 2. SEE SHEET S5 FOR GENERAL NOTES
 3. VERIFY ALL EXISTING DIMENSIONS AND CONDITIONS WITH OTHER DISCIPLINE DRAWINGS, EXISTING DIMENSIONS ARE PROVIDED FOR CONVENIENCE ONLY


DIMENSIONS AND ELEVATIONS ARE SHOWN FOR CONVENIENCE ONLY. CONTRACTOR SHALL FIELD VERIFY AND COORDINATE WITH ARCHITECTURAL DRAWINGS ALL DIMENSIONS AND ELEVATIONS PRIOR TO FABRICATION OR START OF CONSTRUCTION.







ROOF TRUSS LOADING DIAGRAM

- SCALE: 1/4" = 1'-0"
1. TRUSSES SHALL BE DESIGNED FOR THE FOLLOWING LOADS:
 - 1.1. DEAD LOAD: 30 PSF TOTAL (20 PSF T.C. / 10 PSF B.C.)
 - 1.2. SNOW LOAD: 20 PSF
 - 1.3. SNOW DRIFT LOAD AS INDICATED ON PLAN
 - 1.4. NET UPLIFT LOAD: 10 PSF

2. BRIDGING SHALL BE DESIGNED BY ROOF TRUSS DESIGNER
3. ACTUAL TRUSS SPANS AND SPLICES TO BE DETERMINED BY TRUSS DESIGNER. TRUSSES MAY SPAN ACROSS INTERIOR BEARING LINES AS CONTINUOUS OR BE DESIGNED AS SIMPLE SPANS BETWEEN SUPPORT LINES.
4. REFER TO ARCHITECTURAL DRAWINGS FOR ROOF TRUSS PROFILES. ROOF TRUSS MAY BE SLOPED UNI-DIRECTIONALLY TO CENTER, BUT ALL CROSS SLOPES TO DRAIN SHALL BE BY BUILT UP INSULATION. ROOF TRUSSES SHOULD BE AS UNIFORM AND IDENTICAL AS POSSIBLE TO SIMPLIFY DESIGN, FABRICATION AND INSTALLATION.
5. MINIMUM TRUSS SPACING IS 16" o.c. TRUSSES MAY BE SPACED UP TO 24" o.c. PROVIDED THE TRUSSES SATISFY THE REQUIRED LOADING SPECIFICATIONS.
6. ROOF SHEATHING SHALL BE 1/2" PLYWOOD.



REV	DATE	DESCRIPTION





1 SECTION
S3 SCALE: 3/4"=1'-0"

2 SECTION
S3 SCALE: 3/4"=1'-0"

3 SECTION
S3 SCALE: 3/4"=1'-0"


4 SECTION
S3 SCALE: 3/4"=1'-0"



5, 5A SECTION
S3 SCALE: 3/4"=1'-0"

6 SECTION
S3 SCALE: 3/4"=1'-0"

FIELD DRILL NEW HOLES IN EXISTING ANGLES AND BEAM TOP FLANGES AS REQ'D FOR BOLT INSTALLATION, TYPICAL



SHEET TITLE:


MAIN ROOF SECTIONS

REV	DATE	DESCRIPTION

SCALE:
AS NOTED
DATE: 08/15/2022 DRAWN BY: KCB/SGY
CHECKED BY: KCB

SHEET NUMBER:

S3




SHEET TITLE:

PLAYGROUND PLAN & DETAILS

REV	DATE	DESCRIPTION


SCALE:
 AS NOTED
 DATE: 08/15/2022
 DRAWN BY: KCB/SGY
 CHECKED BY: KCB

S4
 SALT DESIGN STUDIO FILE NO.: 2003



PARTIAL SITE PLAN - EQUIPMENT FOUNDATIONS
 SCALE: 1" = 10'-0"

- DIMENSIONS AND ELEVATIONS ARE SHOWN FOR CONVENIENCE ONLY. CONTRACTOR SHALL FIELD VERIFY AND COORDINATE WITH ARCHITECTURAL AND PLAYGROUND EQUIPMENT MANUFACTURER DRAWINGS ALL DIMENSIONS AND ELEVATIONS PRIOR TO FABRICATION OR START OF CONSTRUCTION
- (B) (EXAMPLE) DENOTES PLAYGROUND EQUIPMENT PIECE MARK. COORDINATE WITH FOUNDATION SCHEDULE THIS SHEET AND EQUIPMENT SCHEDULE ON LANDSCAPE DRAWINGS
- G.C. TO VERIFY / CONFIRM ALL EQUIPMENT FOUNDATIONS AND EMBEDDED ELEMENTS WITH MFR PRIOR TO PLACING CONCRETE
- SEE SHEET 55 FOR GENERAL CONSTRUCTION NOTES




PARTIAL SITE PLAN - LIGHTING FOUNDATIONS
 SCALE: 1" = 50'-0"

- F-3 (EXAMPLE) DENOTES FOUNDATION FOR POLE MOUNTED LIGHTING. SEE SCHEDULE FOR FOUNDATION INFORMATION
- COORD FINAL PLACEMENT WITH SITE LIGHTING DRAWINGS











FOOTING SCHEDULE - PLAYGROUND EQUIPMENT

FOOTING - NO EMBEDMENT			
MARK	LENGTH x WIDTH x DEPTH OR DIAMETER (Ø) x DEPTH	COVER (TOP OF FTG BELOW FIN. GRADE)	REINFORCING
F-1	5'-4" x 12" x 28"	10 1/2"	#4 AT 12" O.C. MAX, TOP AND BOTTOM, EACH WAY
F-2	12" Ø x 28"	10 1/2"	(4) #4 VERT w/ #3 TIES AT 12" VERT
F-4	6'-8" x 6'-8" x 28"	10 1/2"	#4 AT 12" O.C. MAX, TOP AND BOTTOM, EACH WAY
F-5	3'-4" x 3'-4" x 28"	10 1/2"	#4 AT 12" O.C. MAX, TOP AND BOTTOM, EACH WAY
F-6	2'-8" x 2'-8" x 28"	10 1/2"	#4 AT 12" O.C. MAX, TOP AND BOTTOM, EACH WAY
F-7	20" Ø x 28"	10 1/2"	(6) #4 VERT w/ #3 TIES AT 12" VERT
FOOTING - WITH EMBEDMENT			
MARK	LENGTH x WIDTH x DEPTH OR DIAMETER (Ø) x DEPTH	COVER (TOP OF FTG BELOW FIN. GRADE)	REINFORCING
F-1E	26" x 26" x 28"	10 1/2"	#4 AT 12" O.C. MAX, TOP AND BOTTOM, EACH WAY
F-2E	26" x 18" x 28"	10 1/2"	#4 AT 12" O.C. MAX, TOP AND BOTTOM, EACH WAY
F-3E	12" x 28"	10 1/2"	(4) #4 VERT w/ #3 TIES AT 12" VERT



FOOTING SCHEDULE - LIGHT POLES

FOOTING - NO EMBEDMENT			
MARK	LENGTH x WIDTH x DEPTH OR DIAMETER (Ø) x DEPTH	COVER (TOP OF FTG BELOW FIN. GRADE)	REINFORCING
F-3	24" Ø x 16'-0"	FOR LIGHT POLES OVER 20'-0" TO 55'-0" DEPTH NOTED STARTS AT FINISHED GRADE, VERIFY ADDITIONAL T.O. CONC ABOVE FINISHED GRADE w/ ARCHITECT / LIGHTING CONSULTANT	SEE 1/54 - "LIGHT POLE ROUND FTG"
	24" Ø x 8'-0"	FOR LIGHT POLES LESS THAN 20'-0" TALL DEPTH NOTED STARTS AT FINISHED GRADE, VERIFY ADDITIONAL T.O. CONC ABOVE FINISHED GRADE w/ ARCHITECT / LIGHTING CONSULTANT	SEE 1/54 - "LIGHT POLE ROUND FTG" FOR REINFORCEMENT



GENERAL NOTES

- 1. THE WORK SHOWN ON THESE DRAWINGS HAS BEEN DESIGNED IN ACCORDANCE WITH THE STRUCTURAL REQUIREMENTS OF THE PENNSYLVANIA UNIFORM CONSTRUCTION CODE (PA UCC), BASED UPON THE 2018 INTERNATIONAL BUILDING CODE (IBC) AND THE AMERICAN SOCIETY OF CIVIL ENGINEERS (ASCE) MINIMUM DESIGN LOADS FOR BUILDINGS AND OTHER STRUCTURES ASCE 7-16.

Table with 2 columns: Item, Value. Includes ROOF LIVE LOAD (20PSF), SNOW LOAD DESIGN DATA, WIND DESIGN DATA, and EARTHQUAKE DESIGN DATA.

Table with 2 columns: Item, Value. Includes WIND DESIGN DATA (BASIC WIND SPEED 112 MPH) and EARTHQUAKE DESIGN DATA (SEISMIC RISK CATEGORY II).

Table with 2 columns: Item, Value. Includes EARTHQUAKE DESIGN DATA (SEISMIC IMPORTANCE FACTOR - 1.0) and BASIC SEISMIC FORCE RESISTING SYSTEMS (UNREINFORCED MASONRY SHEAR WALLS).

- 4. THE BUILDING RENOVATIONS REPLACE A WOOD FRAMED ROOF WITH A SIMILAR WOOD FRAMED STRUCTURE, AS SUCH, DEMAND CAPACITY RATIOS REMAIN BELOW THE 98% AND 108% THRESHOLD FOR GRAVITY LOAD CARRYING ELEMENTS AND LATERAL LOAD CARRYING ELEMENTS, RESPECTIVELY. THEREFORE, DETAILED ANALYSIS OF THE EXISTING STRUCTURE IS NOT REQUIRED PER IBC CHAPTER 5.
- 5. SOME DETAILS OF THE WORK ARE SHOWN ON THE ARCHITECTURAL DRAWINGS. A CAREFUL REVIEW AND STUDY OF THESE DETAILS IS NECESSARY BEFORE THE FULL SCOPE OF THE WORK CAN BE COMPREHENDED.
- 6. STRUCTURAL MEMBERS SHOWN DEPICT SIZES AND APPROXIMATE LOCATIONS ONLY. ROOF CONFIGURATIONS, SLOPE, DIMENSIONS AND ELEVATIONS ARE TO BE VERIFIED AND COORDINATED BY THE CONTRACTOR WITH THE ARCHITECTURAL AND MECHANICAL DRAWINGS.
- 7. PRINCIPAL OPENINGS IN THE STRUCTURE AND BUILDING ENVELOPE ARE SHOWN ON THE CONTRACT DOCUMENTS. REFER TO AND COORDINATE WITH ARCHITECTURAL, MECHANICAL, ELECTRICAL, AND PLUMBING DRAWINGS FOR SLEEVES, CURBS, INLETS, ETC. NOT INDICATED ON THESE DRAWINGS. THE LOCATION OF SLEEVES OR OPENINGS IN STRUCTURAL MEMBERS SHALL BE APPROVED BY THE STRUCTURAL ENGINEER PRIOR TO INSTALLATION.
- 8. THIS STRUCTURE HAS BEEN DESIGNED TO BE SELF-SUPPORTING AND STABLE AFTER THE CONSTRUCTION OF THE BUILDING HAS BEEN COMPLETED. THE STABILITY OF THE STRUCTURE PRIOR TO COMPLETION IS SOLELY THE RESPONSIBILITY OF THE CONTRACTOR. THIS RESPONSIBILITY EXTENDS TO ALL RELATED ASPECTS OF THE CONSTRUCTION ACTIVITY INCLUDING, BUT NOT LIMITED TO, ERECTION METHODS, ERECTION SEQUENCES, TEMPORARY BRACING, FORMS, SHORING, USE OF EQUIPMENT, AND SIMILAR CONSTRUCTION PROCEDURES, UNLESS SPECIFICALLY INDICATED ON THE CONTRACT DOCUMENTS. LACK OF COMMENT ON THE PART OF THE ENGINEER WITH REGARD TO CONSTRUCTION PROCEDURES IS NOT TO BE INTERPRETED AS APPROVAL OF THOSE PROCEDURES.
- 9. JOB SITE SAFETY IS SOLELY THE RESPONSIBILITY OF THE CONTRACTOR. REVIEW OF THE CONSTRUCTION BY THE ENGINEER IS FOR CONFORMANCE WITH DESIGN ASPECTS ONLY, NOT TO REVIEW THE CONTRACTOR'S PROVISIONS FOR JOB SITE SAFETY. GUIDELINES FOR CONSTRUCTION SAFETY SHALL BE IN ACCORDANCE WITH, BUT NOT LIMITED TO, THE CONSTRUCTION INDUSTRY OSHA SAFETY AND HEALTH STANDARDS (1926 STANDARDS), AND ANY LOCAL ORDINANCES OR CODES THAT MIGHT APPLY. LACK OF COMMENT ON THE PART OF THE ENGINEER WITH REGARD TO JOB SITE SAFETY IS NOT TO BE INTERPRETED AS APPROVAL OF JOB SITE SAFETY ASPECTS.
- 10. THE STRUCTURAL DRAWINGS ARE TO BE USED IN CONJUNCTION AND COORDINATION WITH THE ARCHITECTURAL, MECHANICAL, ELECTRICAL, AND PLUMBING DRAWINGS.
- 11. SPECIAL INSPECTIONS, AS REQUIRED BY THE PA UCC AND IBC, SHALL BE PERFORMED BY AN APPROVED AGENCY, IN CONTRACT WITH THE OWNER OR OWNER'S REPRESENTATIVE. THE CONTRACTOR SHALL COORDINATE THE REQUIRED SPECIAL INSPECTIONS WITH THE WORK AND SHALL NOT CONCEAL WORK UNTIL THE REQUIRED INSPECTIONS HAVE BEEN COMPLETED AND THE WORK APPROVED.
- 12. STRUCTURAL OBSERVATIONS PERFORMED BY THE ENGINEER DURING CONSTRUCTION DO NOT CONSTITUTE CONTINUOUS OR SPECIAL INSPECTION SERVICES. REQUIRED INSPECTIONS REMAIN THE RESPONSIBILITY OF THE BUILDING INSPECTOR OR TESTING AGENCY IDENTIFIED. STRUCTURAL OBSERVATIONS PERFORMED BY THE ENGINEER DO NOT CONSTITUTE SUPERVISION OF CONSTRUCTION AND DO NOT GUARANTEE THE WORK OF THE CONTRACTOR.
- 13. IT IS EACH CONTRACTOR'S RESPONSIBILITY TO PERFORM ALL WORK IN ACCORDANCE WITH THE FEDERAL, STATE, AND LOCAL LAWS, BYLAWS, ORDINANCES AND REGULATIONS IN ANY MANNER AFFECTING THE CONDUCT OF THIS WORK, AS WELL AS ALL ORDERS OR DECREES WHICH HAVE BEEN PROMULGATED OR ENACTED BY ANY LEGAL BODIES OR TRIBUNALS HAVING AUTHORITY OR JURISDICTION OVER THE WORK, MATERIALS, EMPLOYEES, OR CONTRACT.
- 14. IF FAULTY CONSTRUCTION PROCEDURES, OR MATERIAL, RESULT IN DEFECTIVE WORK THAT REQUIRES ADDITIONAL ENGINEERING TIME TO DEVISE CORRECTIVE MEASURES, PROFESSIONAL FEES MAY BE CHARGED TO THE CONTRACTOR AT THE STANDARD HOURLY RATE OF ADDITIONAL SERVICES. SUCH FEES MAY BE WITHHELD FROM THE CONTRACTORS PAYMENT. REFER TO GENERAL CONDITIONS SECTION OF THE PROJECT SPECIFICATIONS.
- 15. ALL EXISTING CONDITIONS SHALL BE FIELD VERIFIED PRIOR TO BEGINNING ANY WORK. IF EXISTING CONDITIONS DO NOT PERMIT THE INSTALLATION OF THE WORK IN ACCORDANCE WITH THE DETAILS AS SHOWN, THE CONTRACTOR SHALL NOTIFY THE ARCHITECT IMMEDIATELY AND PROVIDE AN ACCURATE SKETCH OF THE CONDITION, INCLUDING A PROPOSED MODIFICATION OR CORRECTION, FOR REVIEW AND APPROVAL.
- 16. UNLESS NOTED OTHERWISE IN THE CONTRACT DOCUMENTS, THE GENERAL CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL STRUCTURAL STEEL, MISCELLANEOUS STEEL, AND LOOSE LINTELS THAT ARE NECESSARY TO SUPPORT ALL ROOF TOP MOUNTED MECHANICAL EQUIPMENT, MASONRY WALL OPENINGS AND FLOOR AND ROOF OPENINGS. THE GENERAL CONTRACTOR IS RESPONSIBLE FOR REVIEWING ALL DRAWINGS OF ALL PRIME CONTRACTS TO DETERMINE THE QUANTITY, SIZE, AND LOCATIONS OF ALL ROOF TOP EQUIPMENT, ALL MASONRY OPENINGS, AND ALL FLOOR AND ROOF OPENINGS.
- 17. THE CONTRACTOR'S CONSTRUCTION SEQUENCES SHALL ALLOW FOR THE EFFECTS OF THERMAL MOVEMENTS DURING THE CONSTRUCTION PERIOD. PRIOR TO THE BUILDING BEING ENCLOSED AND TEMPERATURE CONTROLLED, NEGATIVE EFFECTS OF SUCH THERMAL MOVEMENTS, SUCH AS MATERIAL CRACKING, FROST HEAVE, ETC. SHALL BE CORRECTED BY THE CONTRACTOR AT NO ADDITIONAL COST TO THE OWNER.

FOUNDATION NOTES

- 1. THE FOUNDATIONS HAVE BEEN DESIGNED TO REST ON INORGANIC, UNDISTURBED SOIL HAVING AN ALLOWABLE BEARING VALUE OF 2,000 PSF. SUCH BEARING STRATA IS ANTICIPATED AT THE BOTTOM OF FOOTING ELEVATIONS NOTED ON THE FOUNDATION PLAN. ALL BEARING STRATA SHALL BE VERIFIED BY A LICENSED GEOTECHNICAL ENGINEER PRIOR TO THE PLACING OF CONCRETE IN ORDER TO VERIFY THE BEARING VALUE. THE BEARING VALUE SHOULD BE VERIFIED TO A DEPTH OF 3 TO 4 FEET BELOW BEARING ELEVATION TO ENSURE THE BEARING MATERIALS COMPLY WITH THE BORING LOGS AND DESIGN CRITERIA.
- 2. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LIMITING POURS TO MINIMIZE SHRINKAGE CRACKING. IN GENERAL, WALLS SHALL NOT BE Poured IN CONTINUOUS LENGTHS EXCEEDING 40 FEET. THE LOCATION AND CONFIGURATION OF JOINTS EXPOSED TO VIEW SHALL BE COORDINATED WITH THE ARCHITECT.
- 3. EXCAVATIONS FOR SPREAD AND CONTINUOUS FOOTINGS SHALL BE CLEANED AND HAND TAMPED TO A UNIFORM SURFACE. CONCRETE SHALL BE PLACED WITHIN 24 HOURS OF EXCAVATION OF THE FOOTING BEARING SURFACE. THE CONTRACTOR IS RESPONSIBLE FOR HAVING ALL REQUIRED INSPECTIONS, OBSERVATIONS AND TESTING COMPLETED WITHIN THAT TIMEFRAME.
- 4. ALL SOIL SURROUNDING AND UNDER FOOTINGS SHALL BE PROTECTED FROM FREEZING AND THAWING DURING THE COURSE OF CONSTRUCTION.
- 5. THE BOTTOM OF EXTERIOR FOOTINGS NOT ON SOLID ROCK SHALL BE AT MINIMUM 3'-0" BELOW GRADE.
- 6. THE INSPECTION AND TESTING OF ALL SUBGRADE AND COMPACTED EARTHWORK SHALL BE CONDUCTED UNDER THE SUPERVISION OF THE OWNER'S GEOTECHNICAL CONSULTANT. THE CONTRACTOR SHALL ADVISE THE ARCHITECT AND STRUCTURAL ENGINEER TWENTY-FOUR HOURS PRIOR TO PLACEMENT OF CONCRETE IN THE FOOTINGS. IF UNSUITABLE SUBGRADE SOILS ARE ENCOUNTERED, THE CONTRACTOR SHALL SUBMIT RECOMMENDATIONS PREPARED BY A LICENSED GEOTECHNICAL CONSULTANT TO THE STRUCTURAL ENGINEER FOR REVIEW AND APPROVAL.

CONCRETE

- 1. ALL CONCRETE WORK SHALL CONFORM TO THE REQUIREMENTS OF ACI 301 (LATEST EDITION), "SPECIFICATIONS FOR STRUCTURAL CONCRETE IN BUILDINGS" AND ACI 318 (LATEST EDITION), "BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE."
 - 2. ALL CONCRETE SHALL BE NORMAL WEIGHT CONCRETE. FOUNDATION, FOOTINGS, AND PIT BOTTOMS SHALL DEVELOP A COMPRESSIVE STRENGTH OF 4500 PSI IN 28 DAYS AND CONCRETE FOR WALLS, PIERS, SLABS ON GRADE, AND ELEVATED SLABS SHALL DEVELOP A COMPRESSIVE STRENGTH OF 4,000 PSI IN 28 DAYS.
 - 3. ALL EXTERIOR CONCRETE SHALL COMPLY WITH THE REQUIREMENTS OF ACI 318, TABLE 4.3.1 FOR EXPOSURE CLASS FI
 - 4. ALL DETAILING, FABRICATION, AND ERECTION OF REINFORCING BARS, TESTING, OR REMEDIAL WORK NECESSARY BECAUSE OF EVIDENCE OF LOW STRENGTH OR NON-CONFORMING CONCRETE OR WORKMANSHIP.
 - 6. CONTRACTOR SHALL SUBMIT STEEL REINFORCING DRAWINGS THAT DETAIL FABRICATION, BENDING AND PLACEMENT. INCLUDE BAR SIZES, LENGTHS, MATERIAL, GRADE, BAR SCHEDULES, STIRRUP SPACING, BENT BAR DIAGRAMS, BAR ARRANGEMENTS, SPLICES AND LAPS, MECHANICAL CONNECTIONS, TIE SPACING, HOOP SPACING AND SUPPORTS FOR CONCRETE REINFORCING. A 4'x4' SQUARE AREA NEAR THE TITLE BLOCK SHALL BE RESERVED FOR THE ENGINEER'S REVIEW STAMP. THE ENGINEER'S DRAWINGS MAY NOT BE REPRODUCED IN WHOLE OR PART AS A SHOP DRAWING. SHOP DRAWINGS SHALL BE CHECKED PRIOR TO SUBMITTAL. ANY DISCREPANCY FOR THE AFORESAID REQUIREMENTS SHALL BE CAUSE FOR REJECTION OF THE SUBMITTAL WITHOUT REVIEW.
 - 7. NO ADMIXTURES ARE PERMITTED WITHOUT THE ENGINEER'S WRITTEN PERMISSION OTHER THAN ENTRAINED AIR. CONCRETE EXPOSED TO THE WEATHER, SUCH AS THAT USED IN FOUNDATION WALLS, SHALL CONTAIN 4% MIN. AND 6% MAX. ENTRAINED AIR.
 - 8. REINFORCING STEEL SHALL CONFORM TO ASTM A 615, GRADE 60. EPOXY COATED REINFORCING STEEL SHALL CONFORM TO ASTM A 775, GRADE 60.
 - 4. WELDED WIRE REINFORCEMENT SHALL CONFORM TO ASTM A 185, GRADE 60. EPOXY COATED WELDED WIRE REINFORCEMENT SHALL CONFORM TO ASTM A 284, GRADE 75.
 - 10. REINFORCING STEEL SHALL CONFORM TO THE FOLLOWING DESIGNATIONS* DEFORMED BARS ASTM A615, GRADE 60 DEFORMED BARS (WELDABLE) ASTM A106
 - 11. WELDED WIRE FABRIC SHALL CONFORM TO ASTM A 185 WITH A MINIMUM YIELD STRENGTH OF 75KSI AND SHALL BE SUPPLIED IN FLAT SHEETS. LAP TWO MESHES AT SIDES AND ENDS, AND WIRE TIE TOGETHER.
 - 12. CONCRETE SLABS SHALL BE PROTECTED FROM LOSS OF SURFACE MOISTURE FOR NOT LESS THAN 7 DAYS BY USING A CURING COMPOUND CONFORMING TO ASTM C-309, BY WET BURLAP, OR A PLASTIC MEMBRANE.
 - 13. NO WELDING OF REINFORCING BARS WILL BE PERMITTED.
 - 14. GROUT SHALL BE NONSHRINKABLE GROUT CONFORMING TO ASTM C827, AND SHALL HAVE SPECIFIED COMPRESSIVE STRENGTH AT 28 DAYS OF 5000 PSI. PREROUTINGS OF BASE PLATES WILL NOT BE PERMITTED.
 - 15. MIXING, TRANSPORTING AND PLACING OF CONCRETE SHALL CONFORM TO ACI 301 (LATEST EDITION).
 - 16. MINIMUM CONCRETE COVER PROTECTION FOR REINFORCEMENT BARS SHALL BE AS FOLLOWS: (SEE ACI 318 (LATEST EDITION) SECTION 7.1 FOR CONDITIONS NOT NOTED)
- | | |
|----------------------|-------------------|
| FOOTINGS | 3 INCHES |
| SLABS ON GRADE (MAX) | 2 INCHES (TOP) |
| WALLS | 1 1/2 INCHES (1F) |
- PROVIDE STANDARD BAR CHAIRS AND SPACERS AS REQUIRED TO MAINTAIN CONCRETE PROTECTION SPECIFIED.

- 16. REINFORCEMENT DESIGNATED AS "CONTINUOUS" SHALL LAP 41 BAR DIAMETERS MINIMUM AT SPLICES, UNLESS NOTED OTHERWISE:

REBAR SIZE	LAP / SPLICE LENGTHS
#3	18"
#4	24"
#5	30"
#6	36"
#7	42"
#8	48"

- 17. HORIZONTAL FOOTING AND HORIZONTAL WALL REINFORCEMENT SHALL BE CONTINUOUS AND SHALL HAVE 90 DEGREE BENDS AND EXTENSIONS, OR CORNER BARS OF EQUIVALENT SIZE LAPPED 44 BAR DIAMETERS, AT CORNERS AND INTERSECTIONS. NO REINFORCING OR REINFORCING SUPPORTS SHALL BE EMBEDDED INTO THE FOUNDATION SOIL. ALL REINFORCING PROJECTING FROM THE CONCRETE SHALL BE TIED TO THE FOUNDATION OR WALL REINFORCING AND FULLY SUPPORTED FROM MOVEMENT DURING CONCRETE INSTALLATION. NO "WET STICKING" OF REINFORCING IS PERMITTED.
- 18. 18. HORIZONTAL JOINTING WILL NOT BE PERMITTED IN CONCRETE CONSTRUCTION EXCEPT AS SHOWN ON THE CONTRACT DOCUMENTS. VERTICAL JOINTS SHALL OCCUR AT CENTER OF SPANS AT LOCATIONS APPROVED BY THE STRUCTURAL ENGINEER.
- 19. SLABS WITH SHRINKAGE STEEL (W/SF) SHALL HAVE CONSTRUCTION JOINTS OR CONTRACTION JOINTS AT EACH COLUMN LINE IN EACH DIRECTION. ADDITIONAL CRACK CONTRACTION JOINTS SHALL BE PROVIDED, SUCH THAT THE MAXIMUM SPACING BETWEEN CONSTRUCTION AND CRACK CONTROL JOINTS DOES NOT EXCEED 15' AND DOES NOT EXCEED A LENGTH TO WIDTH RATIO 15:1.
- 20. REPAIR CONCRETE EXHIBITING VOIDS DUE TO SNAP TIES, "HONEYCOMBS," ROCK POCKETS, AND RUNS, SPALLS OR OTHERWISE DAMAGED SURFACES WITH DRY PACK OR CEMENT GROUT, AND FINISH FLUSH WITH ADJOINING SURFACES. AT THE DISCRETION OF THE STRUCTURAL ENGINEER OR AS QUALIFIED BY LAB TESTING, EXCESSIVE HONEYCOMBS OR EXPOSED REINFORCEMENT THAT JEOPARDIZE THE DESIGN SHALL BE REMOVED AND REPLACED AT THE EXPENSE OF THE CONTRACTOR.
- 21. PROVIDE TWO (2) #3 X 4" AT ALL RE-ENTRANT CORNERS, PLACED ON THE DIAGONAL WITH 1 1/2" CLEARANCE FROM THE CORNER AND TOP OF SLAB. REFER TO DETAIL.
- 22. CONSTRUCTION JOINTS BETWEEN FOOTINGS AND PILASTERS AND SIMILAR JOINTS SHALL BE PREPARED BY ROUGHENING THE CONTACT SURFACE IN AN APPROVED MANNER TO FULL AMPLITUDE OF APPROX. 14 INCHES, LEAVING THE CONTACT SURFACE FREE AND CLEAR OF LAITANCE. REINFORCED (DOHELED) JOINTS SHALL HAVE BINDER ADDITIVE APPLIED PRIOR TO POUR.
- 23. ALL EXPOSED CORNERS SHALL BE CHAMFERED 3/4" UNLESS OTHERWISE INDICATED.
- 24. CONTRACTOR SHALL TAKE EVERY PRECAUTION TO PROTECT FINISHED SURFACES FROM STAINS OR ABRASIONS. NO FIRE SHALL BE ALLOWED IN DIRECT CONTACT WITH CONCRETE. PROVIDE ADEQUATE PROTECTION AGAINST INJURIOUS ACTION BY SUN OR WIND. FRESH CONCRETE SHALL BE THOROUGHLY PROTECTED FROM HEAVY RAIN, FLOWING WATER, AND MECHANICAL INJURY.
- 25. TOPS OF FOUNDATIONS SHALL BE TROWEL FINISHED AND SMOOTH. REFER TO DRAWINGS FOR BASE PLATE ACCOMMODATIONS.
- 26. SLUMP TESTS SHALL BE MADE PRIOR TO THE ADDITION OF PLASTICIZERS. CONCRETE FOR THE PREPARATION OF TEST CYLINDERS SHALL BE TAKEN FROM THE HOSE END FOR CONCRETE PLACED BY PUMP.
- 27. WATER SHALL NOT BE ADDED TO THE CONCRETE AT THE JOBSITE. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO COORDINATE THE REQUIREMENTS OF THE CONCRETE SUPPLIER AND REFER TO ENSURE PUMPABLE AND WORKABLE MIX WITHOUT THE ADDITION OF WATER AT THE JOBSITE. THE USE OF PLASTICIZERS, RETARDANTS AND OTHER ADDITIVES SHALL BE AT THE OPTION OF THE CONTRACTOR SUBJECT TO THE APPROVAL OF THE STRUCTURAL ENGINEER. FOLLOW THE RECOMMENDATIONS OF THE MANUFACTURER FOR PROPER USE OF RETARDANTS AND OTHER ADDITIVES. USE OF CALCIUM CHLORIDE OR OTHER CHLORIDE BEARING SALTS SHALL NOT BE PERMITTED.

PREFABRICATED WOOD TRUSS NOTES

- 1. PREFABRICATED WOOD TRUSSES SHALL BE ENGINEERED, FABRICATED, AND ERECTED IN ACCORDANCE WITH THE CURRENT EDITION OF THE "DESIGN SPECIFICATION FOR METAL PLATE CONNECTED WOOD TRUSSES" BY THE TRUSS PLATE INSTITUTE (ANSI/TPI 1n - CURRENT ED.). THE MANUFACTURERS SHALL DESIGN THE TRUSS LOADS NOTED ON THE TRUSS LOADING DIAGRAMS.
- 2. TRUSSES MUST BE DESIGNED TO CONSIDER ALL CODE REQUIRED LIVE LOAD PATTERNS.
- 3. WOOD TRUSS DESIGN AND CONSTRUCTION SHALL COMPLY WITH IBC 2018 CHAPTER 23 SECTION 2303.4, "TRUSSES."
- 4. SHOP DRAWINGS AND DESIGN CALCULATIONS BEARING THE CERTIFICATION OF A PROFESSIONAL ENGINEER REGISTERED IN THE COMMONWEALTH OF PENNSYLVANIA SHALL BE SUBMITTED TO THE PROFESSIONAL FOR APPROVAL AND SHALL CONTAIN THE FOLLOWING INFORMATION FOR EACH TYPE AND SIZE OF TRUSS ASSEMBLY TO BE PROVIDED: DETAIL OF TRUSS; SPECIES, SIZE, GRADE, AND WORKING STRESS OF LUMBER USED; CALCULATED FORCE FOR EACH MEMBER, CONNECTOR PLATE SIZES AND ORIENTATION, AND BEARING/REACTION LOADS TO THE SUPPORTING FRAMING. THE SHOP DRAWINGS SHALL ALSO INCLUDE PERMANENT BRACING PLANS AND DETAILS.
- 5. ALL LUMBER USED IN THE FABRICATION OF TRUSSES SHALL BE STRESS GRADED AND SHALL BE OF THE SPECIES, SIZE, AND GRADE SPECIFIED IN THE TRUSS DESIGN.
- 6. CONNECTOR PLATES SHALL BE STAMPED FORM 16, 18, OR 20 GAUGE, GRADE A GALVANIZED STRUCTURAL STEEL. BOTH PLATE WIDTH AND PLATE LENGTH MUST EQUAL OR EXCEED THAT SPECIFIED IN THE TRUSS DESIGN.
- 7. TRUSSES SHALL BE FABRICATED IN ACCORDANCE WITH THE TRUSS DESIGN FROM ACCURATELY CUT WOOD MEMBERS CLAMPED IN RIGID FIXTURES DURING ASSEMBLY TO INSURE TIGHT FITTING JOINTS AND UNIFORMITY IN COMPLETED TRUSS UNITS.
- 8. CONNECTOR PLATES ARE TO BE PRESSED INTO THE WOOD MEMBERS ON BOTH SIDES OF THE TRUSS AT EACH JOINT SO THAT FULL PENETRATION OF THE TEETH IS OBTAINED WITHOUT CRUSHING THE OUTER SURFACE OF THE WOOD.
- 4. TRUSSES SHALL BE INSTALLED PLUMB, ADEQUATELY BRACED, IN THE PROPER ORIENTATION, AND AT THE SPACING SPECIFIED IN THE TRUSS DESIGN.
- 10. CUTTING OF TRUSS MEMBERS OR FIELD ALTERATION OF ANY TRUSS IS NOT PERMITTED.
- 11. ALL ROOF TRUSS SPACING SHALL BE AS SHOWN ON THE DRAWINGS
- 12. THE MINIMUM GRADE AND SPECIES FOR STRUCTURAL LUMBER SHALL BE #1 SOUTHERN PINE, UNLESS NOTED OTHERWISE.
- 13. ALL ROOF TRUSSES SHALL BE ATTACHED WITH HURRICANE STRAPS.
- 14. ALL WOOD TO WOOD CONNECTIONS TO BE MADE WITH SPECIFIC APPLICATIONS OF METAL HANGERS, OR AS DETAILED, AND BE MANUFACTURED BY "SIMPSON" OR APPROVED EQUAL.
- 15. G.C. / ARCHITECT AND JOIST MFR TO COORDINATE LOCATIONS OF UTILITY DRAINS, STACKS, VENTS OR ANY ROOF PENETRATIONS w/ MEP DRAWINGS.
- 16. TRUSS MFR SHALL DETAIL/ PROVIDE ALL PERMANENT TRUSS BRACING REQUIREMENTS TO BE INSTALLED AS PART OF THE ERECTION PROCESS AND TO ACHIEVE FINAL LATERAL SYSTEM STABILITY.
- 17. TEMPORARY TRUSS BRACING SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR AND SHALL BE IN ACCORDANCE WITH THE BUILDING COMPONENT SAFETY INFORMATION: "GUIDE TO GOOD PRACTICE FOR HANDLING, INSTALLING, RESTRAINING & BRACING OF METAL PLATE CONNECTED WOOD TRUSSES." (BCSI 2008).

ROUGH CARPENTRY

- 1. ALL WOOD FRAMING SHALL CONFORM TO THE NATIONAL FOREST PRODUCTS ASSOCIATION "NATIONAL DESIGN STANDARDS FOR WOOD CONSTRUCTION".
- 2. STRUCTURAL WOOD FRAMING USED IN EXTERIOR APPLICATIONS OR IN CONTACT WITH CONCRETE, MASONRY OR STEEL SHALL BE SOUTHERN YELLOW PINE, No. 2 OR BETTER, AGG PRESERVATIVE PRESSURE TREATED WOOD.
- 3. FLUSH-FRAMED CONNECTIONS SHALL BE MADE WITH PREFABRICATED GALVANIZED STEEL HANGERS OF WIDTH AND DEPTH APPROPRIATE FOR THE SUPPORTED MEMBER. INSTALL WITH THE TYPE AND QUANTITY OF FASTENERS RECOMMENDED BY THE MANUFACTURER.
- 4. BUILT-UP MEMBERS SHALL HAVE ADJACENT PLYS NAILED TOGETHER WITH A MIN. OF TWO ROWS OF NAILS AT 1'-0" O/C (10d COMMON NAILS FOR 1 1/2" PLYS, 12d COMMON NAILS FOR 1 3/4" PLYS).
- 5. UNLESS NOTED OTHERWISE, ALL LUMBER SHALL BE NAILED IN ACCORDANCE WITH THE SPECIFIED NAILING SCHEDULE.
- 6. ROOF TRUSSES, JOISTS, AND BEAMS SHALL BE SUPPORTED Laterally AT EACH SUPPORT BY FULL DEPTH SOLID BLOCKING, EXCEPT WHERE MEMBERS ARE SUPPORTED BY A FLUSH HEADER OR NAILED TO A RIM BOARD.

PLYWOOD SHEATHING NOTES

- 1. PLYWOOD SHALL CONFORM TO U.S. PRODUCTS STANDARD PS-1 AND BEAR THE APA GRADE TRADEMARK OF THE AMERICAN PLYWOOD ASSOCIATION.
- 2. PLYWOOD SHEATHING FOR ROOFS, AND WALLS, SHALL BE APA GRADED CD WITH EXTERIOR GLUE. SHEATHING FOR WALLS SHALL BE 3/2", EXPOSURE 1. ROOF SHEATHING SHALL BE 5/8" 40/20.
- 3. PLYWOOD SHEATHING SHALL BE INSTALLED WITH THE LONG DIMENSION OF THE PANEL ACROSS SUPPORTS AND CONTINUOUS OVER TWO OR MORE SPANS.
- 4. LAY-UP ROOF PLYWOOD WITH FACE GRAIN PERPENDICULAR TO SUPPORTS, STAGGER JOINTS AND INSTALL BLOCKING AT ALL EDGES.
- 5. NAIL ROOF PLYWOOD WITH 10d COMMON NAILS AT 6" OC AT ALL EDGES AND BOUNDARIES AND AT 12" OC AT INTERMEDIATE SUPPORTS, UNLESS NOTED OTHERWISE.

POST-INSTALLED ANCHORS:

- 1. EXCEPT WHERE INDICATED ON THE DRAWINGS, POST-INSTALLED ANCHORS SHALL CONSIST OF THE FOLLOWING ANCHOR TYPES AS PROVIDED BY THE FOLLOWING:
 - a. HILTI HIT-HY CONTACT HILTI AT (800) 874-8000 FOR PRODUCT RELATED QUESTIONS.
 - b. DEWALT FASTENERS, CONTACT DEWALT AT (800) 524-3244 FOR PRODUCT RELATED QUESTIONS.
- 2. ANCHORAGE TO CONCRETE:
 - a. ADHESIVE ANCHORS FOR CRACKED AND UNCRACKED CONCRETE USE:
 - HILTI HIT-HY 200 SAFE SET SYSTEM WITH HILTI HIT-Z(R) RODS PER ICC ESR-3187.
 - HILTI HIT-HY 200 SAFE SET SYSTEM WITH HILTI HOLLOW DRILL BIT SYSTEM WITH HAS-E AND HAS-S5 THREADED RODS PER ICC ESR-3187.
 - DEWALT FURELON EPOXY WITH ASTM GRADE 36 STANDARD THREADED RODS PER ICC ESR-3248.
 - DEWALT AC208 (2) PART ADHESIVE SYSTEM FOR FAST CURE AND COLD TEMPERATURES WITH STANDARD GR36/GR18 THREADED ROD PER ICC ESR-4027.
 - a. ADHESIVE ANCHORS FOR CRACKED AND UNCRACKED CONCRETE USE:
 - HILTI HIT-HY 200 SAFE SET SYSTEM WITH HILTI HOLLOW DRILL BIT SYSTEM WITH CONTINUOUSLY DEFORMED REBAR PER ICC ESR-3187.
 - DEWALT FURELON EPOXY WITH CONTINUOUSLY DEFORMED REBAR PER ICC ESR-3248.
 - DEWALT AC208 (2) PART ADHESIVE SYSTEM FOR FAST CURE AND COLD TEMPERATURES WITH CONTINUOUSLY DEFORMED REBAR PER ICC ESR-4027.
- 4. ANCHORAGE TO HOLLOW / MULTI-WYTHE MASONRY:
 - a. ADHESIVE ANCHORS USE:
 - HILTI HIT-HY TO MASONRY ADHESIVE ANCHORING SYSTEM PER ICC ESR-3342 OR DEWALT AC100+ GOLD MASONRY ADHESIVE ANCHORING SYSTEM PER ICC ESR-2582.
 - STEEL ANCHOR ELEMENT SHALL BE HILTI HAS-E OR HAS-S5 CONTINUOUSLY THREADED ROD, CONTINUOUSLY DEFORMED STEEL REBAR, ASTM GRADE 36 STANDARD THREADED ROD, OR ASTM F543, GRADE 316 STAINLESS STEEL CONTINUOUSLY THREADED ROD.
 - THE APPROPRIATE SIZE SCREEN TUBE SHALL BE USED PER ADHESIVE MANUFACTURER'S RECOMMENDATION.
 - 5. ANCHOR CAPACITY USED IN DESIGN SHALL BE BASED ON THE TECHNICAL DATA PUBLISHED BY HILTI, DEWALT, OR SUCH OTHER METHOD AS APPROVED BY THE STRUCTURAL ENGINEER OF RECORD. SUBSTITUTION REQUESTS FOR ALTERNATE PRODUCTS MUST BE APPROVED IN WRITING BY THE STRUCTURAL ENGINEER OF RECORD PRIOR TO USE. CONTRACTOR SHALL PROVIDE CALCULATIONS DEMONSTRATING THAT THE SUBSTITUTED PRODUCT IS CAPABLE OF ACHIEVING THE PERFORMANCE VALUES OF THE SPECIFIED PRODUCT. SUBSTITUTION WILL BE EVALUATED BY THEIR HAVING AN ICC ESR SHOWING COMPLIANCE WITH THE RELEVANT BUILDING CODE FOR SEISMIC USE, LOAD RESISTANCE, INSTALLATION CATEGORY, AND AVAILABILITY OF COMPREHENSIVE INSTALLATION INSTRUCTIONS. ADHESIVE ANCHOR EVALUATION WILL ALSO CONSIDER CREEP, IN-SERVICE TEMPERATURE AND INSTALLATION TEMPERATURE.
 - 6. INSTALL ANCHORS PER THE MANUFACTURER INSTRUCTIONS, AS INCLUDED IN THE ANCHOR PACKAGING.
 - 7. THE CONTRACTOR SHALL ARRANGE AN ANCHOR MANUFACTURER'S REPRESENTATIVE TO PROVIDE ON SITE INSTALLATION TRAINING FOR ALL OF THEIR ANCHORING PRODUCTS SPECIFIED. THE STRUCTURAL ENGINEER OF RECORD MUST RECEIVE DOCUMENTED CONFIRMATION THAT ALL OF THE CONTRACTOR'S PERSONNEL WHO INSTALL ANCHORS ARE TRAINED PRIOR TO THE COMMENCEMENT OF INSTALLING ANCHORS.
 - 8. ANCHOR CAPACITY IS DEPENDANT UPON SPACING BETWEEN ADJACENT ANCHORS AND PROXIMITY OF ANCHORS TO EDGE OF CONCRETE OR MASONRY. INSTALL ANCHORS IN ACCORDANCE WITH SPACING AND EDGE CLEARANCES INDICATED ON THE DRAWINGS.
 - 4. IN ACCORDANCE WITH THE REQUIREMENTS OF ACI 318, LATEST EDITION, APPENDIX D, THE FOLLOWING MINIMUM CHARACTERISTICS MUST BE ACHIEVED, UNLESS MANUFACTURER'S DOCUMENTATION PERMITS FULLY RATED INSTALLATIONS WITH ALTERNATE CHARACTERISTICS:
 - a. ADHESIVE ANCHORS SHALL HAVE BEEN TESTED AND QUALIFIED FOR USE IN ACCORDANCE WITH ACI 355.4 AND ICC-ES AC308;
 - b. ANCHORS SHALL BE INSTALLED IN HOLES DRILLED WITH A ROTARY IMPACT DRILL OR ROCK DRILL;
 - c. CONCRETE AT TIME OF ANCHOR INSTALLATION SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH OF 2500 psi;
 - d. CONCRETE AT TIME OF ANCHOR INSTALLATION SHALL HAVE MINIMUM AGE OF 21 DAYS (ACI 318-II D2.2.2);
 - e. INSTALLATION SHALL FOLLOW MANUFACTURERS REQUIREMENTS BASED ON SUBSTRATE, INSTALLATION AND IN-SERVICE TEMPERATURES.
 - 10. EXISTING REINFORCING BARS IN THE CONCRETE STRUCTURE MAY CONFLICT WITH SPECIFIC ANCHOR LOCATIONS. UNLESS NOTED ON THE DRAWINGS THAT THE BARS CAN BE CUT, THE CONTRACTOR SHALL REVIEW THE EXISTING STRUCTURAL DRAWINGS AND SHALL UNDERTAKE TO LOCATE THE POSITION OF THE REINFORCING BARS WITH THE TYPE AND LOCATION OF THE CONCRETE ANCHORS, BY HILTI FERROSCAN, GPR, X-RAY, CHIPPING OR OTHER MEANS.
 - 11. ADHESIVE FOR REBAR AND ANCHORS SHALL HAVE BEEN TESTED IN ACCORDANCE WITH ACI 355.4 AND ICC-ES AC308 FOR CRACKED CONCRETE AND SEISMIC APPLICATIONS. DESIGN ADHESIVE BOND STRENGTH HAS BEEN BASED ON ACI 355.4 TEMPERATURE CATEGORY B WITH INSTALLATIONS INTO DRY HOLES DRILLED USING A CARBIDE DRILL BIT INTO CRACKED CONCRETE THAT HAS CURED FOR AT LEAST 21 DAYS. ADHESIVE ANCHORS REQUIRING CERTIFIED INSTALLATIONS SHALL BE INSTALLED BY A CERTIFIED ADHESIVE ANCHOR INSTALLER PER ACI 318-II D.4.2.2. INSTALLATIONS REQUIRING CERTIFIED INSTALLERS SHALL BE INSPECTED PER ACI 318-II D.4.2.4.



PROJECT NAME & ADDRESS: ZIEHLER PLAYGROUND & RECREATION CENTER

200-64 E. OLNEY AVENUE PHILADELPHIA, PA 19120

PROJECT NUMBER:

16640E-01-02

PRIME CONSULTANT / LANDSCAPE ARCHITECTURE



181 EVERINGTON AVE, SUITE 1005 PHILADELPHIA, PA 19127 www.saltdesignstudio.com

OWNER ENGINEER: MELIORA DESIGN 250 MORGAN STREET PHOENIXVILLE, PA 19460 www.melioradesign.com

ARCHITECTURE: IAN SMITH DESIGN GROUP 1417 N. 2ND STREET, #3 PHILADELPHIA, PA 19122 www.is-dg.com

LIGHTING DESIGN: MILLER DESIGN GROUP www.milledesigngrouplighting.com

MEP DESIGN: MARK ULTRICK ENGINEERS, INC. 622 COOPER STREET, #200 CAMDEN, NJ 08102 www.markultrick.com

STRUCTURAL: DHUY ENGINEERING, INC. 1 EAST BRAD STREET, SUITE 310 BETHLEHEM, PA 18018 www.dhuy.com

DRAWING PHASE:

ISSUE FOR BIDDING



SHEET TITLE:

GENERAL NOTES


REV	DATE	DESCRIPTION

SCALE: AS NOTED

DATE: 08/15/2022 DRAWN BY: KCB/SGY

CHECKED BY: KCB

SHEET NUMBER:



SITE PLAN LEGEND

- WJ 36" LIGHT BOLLARD
- WK POLE MOUNTED 8-HEAD LIGHT STRUCTURE
- WN PEDESTRIAN SCALE WALKWAY SINGLE HEAD ON 14' POLE
- WO POLE MOUNTED COURT LIGHT
- PROPOSED LOCATION OF NEW PAD MOUNTED POWER CO. TRANSFORMER
- PROPOSED LOCATION OF NEW 18"x18" FLUSH GROUND MOUNTED HAND BOX
- PROPOSED ROUTE OF NEW UNDERGROUND ELECTRICAL CONDUIT
- PROPOSED ROUTE OF NEW UNDERGROUND COMMUNICATION CONDUIT
- PROPOSED ROUTE OF NEW UNDERGROUND DUCT BANK OR DIRECT BURIAL CABLE.
- PROPOSED LOCATION OF NEW HOMERUN BACK TO PANEL. FIELD COORDINATE WITH OTHER UNDERGROUND UTILITIES AND SECONDARY CONDUIT RUNS.


GENERAL NOTES:

1. CONTRACTOR SHALL REFER TO LIGHTING DESIGNER'S DRAWINGS, "EL" SERIES FOR LOCATION OF ALL LIGHT FIXTURES, ASSOCIATED LIGHTING CONTROLS AND DESCRIPTIONS OF ALL LIGHT FIXTURES. INFORMATION SHOWN ON THIS DRAWING IS FOR POWER CIRCUITRY ONLY.
2. CONTRACTOR SHALL REFER TO STRUCTURAL DRAWINGS FOR ALL POLE FOUNDATIONS.
3. THE LOCATION OF THE TVSS SHALL BE CHOSEN TO MINIMIZE THE LEAD LENGTHS BETWEEN THE TVSS AND THE CIRCUIT BREAKER TO WHICH IT IS CONNECTED. TVSS DEVICE LEADS WHICH ARE MOUNTED EXTERNAL TO THE PANEL (ENCLOSED CIRCUIT BREAKERS), MUST BE ROUTED WITHIN A METAL CONDUIT WHEN NECESSARY (RIGID NIPPLE IF POSSIBLE), AND KEPT AS SHORT AND STRAIGHT AS POSSIBLE. WIRE SIZE FOR LEAD SHALL BE AS SPECIFIED BY MANUFACTURER, MINIMUM SIZE #10 AWG, MAXIMUM SIZE #4 AWG.
4. SURGE PROTECTIVE DEVICES SHALL BE INSTALLED NEATLY. BIND THE PHASE, NEUTRAL, AND GROUND CONDUCTORS TIGHTLY, OVER THE ENTIRE RUN, FROM THE SUPPRESSOR TO THE PANEL (ENCLOSED CIRCUIT BREAKER), AND ALWAYS USE THE SHORTEST LENGTH OF CONNECTING CABLE POSSIBLE.
5. CONNECT SURGE PROTECTOR TO THE GROUNDING SYSTEM.
6. PROVIDE NEMA 4X RATED ENCLOSURE FOR ALL OUTDOOR JUNCTION BOX APPLICATIONS.
7. CONTRACTOR SHALL BE RESPONSIBLE TO SECURING A STRUCTURAL ENGINEERED DRAWING FOR ALL POLE FOUNDATIONS. DETAILS SHOWN ON THESE PLANS ARE DIAGRAMMATIC ONLY. FIELD COORDINATE.

DRAWING NOTES:

- 1 NEW HEAVY DUTY GROUND MOUNTED HAND BOX. CONTRACTOR SHALL SIZE PER NEC. FIELD COORDINATE LOCATION WITH OTHER UNDERGROUND SITE UTILITIES.
- 2 CONTRACTOR SHALL REMOVE EXISTING UNDERGROUND ELECTRICAL SERVICE TO THE BUILDING BACK TO UTILITY CO POLE. PROVIDE 2 NEW UNDERGROUND CONDUITS PER DETAILS 'H' AND 'J' ON DRAWING EO.2. FIELD COORDINATE ROUTE WITH PECO AND OTHER SITE UTILITIES..
- 3 CONTRACTOR SHALL WIRE THIS LIGHT FIXTURE AHEAD OF ALL LOCAL SWITCHING AND TIME CLOCKS. SWITCHING FOR THIS FIXTURE SHALL BE AS DIRECTED ON THE LIGHTING DESIGNER'S DRAWINGS.
- 4 REFER TO STRUCTURAL DRAWINGS FOR BASIC POLE DETAIL.

SITE PLAN - PROPOSED LIGHTING
SCALE: 1/32"=1'-0"



SHEET TITLE:
SITE PLAN-ELECTRICAL

REV	DATE	DESCRIPTION

SCALE:
 AS NOTED
 DATE: 06/24/2022 DRAWN BY: WOJ
 SHEET NUMBER: CHECKED BY: MBW

E-0.1